MD-87026 SIGNAL GRAY W/UV

Version Number 1.0 Revision Date 01/04/2019

Page 1 of 20 Print Date 01/08/2019

SAFETY DATA SHEET

MD-87026 SIGNAL GRAY W/UV

Section 1. Identification		
GHS product identifier		MD-87026 SIGNAL GRAY W/UV
Chemical name		Mixture
CAS number	:	Mixture
Other means of identification	:	CC01066723
Product type	:	solid
Relevant identified uses of the substance or mixture and uses advised against Supplier's details : Mesa Industries		
Supplier 5 details	•	230 N 48th Avenue Phoenix, AZ 85043
		(602) 269-3199
		(002) 209-3199
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	COMBUSTIBLE DUSTS SERIOUS EYE DAMAGE - Category 1 CARCINOGENICITY - Category 1A

GHS label elements

MD-87026 SIGNAL GRAY W/UV

Version Number 1.0 Revision Date 01/04/2019



Page 2 of 20

Print Date 01/08/2019

Hazard pictograms	:	
Signal word	: D	anger
Hazard statements	C	lay form combustible dust concentrations in air. auses serious eye damage. lay cause cancer.
Precautionary statements		
General	: N	ot applicable.
Prevention	: O pi	btain special instructions before use. Do not handle until all safety recautions have been read and understood. Wear protective gloves. Vear eye or face protection. Wear protective clothing.
Response	: IF ca pi	F exposed or concerned: Get medical attention. IF IN EYES: Rinse autiously with water for several minutes. Remove contact lenses, if resent and easy to do. Continue rinsing. Immediately call a POISON ENTER or physician.
Storage		tore locked up.
Disposal		ispose of contents and container in accordance with all local, gional, national and international regulations.

Keep container tightly closed.

None known.

Supplemental label elements : Hazards not otherwise classified :

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	CC01066723

CAS number/other identifiers

Ingredient name	%	CAS number
Titanium dioxide	50 - 75	13463-67-7
Decanedioic acid, bis(2,2,6,6-tetramethyl-4-piperidinyl) ester	10 - 25	52829-07-9
Carbon black	3 - 5	1333-86-4

MD-87026 SIGNAL GRAY W/UV

Version Number 1.0 Revision Date 01/04/2019 Page 3 of 20 Print Date 01/08/2019

Quartz	0 - 0.3	14808-60-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	:	Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious,
		3/20



MD-87026 SIGNAL GRAY W/UV

Version Number 1.0 Revision Date 01/04/2019



Page 4 of 20 Print Date 01/08/2019

give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact Inhalation	:	Causes serious eye damage. Exposure to airborne concentrations above statutory or recommended	
Skin contact Ingestion	:	exposure limits may cause irritation of the nose, throat and lungs. No known significant effects or critical hazards. No known significant effects or critical hazards.	
Over-exposure signs/symptoms			
Eye contact	:	Adverse symptoms may include the following: pain watering redness	
Inhalation	:	Adverse symptoms may include the following: respiratory tract irritation coughing	
Skin contact	:	Adverse symptoms may include the following: pain or irritation redness	
Ingestion	:	blistering may occur Adverse symptoms may include the following: stomach pains	
Indication of immediate medical attention and special treatment needed, if necessary			
Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under	
Specific treatments	:	medical surveillance for 48 hours. No specific treatment.	
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the	
4/20			

MD-87026 SIGNAL GRAY W/UV

Version Number 1.0 Revision Date 01/04/2019 Page 5 of 20 Print Date 01/08/2019

rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	Use dry chemical powder. Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
Specific hazards arising from the chemical	:	May form explosible dust-air mixture if dispersed.
Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire- exposed containers cool.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note





MD-87026 SIGNAL GRAY W/UV

Version Number 1.0 Revision Date 01/04/2019	Page 6 of 20 Print Date 01/08/2019			
Environmental precautions	 of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). 			
Methods and materials for containment and cleaning up				
Small spill	: Move containers from spill area. Use spark-proof tools and explosion- proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.			
Large spill	: Move containers from spill area. Use spark-proof tools and explosion- proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.			

Section 7. Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe dust. Do not ingest. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
---------------------	---	---





Version Number 1.0 Revision Date 01/04/2019		Page 7 of 20 Print Date 01/08/2019
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Quartz	OSHA PEL 1989 (1989-03-01) TWA 0.1 mg/m3 (Calculated as Quartz) Form: Respirable dust OSHA PEL Z3 (1997-09-03) TWA 250 MPPCF / (%SiO2+5) Form: Respirable TWA 10 MG /M3 / (%SiO2+2) Form: Respirable TWA 30 MG /M3 / (%SiO2+2) Form: Total dust NIOSH REL (1994-06-01) TWA 0.05 mg/m3 Form: Respirable dust ACGIH TLV (2005-12-09) TWA 0.025 mg/m3 Form: Respirable fraction OSHA PEL (2016-06-23) TWA 0.05 mg/m3 Form: Respirable dust
Carbon black	OSHA PEL 1989 (1989-03-01) TWA 3.5 mg/m3 OSHA PEL (1993-06-30) TWA 3.5 mg/m3 NIOSH REL (1994-06-01)

MD-87026 SIGNAL GRAY W/UV

Version Number 1.0 Revision Date 01/04/2019

Page 8 of 20 Print Date 01/08/2019

		TWA 3.5 mg/m3 TWA 0.1 mgPAH/m ³ ACGIH TLV (2010-12-06) TWA 3 mg/m3 Form: Inhalable fraction
Decanedioic acid, bis(2,2,6,6- tetramethyl-4-piperidinyl) ester		None.
Titanium dioxide		OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (1996-05-18) TWA 10 mg/m3
Appropriate engineering controls	:	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection		



MD-87026 SIGNAL GRAY W/UV

Л	1ESA	
	DUSTRIES	

Version Number 1.0	Page 9 of 20
Revision Date 01/04/2019	Print Date 01/08/2019

Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products
		if a risk assessment indicates this is necessary. Considering the
		parameters specified by the glove manufacturer, check during use that
		the gloves are still retaining their protective properties. It should be
		noted that the time to breakthrough for any glove material may be
		different for different glove manufacturers. In the case of mixtures,
		consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based
		on the task being performed and the risks involved and should be
		approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures
		should be selected based on the task being performed and the risks
		involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that
		meets the appropriate standard or certification. Respirators must be
		used according to a respiratory protection program to ensure proper
		fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state	:	solid [Powder.]
Color	:	GREY
Odor	:	Not available.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n-	:	Not available.

MD-87026 SIGNAL GRAY W/UV

Version Number 1.0 Revision Date 01/04/2019

Page 10 of 20 Print Date 01/08/2019

octanol/water		
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	Dynamic: Not available.
-		Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity Chemical stability	:	No specific test data related to reactivity available for this product or its ingredients. Stable under recommended storage and handling conditions (see
Possibility of hazardous reactions	:	Section 7). Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation.
Incompatible materials	:	Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure				
Remarks - Oral:	No applicable to	No applicable toxicity data						
Remarks - Inhalation:	No applicable to	oxicity data						
Remarks - Dermal:	No applicable to	No applicable toxicity data						
Carbon black								
	LD50 Oral	Rat	15,400 mg/kg	-				
Remarks - Inhalation:	No applicable toxicity data							
Remarks - Dermal:	No applicable toxicity data							



MD-87026 SIGNAL GRAY W/UV

Version Number 1.0 Revision Date 01/04/2019 Page 11 of 20 Print Date 01/08/2019

Remarks - Oral:	No applicable to:	xicity data			
Remarks - Inhalation:	No applicable to	xicity data			
Remarks - Dermal:	No applicable to	xicity data			
Titanium dioxide					
Remarks - Oral:	No applicable to	xicity data			
	LC50 Inhalation	n Rat - M	/lale	6.82 Mg/l	4 h
	LD50 Dermal	Rabbit		> 5,000 mg/kg	-
Conclusion/Summary	: Mix	ture.Not fu	ally tested.		
Irritation/Corrosion					
Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium dioxide	Skin - Mild	Human		72 hrs	_

itanium dioxide	Skin - Mild	Human		72 hrs	-
	irritant				
Conclusion/Summary					
Skin	: M	lixture.Not full	y tested.		
Eyes		lixture.Not full			
Respiratory	: M	lixture.Not full	y tested.		
Sensitization					
Conclusion/Summary					
Skin		lixture.Not full			
Respiratory	: M	lixture.Not full	y tested.		
Mutagenicity					
Conclusion/Summary	: M	lixture.Not full	y tested.		
Carcinogenicity					
Conclusion/Summary	: M	lixture.Not full	y tested.		
Classification	OCILA	LADC	NTD		
Product/ingredient	OSHA	IARC	NTP		
name		1	Vnoum to	ha a human agraina	
Quartz		-	Known to	be a human carcino	igen.
Carbon black		2B			
Titanium dioxide		2B			

Conclusion/Summary : Mixture.Not fully tested.



MD-87026 SIGNAL GRAY W/UV

Version Number 1.0 Revision Date 01/04/2019 Page 12 of 20 Print Date 01/08/2019

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure) Not available.

Specific target organ toxicity (repeated exposure) **Product/ingredient name** Category **Route of exposure Target organs** Quartz Category 1 **Aspiration hazard** Not available. Information on likely routes of Not available. : exposure Potential acute health effects Eye contact Causes serious eye damage. : Inhalation Exposure to airborne concentrations above statutory or recommended : exposure limits may cause irritation of the nose, throat and lungs. Skin contact No known significant effects or critical hazards. : No known significant effects or critical hazards. Ingestion : Symptoms related to the physical, chemical and toxicological characteristics Eye contact : Adverse symptoms may include the following: pain watering redness Inhalation Adverse symptoms may include the following: : respiratory tract irritation coughing Adverse symptoms may include the following: Skin contact : pain or irritation redness blistering may occur Adverse symptoms may include the following: Ingestion :

Delayed and immediate effects as well as chronic effects from short and long-term exposure

stomach pains

Short term exposure



MD-87026 SIGNAL GRAY W/UV

Version Number 1.0 Revision Date 01/04/2019



Page 13 of 20

Print Date 01/08/2019

Potential immediate effects Potential delayed effects	:	Not available. Not available.
Long term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.
General	:	Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.
Carcinogenicity	:	May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	No known significant effects or critical hazards.
Developmental effects	:	No known significant effects or critical hazards.
Fertility effects	:	No known significant effects or critical hazards.

No known significant effects or critical hazards. :

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Quartz			
Remarks - Acute - Fish:	No applicable toxicity data		
Remarks - Acute - Aquatic	No applicable toxicity data		
invertebrates.:			
Remarks - Acute - Aquatic	No applicable toxicity data		
plants:			
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:			
Aquatic invertebrates.:			

MD-87026 SIGNAL GRAY W/UV

Version Number 1.0 Revision Date 01/04/2019 Page 14 of 20 Print Date 01/08/2019

Carbon black					
Remarks - Acute - Fish:	No applicable toxicity data				
	Acute EC50 37.563 Mg/l Fresh	Aquatic invertebrates.	48 h		
	water	Daphnia			
Remarks - Acute - Aquatic	Acute				
invertebrates.:					
Remarks - Acute - Aquatic	No applicable toxicity data				
plants:					
Remarks - Chronic - Fish:	No applicable toxicity data				
Remarks - Chronic -	No applicable toxicity data				
Aquatic invertebrates.:					
Decanedioic acid, bis(2,2,6,6-t	etramethyl-4-piperidinyl) ester				
Remarks - Acute - Fish:	No applicable toxicity data				
	Acute EC50 8.6 Mg/l Fresh water	Aquatic invertebrates.	48 h		
		Daphnia			
Remarks - Acute - Aquatic	Acute				
invertebrates.:					
Remarks - Acute - Aquatic	No applicable toxicity data				
plants:					
Remarks - Chronic - Fish:	No applicable toxicity data	No applicable toxicity data			
Remarks - Chronic -	No applicable toxicity data				
Aquatic invertebrates.:					
Titanium dioxide					
	Acute LC50 > 1,000 Mg/l Marine	Fish - Fish	96 h		
	water				
Remarks - Acute - Fish:	Acute				
	Acute LC50 3 Mg/l Fresh water	Aquatic invertebrates.	48 h		
		Crustaceans			
Remarks - Acute - Aquatic	Acute				
invertebrates.:			-		
	Acute LC50 6.5 Mg/l Fresh water	Aquatic invertebrates.	48 h		
		Daphnia			
Remarks - Acute - Aquatic	Acute				
invertebrates.:					
Remarks - Acute - Aquatic	No applicable toxicity data				
plants:					
Remarks - Chronic - Fish:	No applicable toxicity data				
Remarks - Chronic -	No applicable toxicity data				
Aquatic invertebrates.:					
Conclusion/Summary	: Not available.				
.					
Persistence and degradability	<u>v</u>				

Conclusion/Summary

:



MD-87026 SIGNAL GRAY W/UV

Version Number 1.0 Revision Date 01/04/2019



Page 15 of 20 Print Date 01/08/2019

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Decanedioic acid, bis(2,2,6,6-	0.35	-	low
tetramethyl-4-piperidinyl) ester			

Mobility in soil

r	:	Not available.
(KOC) Other adverse effects	:	No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods The generation of waste should be avoided or minimized wherever : possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	:	Not regulated for transportation.
International Air	:	Consult mode specific transport rules

15/20

MD-87026 SIGNAL GRAY W/UV

Version Number 1.0 Revision Date 01/04/2019

Page 16 of 20 Print Date 01/08/2019

ICAO/IATA

International Water IMO/IMDG

: Consult mode specific transport rules

Section 15. Regulatory information

U.S.	Federal	regulations
------	---------	-------------

ral regulations	: United States - TSCA 12(b) - Chemical export notification: None of the components are listed.
	United States - TSCA 4(a) - Final Test Rules: Not listed
	United States - TSCA 4(a) - ITC Priority list: Not listed
	United States - TSCA 4(a) - Proposed test rules: Not listed
	United States - TSCA 4(f) - Priority risk review: Not listed
	•
	United States - TSCA 5(a)2 - Final significant new use rules: Not listed
	United States - TSCA 5(a)2 - Proposed significant new use rules:
	Not listed
	United States - TSCA 5(e) - Substances consent order: Not listed
	United States - TSCA 6 - Final risk management: Not listed
	United States - TSCA 6 - Proposed risk management: Not listed
	United States - TSCA 8(a) - Chemical risk rules: Not listed
	United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed
	United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not
	determined
	United States - TSCA 8(a) - Preliminary assessment report
	(PAIR): Not listed
	United States - TSCA 8(c) - Significant adverse reaction (SAR):
	Not listed
	United States - TSCA 8(d) - Health and safety studies: Not listed
	United States - EPA Clean water act (CWA) section 307 - Priority
	pollutants: Listed Chromium
	Arsenic
	Nickel
	Zinc ferrite brown spinel (C.I. Pigment Yellow 119)
	Zinc stearate
	United States - EPA Clean water act (CWA) section 311 -
	Hazardous substances: Not listed
	United States - EPA Clean air act (CAA) section 112 - Accidental
	release prevention - Flammable substances: Not listed
	United States - EPA Clean air act (CAA) section 112 - Accidental
	release prevention - Toxic substances: Not listed
	United States - Department of commerce - Precursor chemical:
	Omicu States - Department of commerce - riccursor chemical;

MD-87026 SIGNAL GRAY W/UV

Version Number 1.0 Revision Date 01/04/2019



Page 17 of 20 Print Date 01/08/2019

	Not listed
:	Listed
	NT-(1)-(-1
:	Not listed
:	Not listed
	NT / 11 / 1
:	Not listed
:	Not listed
	:

US. EPA CERCLA Hazardous Substances (40 CFR 302)

:

not applicable

SARA 311/312

Classification

COMBUSTIBLE DUSTS SERIOUS EYE DAMAGE - Category 1 CARCINOGENICITY - Category 1A

Composition/information on ingredients

Name	%	Classification
Zinc stearate	>= 10 - <= 25	Fire hazard
Titanium dioxide	>= 50 - <= 75	Delayed (chronic) health hazard
Decanedioic acid, bis(2,2,6,6-tetramethyl-4- piperidinyl) ester	>= 10 - <= 25	Immediate (acute) health hazard
Carbon black	>= 3 - <= 5	Delayed (chronic) health hazard
Quartz	> 0 - <= 0.3	CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

SARA 313

	Product name	CAS number	%
Form R - Reporting	Zinc ferrite brown spinel	68187-51-9	3 - 5
requirements	(C.I. Pigment Yellow 119)		
	Zinc stearate	557-05-1	10 - 25



Version Number 1.0 Revision Date 01/04/2019



Page 18 of 20 Print Date 01/08/2019

Supplier notification	Zinc ferrite brown spinel (C.I. Pigment Yellow 119)	68187-51-9	3 - 5
	Zinc stearate	557-05-1	10 - 25

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

<u>State regulations</u> Massachusetts New York New Jersey Pennsylvania	setts : y :	None of the components are listed. None of the components are listed. The following components are listed: Quartz Carbon black Titanium dioxide Zinc ferrite brown spinel (C.I. Pigment Yellow 119) Calcium carbonate Zinc stearate The following components are listed: Titanium dioxide
		Quartz
		Carbon black
		Zinc ferrite brown spinel (C.I. Pigment Yellow 119)
		Calcium carbonate
		Zinc stearate

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, Carbon black, Quartz, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Carbon black	No.	No.
Titanium dioxide	No.	No.
Quartz	No.	No.

United States inventory (TSCA 8b) : All components are listed or exempted.

MD-87026 SIGNAL GRAY W/UV

Version Number 1.0 Revision Date 01/04/2019



Page 19 of 20

Print Date 01/08/2019

Canada inventory	:	At least one component is not listed in DSL but all such components are listed in NDSL.
International regulations		
<u>Inventory list</u>		
Australia	:	All components are listed or exempted.
Canada	:	At least one component is not listed in DSL but all such components are listed in NDSL.
China	:	All components are listed or exempted.
Europe inventory	:	All components are listed or exempted.
Japan	:	Not determined.
New Zealand	:	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	All components are listed or exempted.
Turkey	:	Not determined.
United States	:	All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	3
Flammability		3
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

THEORY		
Date of printing	:	01/08/2019
Date of issue/Date of revision	:	01/04/2019
Date of previous issue	:	00/00/0000
Version	:	1.0
Key to abbreviations	:	ATE = Acute Toxicity Estimate

MD-87026 SIGNAL GRAY W/UV

Version Number 1.0 Revision Date 01/04/2019



Page 20 of 20 Print Date 01/08/2019

BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations Not available.

References

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.