XDH/SLATE GREY

Version Number 1.3 Revision Date 04/26/2018 PolyOne.

Page 1 of 18 Print Date 05/01/2018

SAFETY DATA SHEET

XDH/SLATE GREY

Section 1. Identification	on	
GHS product identifier	:	XDH/SLATE GREY
Chemical name	:	Mixture
CAS number	:	Mixture
Other means of identification	:	CC10024112
Product type	:	solid
Relevant identified uses of the subs	stance	e or mixture and uses advised against
Product use	:	Industrial applications. Plastics.
Supplier's details	:	POLYONE CORPORATION
		33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (866) POLYONE
Emorgonov tolonhono numbor		CHEMTDEC 1 800 424 0200 (24brs for spill look fire exposure or
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or
(with hours of operation)		accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.
Classification of the substance or mixture	:	Not classified.
GHS label elements		
Signal word	:	No signal word.
		1/18

XDH/SLATE GREY

Version Number 1.3 Revision Date 04/26/2018

Page 2 of 18 Print Date 05/01/2018

Hazard statements

No known significant effects or critical hazards.

Precautionary statements

General	:	Not applicable.
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known.

Section 3. Composition/information on ingredients

:

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	CC10024112

CAS number/other identifiers

Ingredient name	%	CAS number
2-Propenenitrile, polymer with Ethenylbenzene	50 - 75	9003-54-7
Titanium dioxide	10 - 25	13463-67-7
Carbon black	3 - 5	1333-86-4
Styrene	0 - 0.3	100-42-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

XDH/SLATE GREY

Version Number 1.3 Revision Date 04/26/2018



Page 3 of 18 Print Date 05/01/2018

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	:	Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Potential acute healt	h effects
-----------------------	-----------

Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.
0		-

Over-exposure signs/symptoms

Eye contact	:	No specific data.
Inhalation	:	No specific data.
Skin contact	:	No specific data.
Ingestion	:	No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training.



XDH/SLATE GREY

Version Number 1.3 Revision Date 04/26/2018 Page 4 of 18 Print Date 05/01/2018

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or CO_2 . None known.
Specific hazards arising from the chemical	:	No specific fire or explosion hazard.
Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for contain	nent a	nd cleaning up
Small spill	:	Move containers from spill area. Vacuum or sweep up material and

<u>PolyOne</u>

XDH/SLATE GREY

Version Number 1.3 Revision Date 04/26/2018 Page 5 of 18 Print Date 05/01/2018

Large spill

place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures Advice on general occupational hygiene	:	Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

:

Control parameters

Occupational exposure limits

Exposure limits
OSHA PEL 1989 (1989-03-01)
PEL: Permissible Exposure Level 215 mg/m3 50 ppm
Short-term exposure limit (STEL). A limit value beyond which
there should be no exposure and which refers to a period of fifteen
minutes, unless otherwise stated. 425 mg/m3 100 ppm
OSHA PEL Z2 (1993-06-30)
PEL: Permissible Exposure Level 100 ppm
Ceiling-A concentration that should not be exceeded at any time
during any part of the working day. 200 ppm



XDH/SLATE GREY

Version Numbe	er 1.3
Revision Date	04/26/2018

	Acceptable Maximum Peak (AMP)600 ppmNIOSH REL (1994-06-01)Time Weighted Average (TWA) 215 mg/m350 ppmShort-term exposure limit (STEL). A limit value beyond whichthere should be no exposure and which refers to a period of fifteenminutes, unless otherwise stated. 425 mg/m3100 ppmACGIH TLV (1997-05-21)TLV-TWA: Threshold Limit Value - Time weighted average PEL:Permissible Exposure Level 85 mg/m320 ppmTLV-STEL: Threshold Limit Value - Short Time Exposure Level170 mg/m340 ppm
Carbon black	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 3.5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 3.5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 3.5 mg/m3 Time Weighted Average (TWA) ACGIH TLV (2010-12-06) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction
Titanium dioxide	OSHA PEL 1989 (1989-03-01)PEL: Permissible Exposure Level 10 mg/m3 Form: Total dustOSHA PEL (1993-06-30)PEL: Permissible Exposure Level 15 mg/m3 Form: Total dustNIOSH REL (1994-06-01)ACGIH TLV (1996-05-18)TLV-TWA: Threshold Limit Value - Time weighted average PEL:Permissible Exposure Level 10 mg/m3
2-Propenenitrile, polymer with Ethenylbenzene	
Appropriate engineering controls:Environmental exposure controls:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants. Emissions from ventilation or work process equipment should be

ronmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

XDH/SLATE GREY

Version Number 1.3 Revision Date 04/26/2018

<u>PolyOne</u>

Page 7 of 18 Print Date 05/01/2018

Individual protection measures	
Hygiene measures Eye/face protection	 Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state	:	solid [Pellets.]
Color	:	GREY
Odor	:	Faint odor.
Odor threshold	:	Not available.
pH	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.

XDH/SLATE GREY

Version Number 1.3 Revision Date 04/26/2018 PolyOne

Page 8 of 18 Print Date 05/01/2018

Evaporation rate	: Not available.	
Flammability (solid, gas)	: Not available.	
Lower and upper explosive	: Lower: Not availab	le.
(flammable) limits	Upper: Not available	ole.
Vapor pressure	: Not available.	
Vapor density	: Not available.	
Relative density	: Not available.	
Solubility	: Not available.	
Solubility in water	: insoluble in water.	
Partition coefficient: n- octanol/water	: Not available.	
Auto-ignition temperature	: Not available.	
Decomposition temperature	: Not available.	
SADT	: Not available.	
Viscosity	: Dynamic: Not avai	lable.
-	Kinematic: Not ava	ailable.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Keep away from strong acids. Oxidizer.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Styrene				
	LD50 Oral	Rat	2,650 mg/kg	-



XDH/SLATE GREY

Version Number 1.3 Revision Date 04/26/2018

Page 9 of 18 Print Date 05/01/2018

	LC50 Inhalation	Rat	2,770 ppm	4 h
	LC50 Inhalation	Rat	11.8 Mg/l	4 h
Remarks - Dermal:	No applicable toxicity data			
Carbon black				
	LD50 Oral	Rat	15,400 mg/kg	-
Remarks - Inhalation:	No applicable toxic	city data		
Remarks - Dermal:	No applicable toxic	city data		
Titanium dioxide				
	No applicable toxicity data			
Remarks - Oral:	No applicable toxic	city data		
Remarks - Oral:	No applicable toxic LC50 Inhalation	city data Rat - Male	6.82 Mg/l	4 h
Remarks - Oral:	**		6.82 Mg/l > 5,000 mg/kg	4 h -
2-Propenenitrile, polymer with	LC50 Inhalation LD50 Dermal	Rat - Male		4 h -
	LC50 Inhalation LD50 Dermal	Rat - Male		4 h -
	LC50 Inhalation LD50 Dermal Ethenylbenzene	Rat - Male Rabbit Rat	> 5,000 mg/kg	-
2-Propenenitrile, polymer with	LC50 Inhalation LD50 Dermal Ethenylbenzene LD50 Oral	Rat - Male Rabbit Rat city data	> 5,000 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Styrene	Eyes - Mild	Human			-
	irritant				
	Skin - Mild	Rabbit			-
	irritant				
	Skin -	Rabbit			-
	Moderate				
	irritant				
	Eyes - Severe	Rabbit			-
	irritant				
	Eyes -	Rabbit		24 hrs	-
	Moderate				
	irritant				
Titanium dioxide	Skin - Mild	Human		72 hrs	-
	irritant				
Conclusion/Summary					
Skin		ixture.Not ful			
Eyes		ixture.Not ful			
Respiratory	: M	ixture.Not ful	lly tested.		
Sensitization					
Conclusion/Summary			1		
Skin		ixture.Not ful			
Respiratory	: M	ixture.Not ful	lly tested.		

Mixture.Not fully tested. :

XDH/SLATE GREY

Version Number 1.3 Revision Date 04/26/2018 PolyOne.

Page 10 of 18 Print Date 05/01/2018

Mutagenicity					
Conclusion/Summary	: M	lixture.Not fully	tested.		
Carcinogenicity					
Conclusion/Summary	: M	lixture.Not fully	tested.		
Classification					
Product/ingredient	OSHA	IARC	NTP		
name					
Styrene		2B	Reasonably anticipated to be a human carcinogen.		
Carbon black		2B			
Titanium dioxide		2B	_		
2-Propenenitrile, polymer		3			
with Ethenylbenzene					
<u>Reproductive toxicity</u>					
Conclusion/Summary	: M	lixture.Not fully	tested.		
Teratogenicity					
Conclusion/Summary : Mixture.Not fully tested.					
<u>Specific target organ toxicity (single exposure)</u> Not available.					
Specific target organ toxicity (repeated exposure) Not available.					
Aspiration hazard Not available.					
Information on likely routes exposure	of : N	ot available.			
Potential acute health effects					
Eye contact	: N	o known signific	ant effects or critical hazards.		
Inhalation			ant effects or critical hazards.		
Skin contact			ant effects or critical hazards.		
Ingestion			ant effects or critical hazards.		
Sumptome valated to the physical		-			

Symptoms related to the physical, chemical and toxicological characteristics

XDH/SLATE GREY

Version Number 1.3 Revision Date 04/26/2018 Page 11 of 18 Print Date 05/01/2018

P<u>olyOne</u>

Eye contact	:	No specific data.
Inhalation	:	No specific data.
Skin contact	:	No specific data.
Ingestion	:	No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Long term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	No known significant effects or critical hazards.
Developmental effects	:	No known significant effects or critical hazards.
Fertility effects	:	No known significant effects or critical hazards.
Numerical measures of toxicity		

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Styrene			
	Acute LC50 4.02 Mg/l Fresh water	Fish - Fish	96 h
Remarks - Acute - Fish:	Acute		



XDH/SLATE GREY

Version Number 1.3 Revision Date 04/26/2018 Page 12 of 18 Print Date 05/01/2018

	Acute EC50 0.0047 Mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
Remarks - Acute - Aquatic	Acute	Dupinnu	
invertebrates.:	i louto		
	Acute LC50 52 Mg/l Marine water	Aquatic invertebrates.	48 h
		Crustaceans	
Remarks - Acute - Aquatic	Acute		
invertebrates.:		1	
	Acute EC50 1.4 Mg/l Fresh water	Aquatic plants - Algae	72 h
Remarks - Acute - Aquatic	Acute		
plants:			0.61
	Acute EC50 0.72 Mg/l Fresh water	Aquatic plants - Algae	96 h
Remarks - Acute - Aquatic	Acute		
plants:	Acute NOEC 0.063 Mg/l Fresh	Aquatic plants - Algae	96 h
	water	Aqualle plains - Algae	90 II
Remarks - Acute - Aquatic	Chronic		
plants:			
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:	11 5		
Carbon black			
Remarks - Acute - Fish:	No applicable toxicity data		
	Acute EC50 37.563 Mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
Remarks - Acute - Aquatic	Acute		
invertebrates.:			
Remarks - Acute - Aquatic	No applicable toxicity data		
plants: Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic - Fish:	No applicable toxicity data No applicable toxicity data		
Aquatic invertebrates.:	No applicable toxicity data		
Titanium dioxide			
	Acute LC50 > 1,000 Mg/l Marine	Fish - Fish	96 h
	water		
Remarks - Acute - Fish:	Acute		
	Acute LC50 3 Mg/l Fresh water	Aquatic invertebrates.	48 h
		Crustaceans	
Remarks - Acute - Aquatic	Acute		
invertebrates.:			40.1
	Acute LC50 6.5 Mg/l Fresh water	Aquatic invertebrates.	48 h
Demontra A anta A	A grade	Daphnia	
Remarks - Acute - Aquatic invertebrates.:	Acute		
invertebrates.			



XDH/SLATE GREY

Version Number 1.3 Revision Date 04/26/2018 Page 13 of 18 Print Date 05/01/2018

Remarks - Acute - Aquatic	No applicable toxicity data
plants:	
Remarks - Chronic - Fish:	No applicable toxicity data
Remarks - Chronic -	No applicable toxicity data
Aquatic invertebrates.:	
2-Propenenitrile, polymer with	Ethenylbenzene
Remarks - Acute - Fish:	No applicable toxicity data
Remarks - Acute - Aquatic	No applicable toxicity data
invertebrates.:	
Remarks - Acute - Aquatic	No applicable toxicity data
plants:	
Remarks - Chronic - Fish:	No applicable toxicity data
Remarks - Chronic -	No applicable toxicity data
Aquatic invertebrates.:	
XDH/SLATE GREY	
Remarks - Acute - Aquatic	Chemicals are not readily available as they are bound within the polymer matrix.
invertebrates.:	
Conclusion/Summary	: Chemicals are not readily available as they are bound within the polymer matrix.
	porymer maurx.
Persistence and degradability	<u>v</u>
Conclusion/Summary	: Chemicals are not readily available as they are bound within the polymer matrix.
Conclusion/Summary	: Chemicals are not readily available as they are bound within the polymer matrix.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Benzene, ethenyl-	0.35	13.49	low

Mobility in soil

Soil/water partition coefficient	:	Not available.
(KOC)		
Other adverse effects	:	No known significant effects or critical hazards.

:

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever

XDH/SLATE GREY

Version Number 1.3 Revision Date 04/26/2018



possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	:	Not regulated for transportation.
International Air ICAO/IATA	:	Not classified as dangerous goods under transport regulations.
International Water IMO/IMDG	:	Not classified as dangerous goods under transport regulations.

Section 15. Regulatory information

U.S. Federal regulations	:	United States - TSCA 12(b) - Chemical export notification: None of the components are listed.
		United States - TSCA 4(a) - Final Test Rules: Not listed
		United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed
		United States - TSCA 4(f) - Priority risk review: Not listed
		United States - TSCA 5(a)2 - Final significant new use rules: Not
		listed
		United States - TSCA 5(a)2 - Proposed significant new use rules:
		Not listed
		United States - TSCA 5(e) - Substances consent order: Not listed
		United States - TSCA 6 - Final risk management: Not listed

XDH/SLATE GREY

R	blyOn	e.

Version Number 1.3	Page 15 of 18
Revision Date 04/26/2018	Print Date 05/01/2018

		 United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Chromium (III) oxide Acrylonitrile United States - EPA Clean air act (CAA) section 311 - Hazardous substances: Listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	:	Listed
Clean Air Act Section 602 Class I Substances	:	Not listed
Clean Air Act Section 602 Class II Substances	:	Not listed
DEA List I Chemicals (Precursor Chemicals)	:	Not listed
DEA List II Chemicals (Essential Chemicals)	:	Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification

Not applicable.

:

Composition/information on ingredients

Name	%	Classification	
Styrene	0 - 0.3	F, AH, CH	



XDH/SLATE GREY

Version Number 1.3 Revision Date 04/26/2018 Page 16 of 18 Print Date 05/01/2018

Carbon black	3 - 5	СН
Titanium dioxide	10 - 25	СН
2-Propenenitrile, polymer with Ethenylbenzene	50 - 75	АН

<u>SARA 313</u>

	Product name	CAS number	%
Form R - Reporting	Styrene	100-42-5	0 - 0.3
requirements			
	Chromium (III) oxide	1308-38-9	5 - 10
Supplier notification	Styrene	100-42-5	0 - 0.3
	Chromium (III) oxide	1308-38-9	5 - 10

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations		
Massachusetts	:	None of the components are listed.
New York	:	The following components are listed: Styrene
New Jersey	:	The following components are listed: 2-Propenenitrile, polymer with Ethenylbenzene Titanium dioxide Chromium (III) oxide Carbon black Styrene
Pennsylvania	:	The following components are listed: Titanium dioxide Chromium (III) oxide Carbon black Silica, amorphous
		Styrene
California Dava (5		

California Prop. 65

<u>PolyOne</u>

XDH/SLATE GREY

Version Number 1.3	Page 17 of 18
Revision Date 04/26/2018	Print Date 05/01/2018

WARNING: This product contains a chemical known to the State of California to cause cancer.

United States inventory (TSCA 8b)	:	All components are listed or exempted.
Canada inventory	:	All components are listed or exempted.
International regulations		
Inventory list		
Australia	:	All components are listed or exempted.
Canada	:	All components are listed or exempted.
China	:	Not determined.
Europe inventory	:	All components are listed or exempted.
Japan	:	Not determined.
New Zealand	:	Not determined.
Philippines	:	Not determined.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	All components are listed or exempted.
Turkey	:	Not determined.
United States	:	All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	0
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

1115001.)		
Date of printing	:	05/01/2018
Date of issue/Date of revision	:	04/26/2018
Date of previous issue	:	06/04/2010
Version	:	1.3

XDH/SLATE GREY



Version Number 1.3Page 18 of 18Revision Date 04/26/2018Print Date 05/01/2018

Key to abbreviations	:	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
References	:	Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.