MATERIAL SAFETY DATA SHEET PUREOLOGY GREEN

Version Number 1.0 Revision Date 12/03/2004

Page 1 of 6 Print Date 11/16/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PUREOLOGY GREEN
Product code	:	CC10061996
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Mica	12001-26-2	10 - 30
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling. 		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		



MATERIAL SAFETY DATA SHEET PUREOLOGY GREEN

Version Number 1.0 Revision Date 12/03/2004 Page 2 of 6 Print Date 11/16/2011

Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists se medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures Unusual Fire/Explosion	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Hazards	(NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by scoop or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET PUREOLOGY GREEN

Version Number 1.0 Revision Date 12/03/2004 Page 3 of 6 Print Date 11/16/2011

	EXPOSURE	CONTROLS / PERSO	NAL PROTE	CTION	
Respiratory protection		o personal respiratory pr usty conditions occur we			
Eye/Face Protection	: safety glasses				
Hand protection	: Protective gloves.				
Skin and body protection	: Long sleeved clothing.				
Additional Protective Measures	: Safety shoes.				
General Hygiene Considerations	: Wash hands and face before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice for diagnostics.				
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure time		posure type	List:
-	20 mppcf	PEL:	Т	'otal dust.	OSHA
Components Mica	20 mppcf 3 mg/m3	PEL: Time Weighted Avera (TWA):	ige Respir	otal dust. rable fraction.	OSHA ACGIH
Components	20 mppcf 3 mg/m3 20 mppcf	PEL: Time Weighted Avera (TWA): PEL:	ige Respi	otal dust. rable fraction. otal dust.	OSHA ACGIH OSHA
Components Mica	20 mppcf 3 mg/m3 20 mppcf 20 mppcf	PEL: Time Weighted Avera (TWA): PEL: PEL:	ige Respir	otal dust. rable fraction.	OSHA ACGIH OSHA Z3
Components Mica Silica, amorphous	20 mppcf 3 mg/m3 20 mppcf 20 mppcf 10 mg/m3	PEL: Time Weighted Avera (TWA): PEL: PEL: Time Weighted Avera (TWA):	ge Respin	otal dust. rable fraction. otal dust.	OSHA ACGIH OSHA Z3 ACGIH
Components Mica	20 mppcf 3 mg/m3 20 mppcf 20 mppcf 10 mg/m3 10 mg/m3	PEL: Time Weighted Avera (TWA): PEL: PEL: Time Weighted Avera (TWA): Time Weighted Avera (TWA):	ge Respiner	otal dust. rable fraction. otal dust. otal dust.	OSHA ACGIH OSHA Z3 ACGIH ACGIH
Components Mica Silica, amorphous	20 mppcf 3 mg/m3 20 mppcf 20 mppcf 10 mg/m3	PEL: Time Weighted Avera (TWA): PEL: PEL: Time Weighted Avera (TWA): Time Weighted Avera	ge Respiner	otal dust. rable fraction. otal dust.	OSHA ACGIH OSHA Z3 ACGIH ACGIH
Components Mica Silica, amorphous	20 mppcf 3 mg/m3 20 mppcf 20 mppcf 10 mg/m3 10 mg/m3 15 mg/m3	PEL: Time Weighted Avera (TWA): PEL: PEL: Time Weighted Avera (TWA): Time Weighted Avera (TWA): PEL:	ge Respinered T	Total dust. rable fraction. Total dust. Total dust. Total dust. Total dust.	OSHA ACGIH OSHA Z3 ACGIH ACGIH
Components Mica Silica, amorphous	20 mppcf 3 mg/m3 20 mppcf 20 mppcf 10 mg/m3 10 mg/m3 15 mg/m3	PEL: Time Weighted Avera (TWA): PEL: PEL: Time Weighted Avera (TWA): Time Weighted Avera (TWA):	ge Respinered T	Total dust. rable fraction. Total dust. Total dust. Total dust. Total dust.	OSHA ACGIH OSHA Z3 ACGIH ACGIH
Components Mica Silica, amorphous	20 mppcf 3 mg/m3 20 mppcf 20 mppcf 10 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid	PEL: Time Weighted Avera (TWA): PEL: PEL: Time Weighted Avera (TWA): Time Weighted Avera (TWA): PEL: PEL: CAL AND CHEMICAL	ge Respinent of the second sec	otal dust. rable fraction. 'otal dust.	OSHA ACGIH OSHA Z3 ACGIH ACGIH OSHA Z2 applicable
Components Mica Silica, amorphous Titanium dioxide Form Appearance	20 mppcf 3 mg/m3 20 mppcf 20 mppcf 10 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : flake	PEL: Time Weighted Avera (TWA): PEL: PEL: Time Weighted Avera (TWA): Time Weighted Avera (TWA): PEL: CAL AND CHEMICAL s S	T .ge Respination .ge T .ge T .ge T .ge T .ge T .ge T	otal dust. rable fraction. 'otal dust.	OSHA ACGIH OSHA Z3 ACGIH ACGIH OSHA Z2 applicable determined
Components Mica Silica, amorphous Titanium dioxide Form Appearance Color	20 mppcf 3 mg/m3 20 mppcf 20 mppcf 10 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : flake : GRE	PEL: Time Weighted Avera (TWA): PEL: PEL: Time Weighted Avera (TWA): Time Weighted Avera (TWA): PEL: CAL AND CHEMICAL I E S S EN E	T .ge Respination .ge T .ge T .ge T .ge T .ge T .ge T	otal dust. rable fraction. 'otal dust.	OSHA ACGIH OSHA Z3 ACGIH ACGIH OSHA Z3 applicable determined
Components Mica Silica, amorphous Titanium dioxide Form Appearance Color Odor	20 mppcf 3 mg/m3 20 mppcf 20 mppcf 10 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : flake : GRE : Very	PEL: Time Weighted Avera (TWA): PEL: PEL: Time Weighted Avera (TWA): Time Weighted Avera (TWA): PEL: CAL AND CHEMICAL I E S S EN E faint V	T .ge Respination .ge T	otal dust. rable fraction. 'otal dust. 'otal dust. <tr< td=""><td>OSHA ACGIH OSHA Z3 ACGIH ACGIH OSHA Z applicable determined determined</td></tr<>	OSHA ACGIH OSHA Z3 ACGIH ACGIH OSHA Z applicable determined determined
Components Mica Silica, amorphous Titanium dioxide Form Appearance Color Odor Melting point/range	20 mppcf 3 mg/m3 20 mppcf 20 mppcf 10 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : flake : GRE : Very : Great	PEL: Time Weighted Avera (TWA): PEL: PEL: Time Weighted Avera (TWA): Time Weighted Avera (TWA): PEL: CAL AND CHEMICAL I E s S EN E faint V ter than 130 °C V	T .ge Respination .ge T	otal dust. rable fraction. otal dust. otal dust. otal dust. otal dust. Otal dust. ES te : Not	OSHA ACGIH OSHA Z3 ACGIH ACGIH OSHA Z applicable determined determined determined
Components Mica Silica, amorphous Titanium dioxide Form Appearance Color Odor	20 mppcf 3 mg/m3 20 mppcf 20 mppcf 10 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : flake : GRE : Very : Great	PEL: Time Weighted Avera (TWA): PEL: PEL: Time Weighted Avera (TWA): Time Weighted Avera (TWA): PEL: CAL AND CHEMICAL I E s S EN E faint V ter than 130 °C V applicable p	T .ge Respination .ge T	otal dust. rable fraction. otal dust. otal dust. otal dust. otal dust. Otal dust. ES te : Not	OSHA ACGIH OSHA Z3 ACGIH ACGIH OSHA Z1 oSHA Z1

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET PUREOLOGY GREEN

Version Number 1.0 Revision Date 12/03/2004 Page 4 of 6 Print Date 11/16/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
12001-26-2	Mica	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Not inherently biodegradable.
Additional advice	: Chemicals are not readily available as they are bound within the polymer matrix.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION

PolyOne.

MATERIAL SAFETY DATA SHEET PUREOLOGY GREEN

Version Number 1.0			
Revision Date	12/03/2004		

Page 5 of 6 Print Date 11/16/2011

U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
	: This product does not contain a substance listed by California Prop 65.
California Proposition 65	
65	
65 SARA Title III Section 302 Ext Not applicable	remely Hazardous Substance
65 SARA Title III Section 302 Ext Not applicable SARA Title III Section 313 Tox Not applicable	remely Hazardous Substance
65 SARA Title III Section 302 Ext Not applicable SARA Title III Section 313 Tox	remely Hazardous Substance
65 SARA Title III Section 302 Ext Not applicable SARA Title III Section 313 Tox Not applicable Canadian Regulations:	remely Hazardous Substance
65 SARA Title III Section 302 Ext Not applicable SARA Title III Section 313 Tox Not applicable Canadian Regulations: National Pollutant Relea	remely Hazardous Substance
65 SARA Title III Section 302 Ext Not applicable SARA Title III Section 313 Tox Not applicable Canadian Regulations: National Pollutant Relea Not applicable	remely Hazardous Substance tic Chemicals: se Inventory (NPRI)
65 SARA Title III Section 302 Ext Not applicable SARA Title III Section 313 Tox Not applicable Canadian Regulations: National Pollutant Relea Not applicable WHMIS Classification DSL	remely Hazardous Substance tic Chemicals: se Inventory (NPRI) : Not controlled. : All components of this product are on the Canadian Domestic
65 SARA Title III Section 302 Ext Not applicable SARA Title III Section 313 Tox Not applicable Canadian Regulations: National Pollutant Relea Not applicable WHMIS Classification	remely Hazardous Substance tic Chemicals: se Inventory (NPRI) : Not controlled. : All components of this product are on the Canadian Domestic
65 SARA Title III Section 302 Ext Not applicable SARA Title III Section 313 Tox Not applicable Canadian Regulations: National Pollutant Relea Not applicable WHMIS Classification DSL National Inventories:	remely Hazardous Substance tic Chemicals: se Inventory (NPRI) : Not controlled. : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

POLYONE CORPORATION material safety data sheet		
1		
	Page 6 of 6 Print Date 11/16/2011	
: Not determined		
: Listed		
: Listed		
	HEET I Not determined Listed	

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.