MATERIAL SAFETY DATA SHEET TRANSLUCENT VIOLET

Version Number 1.1 Revision Date 01/05/2005 Page 1 of 5 Print Date 11/16/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	TRANSLUCENT VIOLET
Product code	:	CC10062354
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES

PolyOne.

MATERIAL SAFETY DATA SHEET TRANSLUCENT VIOLET

sion Date 01/05/2005	Page 2 Print Date 11/16/
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion	 Not applicable Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Hazards	(NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

PolyOne.

MATERIAL SAFETY DATA SHEET **TRANSLUCENT VIOLET**

Version Number 1.1 Revision Date 01/05/2005 Page 3 of 5 Print Date 11/16/2011

Respiratory protection	: No personal respir	atory protective equipment normally require	ed.
Eye/Face Protection	: Safety glasses with	ı side-shields.	
Hand protection	: Protective gloves.		
Skin and body protection	: Long sleeved cloth	othing.	
Additional Protective Measures	: Safety shoes.		
General Hygiene Considerations		nce with good industrial hygiene and safety p breaks and at the end of workday.	oractice
Engineering measures		with appropriate exhaust ventilation. Provident ventilation at machinery.	de
Exposure limit(s)			
	PHYSICAL AND CHE		1.1
Form	: Solid : Pellets	Evaporation rate : Not applic Specific Gravity: : Not determ	
Appearance Color	: PINK	Bulk density : Not determined	
Odor	: Very faint	Vapor pressure : Not applic	
Melting point/range	: Not determined	Vapour density : Not applic	
Boiling Point:	: Not applicable	pH : Not applicab	
Water solubility	: Insoluble		
	10. STABILITY AN	D REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from o decomposition, do	xidizing agents and open flame. To avoid th not overheat.	nermal
	: Incompatible with	strong acids and oxidizing agents.	
Incompatible Materials		O2), carbon monoxide (CO), oxides of nitro dous materials, and smoke are all possible.	gen
Incompatible Materials Hazardous decomposition products	(NOx), other hazar	dous materiais, and smoke are an possible.	

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET TRANSLUCENT VIOLET

Version Number 1.1 Revision Date 01/05/2005 Page 4 of 5 Print Date 11/16/2011

There are no known hazardous components above regulatory thresholds in this product.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: There are no known hazardous components above regulatory thresholds in this product.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	

PolyOne

Page 5 of 5

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET TRANSLUCENT VIOLET

Version Number 1.1

vision Date 01/05/2005		Print Date 11/16/20
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
SARA Title III Section 302 Ext Not applicable	rem	ely Hazardous Substance
SARA Title III Section 313 Tox	kic (Chemicals:
Not applicable Canadian Regulations:		
National Pollutant Relea	se Iı	nventory (NPRI)
Not applicable		
WHMIS Classification	:	Not controlled.
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Listed
<u> </u>		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.