MATERIAL SAFETY DATA SHEET

GRAY NEPTUNE

Version Number 1.0 Revision Date 01/25/2005

Page 1 of 6 Print Date 11/17/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone Emergency telephone Telephone Emergency telephone Emerge	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GRAY NEPTUNE
Product code	:	CC10064666
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Rutile, antimony chromium buff	68186-90-3	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin Chronic exposure	 Experience shows no unusual dermatitis hazard from routine handling. Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET **GRAY NEPTUNE**

Version Number 1.0 Revision Date 01/25/2005 Page 2 of 6 Print Date 11/17/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures Unusual Fire/Explosion	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Hazards	(NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET **GRAY NEPTUNE**

Version Number 1.0 Revision Date 01/25/2005 Page 3 of 6 Print Date 11/17/2011

	ai	nd contamination. Keep in a o	ary, coor prace.		
8. 1	EXPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	o personal respiratory protect	ive equipment normally	required.	
Eye/Face Protection	: Safety glasses with side-shields.				
Hand protection	: P1	rotective gloves.			
Skin and body protection	: Lo	ong sleeved clothing.			
Additional Protective Measures	: Sa	afety shoes.			
General Hygiene Considerations		andle in accordance with good ash hands before breaks and		safety practic	
Engineering measures		eat only in areas with approprion of the second s		. Provide	
Exposure limit(s)	Value	Exposure time	Exposure type	List	
Components	Value	Exposure time	Exposure type	List:	
Components Rutile, antimony	Value 0.5 mg/m3	Exposure time PEL:	Exposure type as Sb		
Components		PEL: Time Weighted Average		OSHA Z	
Components Rutile, antimony	0.5 mg/m3	PEL: Time Weighted Average (TWA): Time Weighted Average	as Sb	OSHA Z	
Components Rutile, antimony	0.5 mg/m3 0.5 mg/m3	PEL: Time Weighted Average (TWA):	as Sb as Cr	OSHA Z ACGIH ACGIH	
Components Rutile, antimony	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average	as Sb as Cr as Sb	OSHA Z ACGIH ACGIH OSHA Z	
Components Rutile, antimony chromium buff	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL:	as Sb as Cr as Sb	List: OSHA Z ACGIH ACGIH OSHA Z OSHA Z	
Components Rutile, antimony chromium buff	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL:	as Sb as Cr as Sb as Cr Total dust.	OSHA Z ACGIH ACGIH OSHA Z ACGIH	
Components Rutile, antimony chromium buff Titanium dioxide	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: 2AL AND CHEMICAL PRO	as Sb as Cr as Sb as Cr Total dust.	OSHA Z ACGIH ACGIH OSHA Z ACGIH OSHA Z	
Components Rutile, antimony chromium buff Titanium dioxide	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Evapo	as Sb as Cr as Sb as Cr Total dust.	OSHA Z ACGIH ACGIH OSHA Z ACGIH OSHA Z	
Components Rutile, antimony chromium buff Titanium dioxide	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Peller	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Evapor ts Specifi	as Sb as Cr as Sb as Cr Total dust. OPERTIES oration rate : No fic Gravity: : No	OSHA Z ACGIH ACGIH OSHA Z ACGIH OSHA Z	
Components Rutile, antimony chromium buff Titanium dioxide Form Appearance Color	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pellet : GRE	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Evapor ts Specifi Y Bulk of the second sec	as Sb as Cr as Sb as Cr Total dust. OPERTIES oration rate : No fic Gravity: : No density : No	OSHA Z ACGIH ACGIH OSHA Z ACGIH OSHA Z	
Components Rutile, antimony chromium buff Titanium dioxide Form Appearance Color Odor	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : GRE : Very	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Evaports Specifier Y Bulk of faint Vapor	as Sb as Cr as Sb as Cr Total dust. OPERTIES OPERTIES OPERTIES OPERTIES OPERTIES	OSHA Z ACGIH ACGIH OSHA Z ACGIH OSHA Z OSHA Z	
Components Rutile, antimony chromium buff Titanium dioxide Form Appearance Color	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : GRE : Very : Not d	PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Evaports Specifier Y Bulk of faint Vapor	as Sb as Cr as Sb as Cr Total dust. OPERTIES oration rate : No fic Gravity: : No density : No r pressure : No ur density : No	OSHA Z ACGIH ACGIH OSHA Z ACGIH OSHA Z OSHA Z	

10. STABILITY AND REACTIVITY

Stability

: Stable.

MATERIAL SAFETY DATA SHEET **GRAY NEPTUNE**

Version Number 1.0 Page 4 of 6 Revision Date 01/25/2005 Print Date 11/17/2011 Hazardous Polymerization Will not occur. : Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible Materials Incompatible with strong acids and oxidizing agents. : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen Hazardous decomposition : (NOx), other hazardous materials, and smoke are all possible. products

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
68186-90-3	Rutile, antimony chromium buff	Irritant	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

12. ECOLOGICAL INFORMATION

ersistence and degradability	:	Not readily biodegradable.
wironmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
oaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.
dditional advice	:	No data available
	13	B. DISPOSAL CONSIDERATIONS
roduct	:	Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
ontaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation
	oaccumulation Potential Iditional advice	vironmental Toxicity : oaccumulation Potential : lditional advice : <u>13</u> oduct :



MATERIAL SAFETY DATA SHEET **GRAY NEPTUNE**

Version Number 1.0 Revision Date 01/25/2005

Page 5 of 6 Print Date 11/17/2011

and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

- U.S. DOT Classification : Not regulated for transportation.
- ICAO/IATA (air) : Refer to specific regulation.
- IMO / IMDG (maritime) : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

TSCA Status	:	All components of this product are listed on or exempt from the TSCA
		Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition : This product does not contain a substance listed by California Prop 65. 65

SARA Title III Section 302 Extremely Hazardous Substance Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
CHROMIUM III COMPOUNDSANTIMONY	68186-90-3	2.79
COMPOUNDS		

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Aluminum oxide	1344-28-1	0.23	13
Rutile, antimony chromium buff	68186-90-3	2.79	69
Rutile, antimony chromium buff	68186-90-3	2.79	17

		PolvOne.
POLYONE CORPORAT	'I(ON CON
MATERIAL SAFETY DATA SHE	ЕТ	
GRAY NEPTUNE		
Version Number 1.0 Revision Date 01/25/2005		Page 6 of 6 Print Date 11/17/2011
WHMIS Classification WHMIS Ingredient Discl		
CAS-No. 68186-90-3 DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Listed
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.