# MATERIAL SAFETY DATA SHEET PRIMARY YELLOW UV HDPE

Version Number 1.0 Revision Date 02/08/2005 Page 1 of 6 Print Date 11/17/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PRIMARY YELLOW UV HDPE
Product code	:	CC10065062
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	10 - 30

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eves.</li> </ul>
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne

# MATERIAL SAFETY DATA SHEET PRIMARY YELLOW UV HDPE

Version Number 1.0 Revision Date 02/08/2005 Page 2 of 6 Print Date 11/17/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not applicable
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

PolyOne

# MATERIAL SAFETY DATA SHEET PRIMARY YELLOW UV HDPE

Version Number 1.0 Revision Date 02/08/2005 Page 3 of 6 Print Date 11/17/2011

8. E	XPOSURE	CONTROLS / PERS	SONAL	PROTECTION	
Respiratory protection	: N	lo personal respiratory	, protecti	ve equipment normally	required.
Eye/Face Protection	: S	afety glasses with side	e-shields		
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations				industrial hygiene and a the end of workday.	safety practice
Engineering measures		leat only in areas with ppropriate exhaust ver		iate exhaust ventilation. at machinery.	Provide
Exposure limit(s)					
Components	Value	Exposure time	<b>.</b>	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Av (TWA):			ACGIH
	15 mg/m3	PEL:		Total dust.	OSHA Z1
	9. PHYSIC	CAL AND CHEMIC	AL PRO	PERTIES	
Form	: Solid	1	Evapo	ration rate : No	t applicable
Appearance	: Pelle	ets			t determined
Color	: YEL	LOW	Bulk d		t established
Odor	: Very	' faint	Vapor	pressure : No	t applicable
Melting point/range	: Not o	determined	Vapou	r density : No	t applicable
Boiling Point:		applicable	pН	: No	t applicable
Water solubility	: Insol	uble			
	10. 8	STABILITY AND R	EACTIV	ITY	
Stability	: S	table.			
Hazardous Polymerization	n : W	Vill not occur.			
Conditions to avoid		Leep away from oxidiz ecomposition, do not		ts and open flame. To	avoid thermal

PolyOne

## MATERIAL SAFETY DATA SHEET **PRIMARY YELLOW UV HDPE**

#### Version Number 1.0 Revision Date 02/08/2005

Page 4 of 6 Print Date 11/17/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

**Toxicity Overview** 

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.			
	12. ECOLOGI	CAL INFORMATION	I			
Persistence and degrada	ability : Not readily b	iodegradable.				
Environmental Toxicity	Chemicals ar polymer mat		as they are bound within the			
Bioaccumulation Poten		: Chemicals are not readily available as they are bound within the polymer matrix.				
Additional advice	: No data avail	lable				
	13. DISPOSAL	CONSIDERATIONS				
Product Contaminated packagin	g : Recycling is has the respo	cling is preferred to dis waste material has the r i, transportation and dis deral, state/provincial a preferred when possible nsibility for proper was in accordance with app	product can be recycled. Where posal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations. e. The generator of waste materia te classification, transportation licable federal, state/provincial			
	14. TRANSPO	RT INFORMATION				
U.S. DOT Classification	n : Not regulated	l for transportation.				
ICAO/IATA (air)	: Refer to spec	ific regulation.				
IMO / IMDG (maritime	e) : Refer to spec	ific regulation.				
	15. REGULAT	ORY INFORMATION	1			

PolyOne.

# MATERIAL SAFETY DATA SHEET PRIMARY YELLOW UV HDPE

sion Date 02/08/2005				Prin	Page : t Date 11/17/
US Regulations:		~			
OSHA Status	:	Classified as hazard	-		
TSCA Status	:	All components of t Inventory.	his product are liste	d on or exemp	ot from the TSC
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)			
Not applicable					
California Proposition 65	:	This product does no	ot contain a substand	ce listed by C	alifornia Prop 6
SARA Title III Section 302 Extr Not applicable	rem	ely Hazardous Substa	nce		
SARA Title III Section 313 Tox	tic C	Chemicals:			
Canadian inclandion.					
Canadian Regulations: National Pollutant Releas Chemical Name Aluminum oxide	se Ir	nventory (NPRI)	CAS-No. 1344-28-1	Weight % 0.21	NPRI ID# 13
National Pollutant Releas Chemical Name Aluminum oxide					
National Pollutant Release		Not controlled. DSL status has not restricted by regulat	1344-28-1 been determined. (	0.21	13
National Pollutant Releas Chemical Name Aluminum oxide WHMIS Classification		Not controlled. DSL status has not	1344-28-1 been determined. (	0.21	13
National Pollutant Releas Chemical Name Aluminum oxide WHMIS Classification DSL		Not controlled. DSL status has not	1344-28-1 been determined. (	0.21	13
National Pollutant Releas Chemical Name Aluminum oxide WHMIS Classification DSL National Inventories:	:	Not controlled. DSL status has not restricted by regulat	1344-28-1 been determined. (	0.21	13
National Pollutant Releas Chemical Name Aluminum oxide WHMIS Classification DSL National Inventories: Australia AICS	:	Not controlled. DSL status has not restricted by regulat Listed	1344-28-1 been determined. (	0.21	13
National Pollutant Releas Chemical Name Aluminum oxide WHMIS Classification DSL National Inventories: Australia AICS China IECS	: :	Not controlled. DSL status has not restricted by regulat Listed Listed	1344-28-1 been determined. (	0.21	13
National Pollutant Releas Chemical Name Aluminum oxide WHMIS Classification DSL National Inventories: Australia AICS China IECS Europe EINECS	: :	Not controlled. DSL status has not restricted by regulat Listed Listed Not determined	1344-28-1 been determined. (	0.21	13
National Pollutant Release         Chemical Name         Aluminum oxide         WHMIS Classification         DSL         National Inventories:         Australia AICS         China IECS         Europe EINECS         Japan ENCS	: :	Not controlled. DSL status has not restricted by regulat Listed Listed Not determined Not determined	1344-28-1 been determined. (	0.21	13

<u>PolyOne</u>

## MATERIAL SAFETY DATA SHEET PRIMARY YELLOW UV HDPE

Version Number 1.0 Revision Date 02/08/2005 Page 6 of 6 Print Date 11/17/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.