MATERIAL SAFETY DATA SHEET BLUE 505120 (LASERMARK) V2

Version Number 1.0 Revision Date 02/16/2005 Page 1 of 6 Print Date 11/17/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	BLUE 505120 (LASERMARK) V2
Product code :	CC10065326
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Decanedioic acid,	52829-07-9	5 - 10
bis(2,2,6,6-tetramethyl-4-piperidinyl) ester		
Titanium dioxide	13463-67-7	1 - 5
Talc	14807-96-6	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne

MATERIAL SAFETY DATA SHEET BLUE 505120 (LASERMARK) V2

Version Number 1.0 Revision Date 02/16/2005 Page 2 of 6 Print Date 11/17/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

MATERIAL SAFETY DATA SHEET BLUE 505120 (LASERMARK) V2

Version Number 1.0 Revision Date 02/16/2005 Page 3 of 6 Print Date 11/17/2011

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Talc	2 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form
Appearance
Color
Odor
Melting point/range
Boiling Point:
Water solubility

:	Solid
:	Pellets
:	BLUE
:	Very faint
:	Not determined
:	Not applicable
:	Insoluble

Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH

- Not applicableNot determinedNot establishedNot applicable
- : Not applicable
- : Not applicable

10. STABILITY AND REACTIVITY

Stability:Stable.Hazardous Polymerization:Will not occur.Conditions to avoid:Keep away from oxidizing agents and open flame. To avoid thermal

MATERIAL SAFETY DATA SHEET BLUE 505120 (LASERMARK) V2

Version Number 1.0 Revision Date 02/16/2005 Page 4 of 6 Print Date 11/17/2011

		decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
52829-07-9	Decanedioic acid,	Irritant	Eyes.
	bis(2,2,6,6-tetramethyl-4-p		
	iperidinyl) ester		
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
14807-96-6	Talc	Systemic effects	Eyes, Respiratory system, Skin.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
52829-07-9	Decanedioic acid, bis(2,2,6,6-tetramethyl-4-p iperidinyl) ester	Oral LD50 Dermal LD50	3,700 mg/kg > 3,100 mg/kg	rat rabbit

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	:	No data available
	1	3. DISPOSAL CONSIDERATIONS
Product	:	Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with

applicable federal, state/provincial and local regulations.

PolyOne

MATERIAL SAFETY DATA SHEET BLUE 505120 (LASERMARK) V2

Version Number 1.0 Revision Date 02/16/2005 Page 5 of 6 Print Date 11/17/2011

Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
14. TRANSPORT INFORMATION			
U.S. DOT Classification ICAO/IATA (air) IMO / IMDG (maritime)	 Not regulated for transportation. Refer to specific regulation. Refer to specific regulation. 		
15. REGULATORY INFORMATION			
US Regulations:			
OSHA Status	: Classified as hazardous based on components.		
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.		
US. EPA CERCLA Hazardous Substances (40 CFR 302)			
Not applicable			
California Proposition 65	: This product does not contain a substance listed by California Prop 65.		
SARA Title III Section 302 Extremely Hazardous Substance Not applicable			
SARA Title III Section 313 Toxic Chemicals:			
Not applicable Canadian Regulations:			
National Pollutant Release Inventory (NPRI)			
Not applicable			
WHMIS Classification : D2A			
WHMIS Ingredient Disclosure List			
CAS-No.			

PolyOne

MATERIAL SAFETY DATA SHEET BLUE 505120 (LASERMARK) V2

Version Number 1.0 Revision Date 02/16/2005 Page 6 of 6 Print Date 11/17/2011

14807-96-6 DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Listed
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.