MATERIAL SAFETY DATA SHEET

### **RED 82200**

Version Number 1.0 Revision Date 03/09/2005 Page 1 of 6 Print Date 11/17/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| Telephone :<br>Emergency telephone :<br>number | : | Product Stewardship (770) 271-5902<br>CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure<br>or accident). |
|--|---|---|
| Product name                                   | : | RED 82200   |
| Product code                                   | : | CC10066586  |
| Chemical Name                                  | : | Mixture   |
| CAS-No.  | : | Mixture   |
| Product Use                                    | : | Industrial Applications   |

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

| Components   | CAS-No.    | Weight % |
|--|------------|----------|
| 8-Oxa-3,5-dithia-4-stannatetradecanoic acid,<br>10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl | 57583-35-4 | 1 - 5    |
| ester  |            |          |
| Titanium dioxide   | 13463-67-7 | 1 - 5    |

### 3. HAZARDS IDENTIFICATION

### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

### POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Ingestion, Skin contact  |
|---------------------|--|
| Acute exposure      |  |
| Inhalation          | : Particulates, like other inert materials can be mechanically irritating.<br>Excessive inhalation of product vapors, especially during heating or<br>processing, may be irritating to respiratory system. |
| Ingestion           | : May be harmful if swallowed.   |
| Eyes                | : Particulates, like other inert materials can be mechanically irritating.   |
| Skin                | : Experience shows no unusual dermatitis hazard from routine handling.   |
| Chronic exposure    | : Refer to Section 11 for Toxicological Information.   |



MATERIAL SAFETY DATA SHEET

### **RED 82200**

Version Number 1.0 Revision Date 03/09/2005 Page 2 of 6 Print Date 11/17/2011

| Medical Conditions<br>Aggravated by Exposure:  | : None known.  |
|--|--|
|  | 4. FIRST AID MEASURES  |
| Inhalation   | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.  |
| Ingestion  | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.   |
| Eyes   | : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.   |
| Skin   | : Wash off with soap and plenty of water. If skin irritation persists seel medical attention.  |
|  | 5. FIRE-FIGHTING MEASURES  |
| Flash point  | : Not applicable   |
| Flammable Limits<br>Upper explosion limit<br>Lower explosion limit<br>Autoignition temperature<br>Suitable extinguishing media<br>Special Fire Fighting<br>Procedures<br>Unusual Fire/Explosion<br>Hazards | <ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foamnone.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.</li> </ul> |
|  | 6. ACCIDENTAL RELEASE MEASURES   |
| Personal precautions   | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.   |
| Environmental precautions  | : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.   |
| Methods for cleaning up  | : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.  |
|  | 7. HANDLING AND STORAGE  |



# MATERIAL SAFETY DATA SHEET **RED 82200**

| Version Number 1.0<br>Revision Date 03/09/2005 | Page 3 of 6<br>Print Date 11/17/2011  |
|--|---|
|  |   |
| Handling :                                     | Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.       |
| Storage :                                      | Keep containers dry and tightly closed to avoid moisture absorption<br>and contamination. Keep in a dry, cool place.          |
| 8. EXPOSU                                      | RE CONTROLS / PERSONAL PROTECTION   |
| Respiratory protection :                       | No personal respiratory protective equipment normally required.   |
| Eye/Face Protection :                          | Safety glasses with side-shields.   |
| Hand protection :                              | Protective gloves.  |
| Skin and body protection :                     | Long sleeved clothing.  |
| Additional Protective :<br>Measures            | Safety shoes.   |
| General Hygiene :<br>Considerations            | Handle in accordance with good industrial hygiene and safety practice.<br>Wash hands before breaks and at the end of workday. |
| Engineering measures :                         | Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.                |

Exposure limit(s)

| Components  | Value     | Exposure time                     | Exposure type | List:   |
|---|-----------|-----------------------------------|---------------|---------|
| 8-Oxa-3,5-dithia-4-sta<br>nnatetradecanoic acid,<br>10-ethyl-4,4-dimethyl-<br>7-oxo-, 2-ethylhexyl<br>ester | 0.1 mg/m3 | PEL:                              | as Sn         | OSHA Z1 |
|   | 0.1 mg/m3 | Time Weighted Average (TWA):      | as Sn         | ACGIH   |
|   | 0.2 mg/m3 | Short Term Exposure Limit (STEL): | as Sn         | ACGIH   |
| Titanium dioxide  | 10 mg/m3  | Time Weighted Average (TWA):      |               | ACGIH   |
|   | 15 mg/m3  | PEL:                              | Total dust.   | OSHA Z1 |

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range Solid
Pellets
RED
Very faint
Not determined

Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density Not applicableNot determinedNot established

- : Not applicable
- : Not applicable

| POLYONE CORPORA                                | ATION  | PolyOne  |
|--|--|--|
| MATERIAL SAFETY DATA S                         | HEET   |  |
| RED 82200                                      |  |  |
| Version Number 1.0<br>Revision Date 03/09/2005 |  | Page 4 of 6<br>Print Date 11/17/2011   |
| Boiling Point:<br>Water solubility             | : Not applicable pH<br>: Insoluble   | : Not applicable   |
|  | 10. STABILITY AND REACTIVITY   |  |
| Stability                                      | : Stable.  |  |
| Hazardous Polymerization                       | : Will not occur.  |  |
| Conditions to avoid                            | : Keep away from oxidizing agents and og decomposition, do not overheat.   | pen flame. To avoid thermal  |
| Incompatible Materials                         | : Avoid contact with strong oxidizers. Als<br>acetal copolymers and with amine conta<br>processing. At processing conditions, th<br>destructive and involve rapid degradatio<br>mechanically clean processing equipment<br>quantities of these materials from comin<br>Prevent cross contamination of feedstoc | ining materials during<br>nese materials are mutually<br>on. Thoroughly purge and<br>nt to avoid even trace<br>g in contact with each other. |
| Hazardous decomposition products               | <ul> <li>Carbon dioxide (CO2), carbon monoxid<br/>(NOx), hydrogen chloride (HCl), other I<br/>smoke are all possible. Prolonged heatin<br/>or more) above 392 °F (200 °C) or short<br/>°C) may result in product decomposition<br/>monoxide and hydrogen chloride.</li> </ul>                                  | nazardous materials, and<br>ng (approximately 30 minutes<br>term heating at 482 °F (250  |

### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

| CAS-No.    | Chemical Name  | Effect           | Target Organ        |
|------------|--|------------------|---------------------|
| 57583-35-4 | 8-Oxa-3,5-dithia-4-stannat etradecanoic acid,        | Irritant         | Eyes, Skin.         |
|            | 10-ethyl-4,4-dimethyl-7-o<br>xo-, 2-ethylhexyl ester |                  |                     |
| 13463-67-7 | Titanium dioxide                                     | Systemic effects | Respiratory system. |

### **12. ECOLOGICAL INFORMATION**

| Persistence and degradability | : | Not readily biodegradable.   |
|-------------------------------|---|--|
| Environmental Toxicity        | : | Chemicals are not readily available as they are bound within the polymer matrix. |
| Bioaccumulation Potential     | : | Chemicals are not readily available as they are bound within the                 |



| D 82200  |  |  |
|--|--|--|
| ion Number 1.0<br>sion Date 03/09/2005           |  | Page 5<br>Print Date 11/17/2   |
|  | polymer matrix.  |  |
| Additional advice                                | : No data available  |  |
|  | 13. DISPOSAL CONSIDERATIONS  |  |
| Product  | : Like most thermoplastic plastics the possible recycling is preferred to disp generator of waste material has the reclassification, transportation and disp applicable federal, state/provincial ar | posal or incineration. The<br>esponsibility for proper waste<br>posal in accordance with |
| Contaminated packaging                           | : Recycling is preferred when possible<br>has the responsibility for proper wast<br>and disposal in accordance with appl<br>and local regulations.   | e classification, transportation   |
|  | 14. TRANSPORT INFORMATION  |  |
| U.S. DOT Classification                          | : Not regulated for transportation.  |  |
| ICAO/IATA (air)                                  | : Refer to specific regulation.  |  |
| IMO / IMDG (maritime)                            | : Refer to specific regulation.  |  |
|  | 15. REGULATORY INFORMATION   | I  |
| US Regulations:                                  |  |  |
| OSHA Status                                      | : Classified as hazardous based on con   | nponents.  |
| TSCA Status                                      | : All components of this product are lis<br>Inventory.   | sted on or exempt from the TSC.  |
| US. EPA CERCLA Hazardous                         | Substances (40 CFR 302)  |  |
| Not applicable                                   |  |  |
| California Proposition<br>65                     | : WARNING! This product contains a California to cause cancer.   | a chemical known to the State of   |
| SARA Title III Section 302 Ext<br>Not applicable | remely Hazardous Substance   |  |
| SARA Title III Section 313 Tox                   | ic Chemicals:  |  |

### MATERIAL SAFETY DATA SHEET

### **RED 82200**

Version Number 1.0 Revision Date 03/09/2005 Page 6 of 6 Print Date 11/17/2011

Not applicable Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name                                  | CAS-No.    | Weight % | NPRI ID# |
|--|------------|----------|----------|
| Manganese antimony titanium brown rutile (C.I. | 68412-38-4 | 0.58     | 147      |
| Pigment Yellow 164)                            |            |          |          |
| Manganese antimony titanium brown rutile (C.I. | 68412-38-4 | 0.58     | 17       |
| Pigment Yellow 164)                            |            |          |          |

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

| CAS-No.    |  |
|------------|--|
| 57583-35-4 |  |

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

| Australia AICS    | : Not determined |
|-------------------|------------------|
| China IECS        | : Not determined |
| Europe EINECS     | : Not determined |
| Japan ENCS        | : Not determined |
| Korea KECI        | : Not determined |
| Philippines PICCS | : Not determined |
|                   |                  |

:

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.