MATERIAL SAFETY DATA SHEET

STOCK WHITE PVC

Version Number 1.0 Revision Date 03/11/2005

Page 1 of 6 Print Date 11/17/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
:	STOCK WHITE PVC
:	CC10066922
:	Mixture
:	Mixture
:	Industrial Applications
	: : : : :

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
8-Oxa-3,5-dithia-4-stannatetradecanoic acid, 10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl ester	57583-35-4	1 - 5
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET **STOCK WHITE PVC**

Version Number 1.0

Revision Date 03/11/2005

Page 2 of 6 Print Date 11/17/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET **STOCK WHITE PVC**

/ersion Number 1.0 Revision Date 03/11/2005		Page 3 of 6 Print Date 11/17/2011
Handling		vent the build up of electrostatic charge. Heat ropriate exhaust ventilation.
Storage		nd tightly closed to avoid moisture absorption eep in a dry, cool place.
8. EXI	RE CONTROLS / PER	RSONAL PROTECTION
Respiratory protection	No personal respirator	ry protective equipment normally required.
Eye/Face Protection	Safety glasses with sid	le-shields.
Hand protection	Protective gloves.	
Skin and body protection	Long sleeved clothing.	
Additional Protective Measures	Safety shoes.	
General Hygiene Considerations		with good industrial hygiene and safety practice. eaks and at the end of workday.
Engineering measures		h appropriate exhaust ventilation. Provide entilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
8-Oxa-3,5-dithia-4-sta	0.1 mg/m3	PEL:	as Sn	OSHA Z1
nnatetradecanoic acid,				
10-ethyl-4,4-dimethyl-				
7-oxo-, 2-ethylhexyl				
ester				
	0.1 mg/m3	Time Weighted Average	as Sn	ACGIH
		(TWA):		
	0.2 mg/m3	Short Term Exposure Limit	as Sn	ACGIH
	_	(STEL):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range : Solid: Pellets: WHITE: Very faint: Not determined

Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density Not applicableNot determinedNot established

- : Not applicable
- : Not applicable



MATERIAL SAFETY DATA SHEET STOCK WHITE PVC

Version Number 1.0 Revision Date 03/11/2005

Page 4 of 6 Print Date 11/17/2011

Water solubility	: Insoluble		
	10. STABILITY	AND REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid		m oxidizing agents and do not overheat.	open flame. To avoid thermal
Incompatible Materials	acetal copolym processing. At destructive and mechanically c quantities of th	ers and with amine con processing conditions, involve rapid degradat lean processing equipm	ing in contact with each other.
Hazardous decomposition products	(NOx), hydrog smoke are all p or more) above °C) may result	en chloride (HCl), other ossible. Prolonged hea 392 °F (200 °C) or sho	ide (CO), oxides of nitrogen hazardous materials, and ting (approximately 30 minutes ort term heating at 482 °F (250 on and evolution of carbon

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
57583-35-4	8-Oxa-3,5-dithia-4-stannat etradecanoic acid,	Irritant	Eyes, Skin.
	10-ethyl-4,4-dimethyl-7-o xo-, 2-ethylhexyl ester		
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the

POLYONE	CORPORATION



MATERIAL SAFETY DATA SHEET
STOCK WHITE PVC

Version Number 1.0 Revision Date 03/11/2005 Page 5 of 6 Print Date 11/17/2011

	polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	as Substances (40 CFR 302)
Not applicable	
California Propositior 65	: WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 E Not applicable	xtremely Hazardous Substance
SARA Title III Section 313 T	oxic Chemicals:

PolyOne

MATERIAL SAFETY DATA SHEET

STOCK WHITE PVC

Version Number 1.0 Revision Date 03/11/2005 Page 6 of 6 Print Date 11/17/2011

Not applicable Canadian Regulations:					
National Pollutant Rel	ease I	nventory (NPRI)		1	
Chemical Name			CAS-No.	Weight %	NPRI ID#
Aluminum oxide			1344-28-1	0.48	13
WHMIS Classification WHMIS Ingredient Di					
CAS-No. 57583-35-4					
DSL	:	All components of Substances List (DS			Domestic
National Inventories:					
Australia AICS	:	Not determined			
China IECS	:	Not determined			
Europe EINECS	:	Not determined			
Japan ENCS	:	Not determined			
Korea KECI	:	Not determined			
Philippines PICCS	:	Not determined			
		16. OTHER INFO	RMATION		

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.