MATERIAL SAFETY DATA SHEET **WHITE**

Version Number 1.0 Revision Date 03/30/2005

Page 1 of 6 Print Date 11/17/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	WHITE
Product code	:	CC10067364
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	5 - 10
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET WHITE

Version Number 1.0 Revision Date 03/30/2005 Page 2 of 6 Print Date 11/17/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET **WHITE**

sion Date 03/30/2005			Prir	Page : nt Date 11/17/
Handling		ake measures to prevent th nly in areas with appropria		c charge. Heat
Storage		eep containers dry and tig		sture absorption
8. F	XPOSURE	CONTROLS / PERSON	AL PROTECTION	
Respiratory protection	: N	o personal respiratory pro	tective equipment norma	lly required.
Eye/Face Protection	: S	afety glasses with side-shi	elds.	
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations		andle in accordance with g		
Engineering measures		leat only in areas with app ppropriate exhaust ventilat		on. Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Components Silica, amorphous	Value 20 mppcf	Exposure time PEL:	Exposure type Total dust.	List: OSHA
Components Silica, amorphous	20 mppcf	Exposure time PEL: PEL:	Total dust.	OSHA
Silica, amorphous	20 mppcf 20 mppcf 10 mg/m3	PEL:	Total dust. Total dust.	OSHA Z3
	20 mppcf 20 mppcf	PEL: PEL: Time Weighted Averag	Total dust. Total dust. e	OSHA Z3 ACGIH
Silica, amorphous	20 mppcf 20 mppcf 10 mg/m3	PEL: PEL: Time Weighted Averag (TWA): Time Weighted Averag	Total dust. Total dust. e	OSHA Z3 ACGIH ACGIH
Silica, amorphous	20 mppcf 20 mppcf 10 mg/m3 10 mg/m3 15 mg/m3	PEL: PEL: Time Weighted Averag (TWA): Time Weighted Averag (TWA):	Total dust. Total dust. ee Total dust.	OSHA Z3 ACGIH ACGIH
Silica, amorphous Titanium dioxide	20 mppcf 20 mppcf 10 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC	PEL: PEL: Time Weighted Averag (TWA): Time Weighted Averag (TWA): PEL: CAL AND CHEMICAL	Total dust. Total dust. ge Total dust. PROPERTIES	OSHA Z3 ACGIH ACGIH OSHA Z
Silica, amorphous Titanium dioxide	20 mppcf 20 mppcf 10 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solic	PEL: PEL: Time Weighted Averag (TWA): Time Weighted Averag (TWA): PEL: CAL AND CHEMICAL	Total dust. Total dust. ee Total dust. PROPERTIES	OSHA Z3 ACGIH ACGIH OSHA Z
Silica, amorphous Titanium dioxide	20 mppcf 20 mppcf 10 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC	PEL: PEL: Time Weighted Averag (TWA): Time Weighted Averag (TWA): PEL: CAL AND CHEMICAL I I Events Sp	Total dust. Total dust. re ge Total dust. PROPERTIES raporation rate ecific Gravity:	OSHA Z3 ACGIH ACGIH OSHA Z
Silica, amorphous Titanium dioxide Form Appearance Color	20 mppcf 20 mppcf 10 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle : WHI	PEL: PEL: Time Weighted Averag (TWA): Time Weighted Averag (TWA): PEL: CAL AND CHEMICAL I t Events Sp TE Bu	Total dust. Total dust. ge ge Total dust. PROPERTIES aporation rate ecific Gravity: ilk density	OSHA Z3 ACGIH ACGIH OSHA Z Not applicable Not determined Not established
Silica, amorphous Titanium dioxide Form Appearance Color Odor	20 mppcf 20 mppcf 10 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle : WHI : Very	PEL: PEL: Time Weighted Averag (TWA): Time Weighted Averag (TWA): PEL: CAL AND CHEMICAL D t Events Sp TE Bu faint Va	Total dust. Total dust. Total dust. ge Total dust. PROPERTIES aporation rate recific Gravity: ilk density upor pressure	OSHA Z3 ACGIH ACGIH OSHA Z Not applicable Not determined Not established Not applicable
Silica, amorphous Titanium dioxide Form Appearance Color Odor Melting point/range	20 mppcf 20 mppcf 10 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle : WHI : Very : Not of	PEL: PEL: Time Weighted Averag (TWA): Time Weighted Averag (TWA): PEL: CAL AND CHEMICAL 1 t Events Sp TE But t faint Va determined Va	Total dust. Total dust. Total dust. ge Total dust. PROPERTIES raporation rate recific Gravity: ilk density upor pressure upour density	OSHA Z3 ACGIH ACGIH OSHA Z OSHA Z Not applicable Not determined Not established Not applicable Not applicable
Silica, amorphous Titanium dioxide Form Appearance Color Odor	20 mppcf 20 mppcf 10 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle : WHI : Very : Not of	PEL: PEL: Time Weighted Averag (TWA): Time Weighted Averag (TWA): PEL: CAL AND CHEMICAL 1 the Event of the Even of the Event of the Event of	Total dust. Total dust. Total dust. ge Total dust. PROPERTIES raporation rate recific Gravity: ilk density upor pressure upour density	OSHA Z3 ACGIH ACGIH OSHA Z Not applicable Not determined Not established Not applicable
Silica, amorphous Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	20 mppcf 20 mppcf 10 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not a : Insol	PEL: PEL: Time Weighted Averag (TWA): Time Weighted Averag (TWA): PEL: CAL AND CHEMICAL 1 the Event of the Even of the Event of the Event of	Total dust. Total dust. Total dust. ge Total dust. PROPERTIES Propert	OSHA Z3 ACGIH ACGIH OSHA Z OSHA Z Not applicable Not determined Not established Not applicable Not applicable
Silica, amorphous Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	20 mppcf 20 mppcf 10 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not a : Insol 10. S	PEL: PEL: Time Weighted Averag (TWA): Time Weighted Averag (TWA): PEL: PEL: CAL AND CHEMICAL I I Events Sp TE But faint Vata determined Vata applicable pH uble	Total dust. Total dust. Total dust. ge Total dust. PROPERTIES Propert	OSHA Z3 ACGIH ACGIH OSHA Z OSHA Z Not applicable Not determined Not established Not applicable Not applicable
Silica, amorphous Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	20 mppcf 20 mppcf 10 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not a : Insol 10. S	PEL: PEL: Time Weighted Averag (TWA): Time Weighted Averag (TWA): PEL: CAL AND CHEMICAL 1 t Events Sp TE But t faint Vata determined Vata applicable pH uble	Total dust. Total dust. Total dust. ge Total dust. PROPERTIES Propert	OSHA Z3 ACGIH ACGIH OSHA Z OSHA Z Not applicable Not determined Not established Not applicable Not applicable



MATERIAL SAFETY DATA SHEET WHITE

Version Number 1.0 Revision Date 03/30/2005 Page 4 of 6 Print Date 11/17/2011

Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste



MATERIAL SAFETY DATA SHEET
WHITE

HIIE		
sion Number 1.0 ision Date 03/30/2005		Page 5 o Print Date 11/17/20
		classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA (air)	:	Refer to specific regulation.
IMO / IMDG (maritime)	:	Refer to specific regulation.
	15	5. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	s Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.
-	: trem	California to cause cancer.
65 SARA Title III Section 302 Ex		California to cause cancer. ely Hazardous Substance
65 SARA Title III Section 302 Ex Not applicable		California to cause cancer. ely Hazardous Substance
65 SARA Title III Section 302 Ex Not applicable SARA Title III Section 313 To Not applicable	oxic C	California to cause cancer. ely Hazardous Substance Chemicals:
65 SARA Title III Section 302 Ex Not applicable SARA Title III Section 313 To Not applicable Canadian Regulations:	oxic C	California to cause cancer. ely Hazardous Substance Chemicals:
65 SARA Title III Section 302 Ex Not applicable SARA Title III Section 313 To Not applicable Canadian Regulations: National Pollutant Rele	oxic C ase Ir	California to cause cancer. ely Hazardous Substance Chemicals:

PolvOn<u>e</u>

Page 6 of 6

MATERIAL SAFETY DATA SHEET WHITE

Version Number 1.0 Revision Date 03/30/2005

Print Date 11/17/2011 Substances List (DSL) or are exempt. National Inventories: Australia AICS : Listed China IECS Listed : Europe EINECS Listed : Japan ENCS Listed : Korea KECI : Listed Philippines PICCS : Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.