MATERIAL SAFETY DATA SHEET

STAN-TONE VC-29849 AP4 SATIN JADE PC

Version Number 1.0 Revision Date 04/19/2005 Page 1 of 6 Print Date 11/17/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| Telephone:Emergency telephone:number | Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
|--------------------------------------|---|
| Product name : | STAN-TONE VC-29849 AP4 SATIN JADE PC |
| Product code : | CC10068932 |
| Chemical Name : | Mixture |
| CAS-No. : | Mixture |
| Product Use : | Industrial Applications |

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

| Components | CAS-No. | Weight % |
|------------------|------------|----------|
| Titanium dioxide | 13463-67-7 | 1 - 5 |
| Aluminum | 7429-90-5 | 5 - 10 |
| Mica | 12001-26-2 | 5 - 10 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Skin contact, Ingestion |
|---|--|
| Acute exposure | |
| Inhalation Ingestion Eyes Skin | Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling. |
| Chronic exposure | : Refer to Section 11 for Toxicological Information. |
| Medical Conditions Aggravated by Exposure: | : None known. |



MATERIAL SAFETY DATA SHEET STAN-TONE VC-29849 AP4 SATIN JADE PC

Version Number 1.0 Revision Date 04/19/2005 Page 2 of 6 Print Date 11/17/2011

| | 4. FIRST AID MEASURES |
|-------------------------------------|--|
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. |
| Eyes | : Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention. |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists see medical attention. |
| | 5. FIRE-FIGHTING MEASURES |
| Flash point | : Not applicable |
| Flammable Limits | |
| Upper explosion limit | : Not applicable |
| Lower explosion limit | : Not applicable |
| Autoignition temperature | : Not relevant |
| Suitable extinguishing media | : Carbon dioxide blanket, water spray, dry powder, foamnone. |
| Sumption examplify mount | · Carbon dioxide blanket, water spray, ary powder, rounnone. |
| Special Fire Fighting Procedures | : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. |
| Unusual Fire/Explosion Hazards | May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible. |
| | 5. ACCIDENTAL RELEASE MEASURES |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. |
| Environmental precautions | : Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil. |
| Methods for cleaning up | : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods. |
| | 7. HANDLING AND STORAGE |
| | |
| Handling | : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume |



MATERIAL SAFETY DATA SHEET STAN-TONE VC-29849 AP4 SATIN JADE PC

Version Number 1.0 Revision Date 04/19/2005 Page 3 of 6 Print Date 11/17/2011

| Storage | : | condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place. |
|-----------------------------------|------|--|
| 8. EXP | OSUI | RE CONTROLS / PERSONAL PROTECTION |
| Respiratory protection | : | No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection. |
| Eye/Face Protection | : | Safety glasses with side-shields. |
| Hand protection | : | Protective gloves. |
| Skin and body protection | : | Long sleeved clothing. |
| Additional Protective Measures | : | Safety shoes. |
| General Hygiene Considerations | : | Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. |
| Engineering measures | : | Heat only in areas with appropriate exhaust ventilation. Provide |

Exposure limit(s)

| Components | Value | Exposure time | Exposure type | List: |
|------------------|----------|-----------------------|------------------------|---------|
| Aluminum | 10 mg/m3 | Time Weighted Average | Dust. | ACGIH |
| | | (TWA): | | |
| | 15 mg/m3 | PEL: | Total dust. as Al | OSHA Z1 |
| | 5 mg/m3 | PEL: | Respirable dust. as Al | OSHA Z1 |
| Mica | 20 mppcf | PEL: | Total dust. | OSHA |
| | 3 mg/m3 | Time Weighted Average | Respirable fraction. | ACGIH |
| | | (TWA): | | |
| Titanium dioxide | 10 mg/m3 | Time Weighted Average | | ACGIH |
| | | (TWA): | | |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |

appropriate exhaust ventilation at machinery.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range Boiling Point: Solid
powder, granular
GREEN
Very faint
Not determined
Not applicable

Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH Not applicable
Not determined
Not determined
Not applicable
Not applicable
Not applicable

PolyOne

MATERIAL SAFETY DATA SHEET STAN-TONE VC-29849 AP4 SATIN JADE PC

Version Number 1.0 Revision Date 04/19/2005

Page 4 of 6 Print Date 11/17/2011

| | 10. STABILITY AND REACTIVITY |
|----------------------------------|---|
| Stability | : Stable. |
| Hazardous Polymerization | : Will not occur. |
| Conditions to avoid | : To avoid thermal decomposition, do not overheat. Keep away from oxidizing agents and open flame. |
| Incompatible Materials | : Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing |
| Hazardous decomposition products | Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minut or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride. |

luated as a whole for health effects. Exposure effects listed are based on existing mixture has not health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|------------|------------------|------------------|---------------------------------|
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. |
| 7429-90-5 | Aluminum | Irritant | Skin, Respiratory system. |
| | | Systemic effects | Eyes, Skin, Respiratory system. |
| 12001-26-2 | Mica | Systemic effects | Respiratory system. |

| Dersistance and degradability | Not readily higher adable |
|----------------------------------|---|
| Persistence and degradability | : Not readily biodegradable. |
| Environmental Toxicity | : Adverse ecological impact is not known or expected under normal use |
| Bioaccumulation Potential | : No data available |
| Additional advice | : No data available |
| | 13. DISPOSAL CONSIDERATIONS |
| Product | : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with |

| POLYONE CORPORATION | POLYONE | CORPORATION |
|---------------------|---------|-------------|
|---------------------|---------|-------------|

PolyOne.

MATERIAL SAFETY DATA SHEET STAN-TONE VC-29849 AP4 SATIN JADE PC

| sion Number 1.0 sion Date 04/19/2005 | | | Page 5 Print Date 11/17/2 |
|--|-------------------------------|--|--|
| | | | |
| | applicable federal | , state/provincial and 1 | local regulations. |
| Contaminated packaging | : Recycling is prefe | rred when possible. T | The generator of waste material |
| | has the responsibil | lity for proper waste c cordance with application | lassification, transportation ble federal, state/provincial |
| | 14. TRANSPORT I | | |
| | | | |
| U.S. DOT Classification | : Not regulated for | transportation. | |
| ICAO/IATA (air) | : Not regulated for | transportation. | |
| IMO / IMDG (maritime) | : Not regulated for | transportation. | |
| | 15. REGULATORY | INFORMATION | |
| | | | |
| US Regulations: | | | |
| OSHA Status | : Classified as hazar | rdous based on compo | onents. |
| TSCA Status | : All components o Inventory. | of this product are listed | d on or exempt from the TSCA |
| US. EPA CERCLA Hazardou | 1s Substances (40 CFR 30 | 2) | |
| Not applicable | | | |
| | | | |
| | | | |
| California Proposition 65 | n : Not applicable | | |
| SARA Title III Section 302 E Not applicable | Extremely Hazardous Subs | stance | |
| SARA Title III Section 313 T | oxic Chemicals: | | |
| Chemical Name | | CAS-No. | Weight 0/ |
| ALUMINUM (FUM | E OR DUST) | 7429-90-5 | Weight % 8.92 |
| Considian Deculations | | | |
| Canadian Regulations: | | | |
| | ease Inventory (NPRI) | | |
| National Pollutant Rel Chemical Name | | CAS-No. | Weight % NPRI ID# |



MATERIAL SAFETY DATA SHEET STAN-TONE VC-29849 AP4 SATIN JADE PC

Version Number 1.0 Revision Date 04/19/2005

Page 6 of 6 Print Date 11/17/2011

| Chemical Name | | | CAS-No. | Weight % | NPRI ID# |
|--|------|---|---------------|----------|----------|
| Aluminum | | | 7429-90-5 | 8.92 | 12 |
| Chromium (III) oxide | | 1308-38-9 | 0.59 | 69 | |
| Misc00005- Misc Zinc C | pd's | | Not Available | 0.69 | 241 |
| WHMIS Classification WHMIS Ingredient Dis CAS-No. 7429-90-5 12001-26-2 | | | | | |
| DSL | : | All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt. | | | |
| ational Inventories: | | | | | |
| Australia AICS | : | Not determined | | | |
| China IECS | : | Not determined | | | |
| Europe EINECS | : | Not determined | | | |
| Japan ENCS | : | Not determined | | | |
| Korea KECI | : | Not determined | | | |
| Philippines PICCS | : | Not determined | | | |
| | | | | | |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.