# MATERIAL SAFETY DATA SHEET

## **SLIME GREEN**

Version Number 1.0 Revision Date 05/05/2005 Page 1 of 7 Print Date 11/17/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Product Stewardship (770) 271-5902Emergency telephone:CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exponentiation or accident).	sure
Product name : SLIME GREEN	
Product code : CC10069029	
Chemical Name : Mixture	
CAS-No. : Mixture	
Product Use : Industrial Applications	

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5
Chrome yellow (Lead chromate pigment)	1344-37-2	10 - 30

### **3. HAZARDS IDENTIFICATION**

### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> </ul>
Skin Chronic exposure	<ul> <li>Experience shows no unusual dermatitis hazard from routine handling.</li> <li>Refer to Section 11 for Toxicological Information.</li> </ul>
Medical Conditions Aggravated by Exposure:	: None known.



## MATERIAL SAFETY DATA SHEET SLIME GREEN

Version Number 1.0 Revision Date 05/05/2005 Page 2 of 7 Print Date 11/17/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foamnone.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> </ul>
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



## MATERIAL SAFETY DATA SHEET SLIME GREEN

Version Number 1.0 Revision Date 05/05/2005 Page 3 of 7 Print Date 11/17/2011

		nd contamination. Keep in a c	dry, cool place.	
8. 1	EXPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: No personal respiratory protective equipment normally required.			
Eye/Face Protection	: Sa	afety glasses with side-shields	5.	
Hand protection	: P1	rotective gloves.		
Skin and body protection	: Lo	ong sleeved clothing.		
Additional Protective Measures	: Sa	afety shoes.		
General Hygiene Considerations		andle in accordance with good ash hands before breaks and		safety practice
Engineering measures		eat only in areas with appropropropriate exhaust ventilation		. Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Chrome yellow (Lead	0.05	Time Weighted Average		
Children yenow (Leau	0.00			OSHA
chromate pigment)	mg/m3	(TWA):		OSHA
	mg/m3 0.03	• •		OSHA OSHA
	mg/m3 0.03 mg/m3	(TWA): OSHA Action level:		OSHA
	mg/m3 0.03 mg/m3 0.01	(TWA): OSHA Action level: Time Weighted Average	as Cr	
	mg/m3 0.03 mg/m3 0.01 mg/m3	(TWA): OSHA Action level: Time Weighted Average (TWA):		OSHA ACGIH
	mg/m3 0.03 mg/m3 0.01 mg/m3 0.05	(TWA): OSHA Action level: Time Weighted Average (TWA): Time Weighted Average	as Cr as Pb	OSHA
	mg/m3 0.03 mg/m3 0.01 mg/m3 0.05 mg/m3	(TWA): OSHA Action level: Time Weighted Average (TWA): Time Weighted Average (TWA):	as Pb	OSHA ACGIH ACGIH
	mg/m3 0.03 mg/m3 0.01 mg/m3 0.05	(TWA): OSHA Action level: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average		OSHA ACGIH ACGIH
chromate pigment)	mg/m3 0.03 mg/m3 0.01 mg/m3 0.05 mg/m3 1 mg/m3	(TWA): OSHA Action level: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL:	as Pb	OSHA ACGIH ACGIH OSHA ZI ACGIH
chromate pigment)	mg/m3 0.03 mg/m3 0.01 mg/m3 0.05 mg/m3 1 mg/m3 10 mg/m3	(TWA): OSHA Action level: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA):	as Pb as Cr	OSHA ACGIH ACGIH OSHA ZI ACGIH
chromate pigment)	mg/m3 0.03 mg/m3 0.01 mg/m3 0.05 mg/m3 1 mg/m3 10 mg/m3 15 mg/m3	(TWA): OSHA Action level: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA):	as Pb as Cr Total dust.	OSHA ACGIH ACGIH OSHA ZI ACGIH
chromate pigment)	mg/m3 0.03 mg/m3 0.01 mg/m3 0.05 mg/m3 1 mg/m3 10 mg/m3 15 mg/m3	(TWA): OSHA Action level: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	as Pb as Cr Total dust.	OSHA ACGIH ACGIH OSHA ZI ACGIH
chromate pigment) Titanium dioxide	mg/m3 0.03 mg/m3 0.01 mg/m3 0.05 mg/m3 1 mg/m3 10 mg/m3 15 mg/m3	(TWA): OSHA Action level: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	as Pb as Cr Total dust. OPERTIES	OSHA ACGIH ACGIH OSHA ZI ACGIH OSHA ZI
chromate pigment) Chromate pigment Chromate	mg/m3 0.03 mg/m3 0.01 mg/m3 0.05 mg/m3 1 mg/m3 10 mg/m3 15 mg/m3 <b>9. PHYSIC</b> : Solid	(TWA): OSHA Action level: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	as Pb as Cr Total dust. OPERTIES oration rate : No fic Gravity: : No	OSHA ACGIH ACGIH OSHA ZI ACGIH OSHA ZI
chromate pigment)  chromate pigment)  Titanium dioxide  Form Appearance	mg/m3 0.03 mg/m3 0.01 mg/m3 0.05 mg/m3 1 mg/m3 10 mg/m3 15 mg/m3 <b>9. PHYSIC</b> : Solid : Pellet	(TWA): OSHA Action level: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Evaports EN Bulk of Comparison of Compar	as Pb as Cr Total dust. DPERTIES Dration rate : No fic Gravity: : No density : No	OSHA ACGIH ACGIH OSHA Z1 ACGIH OSHA Z1 OSHA Z1
chromate pigment) chromate pigment) Titanium dioxide Form Appearance Color Odor	mg/m3 0.03 mg/m3 0.01 mg/m3 0.05 mg/m3 1 mg/m3 10 mg/m3 15 mg/m3 <b>9. PHYSIC</b> : Solid : Pellet : GREL : Very	(TWA): OSHA Action level: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Evaports Evaports EN Bulk of faint Vapor	as Pb as Cr Total dust. OPERTIES OPERTIES OPERTIES OPERTIES OPERTIES OPERTIES OPERTIES OPERTIES	OSHA ACGIH ACGIH OSHA Z1 ACGIH OSHA Z1 OSHA Z1
chromate pigment)  chromate pigment)  Titanium dioxide  Form Appearance Color	mg/m3 0.03 mg/m3 0.01 mg/m3 0.05 mg/m3 1 mg/m3 10 mg/m3 15 mg/m3 <b>9. PHYSIC</b> : Solid : Pellet : GREL : Very : Not d	(TWA): OSHA Action level: Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Evaports Evaports EN Bulk of faint Vapor	as Pb as Cr Total dust. OPERTIES oration rate : Note fic Gravity: : Note density : Note pressure : Note pressure : Note ur density : Note or density : Note or density : Note or density : Note or density : Note	OSHA ACGIH ACGIH OSHA Z1 ACGIH OSHA Z1 OSHA Z1 OSHA Z1

### 10. STABILITY AND REACTIVITY

### MATERIAL SAFETY DATA SHEET SLIME GREEN

Version Number 1.0 Revision Date 05/05/2005

Page 4 of 7 Print Date 11/17/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1344-37-2	Chrome yellow (Lead chromate pigment)	Systemic effects	central nervous system (CNS), reproductive system.

#### Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1344-37-2	Chrome yellow (Lead	no	1	no
	chromate pigment)			

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

### Additional Health Hazard Information:

Chrome yellow (Lead chromate pigment) 1344-37-2 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

### **12. ECOLOGICAL INFORMATION**

Persistence and degradability

: Not readily biodegradable.



## MATERIAL SAFETY DATA SHEET SLIME GREEN

Page 5 Print Date 11/17/2
: Chemicals are not readily available as they are bound within the polymer matrix.
: Chemicals are not readily available as they are bound within the polymer matrix.
: No data available
13. DISPOSAL CONSIDERATIONS
: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
14. TRANSPORT INFORMATION
: Not regulated for transportation.
: Refer to specific regulation.
: Refer to specific regulation.
15. REGULATORY INFORMATION
: Classified as hazardous based on components.
: All components of this product are listed on or exempt from the TSCA Inventory.
s Substances (40 CFR 302)
: WARNING! This product contains a chemical known to the State of California to cause cancer., WARNING! This product contains a chemical known to the State of California to cause birth defects or

PolyOne

### MATERIAL SAFETY DATA SHEET SLIME GREEN

Version Number 1.0 Revision Date 05/05/2005

Page 6 of 7 Print Date 11/17/2011

other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
CHROMIUM VI COMPOUNDSLEAD	1344-37-2	20.32
COMPOUNDS, INORGANICLEAD		
COMPOUNDS		

**Canadian Regulations:** 

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight %	NPRI ID#
Chrome yellow (Lead chromate pigment)	1344-37-2	20.32	235
Chrome yellow (Lead chromate pigment)	1344-37-2	20.32	236
Phthalocyanine green	1328-53-6	0.32	71

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
1344-37-2

DSL

: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Listed
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Not determined

Philippines PICCS : Not determined

### **16. OTHER INFORMATION**



MATERIAL SAFETY DATA SHEET SLIME GREEN

Version Number 1.0 Revision Date 05/05/2005 Page 7 of 7 Print Date 11/17/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.