MATERIAL SAFETY DATA SHEET

SILVER

Version Number 1.0 Revision Date 06/14/2005 Page 1 of 6 Print Date 11/18/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	SILVER
Product code	:	CC10071195
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	1 - 5
Aluminum	7429-90-5	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	Inhalation, Ingestion, Skin contact	
Acute exposure		
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. 	
Skin	: Experience shows no unusual dermatitis hazard from routine handling.	
Chronic exposure	: Refer to Section 11 for Toxicological Information.	
Medical Conditions Aggravated by Exposure:	: None known.	



MATERIAL SAFETY DATA SHEET **SILVER**

Version Number 1.0 Revision Date 06/14/2005 Page 2 of 6 Print Date 11/18/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET **SILVER**

Version Number 1.0 Revision Date 06/14/2005 Page 3 of 6 Print Date 11/18/2011

8. F	EXPOSURE	CONTROLS / PERSONAL	PROTECTION			
Respiratory protection	: N	o personal respiratory protect	tive equipment normally r	equired.		
Eye/Face Protection	: S	afety glasses with side-shields	s.			
Hand protection	: P	: Protective gloves.				
Skin and body protection	: L	: Long sleeved clothing.				
Additional Protective Measures	: S	afety shoes.				
General Hygiene Considerations		andle in accordance with good Vash hands before breaks and		afety practice		
Engineering measures		leat only in areas with appropriate exhaust ventilation		Provide		
Exposure limit(s)						
Components	Value	Exposure time	Exposure type	List:		
Aluminum	10 mg/m3	Time Weighted Average (TWA):	Dust.	ACGIH		
	15 mg/m3	PEL:	Total dust. as Al	OSHA Z1		
	5 mg/m3	PEL:	Respirable dust. as Al	OSHA Z1		
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1		
	15 mg/m3	PEL:	Total dust.	OSHA Z1		
	9. PHYSIC	CAL AND CHEMICAL PRO	OPERTIES			
Form	: Solic	l Evapo	oration rate : Not	applicable		
Appearance	: Pelle			determined		
Color	: GRE	Y Bulk of	density : Not	established		
Odor	: Very			applicable		
Melting point/range				applicable		
Boiling Point:		applicable pH	: Not	applicable		
Water solubility	: Insol	uble				
	10. 8	STABILITY AND REACTI	VITY			
Q4.1.:1:4	: S	table.				
Stability		Vill not occur.				
Hazardous Polymerization	n : V					

<u>PolyOne</u>.

MATERIAL SAFETY DATA SHEET **SILVER**

Version Number 1.0 Revision Date 06/14/2005

Page 4 of 6 Print Date 11/18/2011

Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.

ILVER rsion Number 1.0	
rsion Number 1.0 vision Date 06/14/2005	
	Page 5 Print Date <i>11/18/</i> 2
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
California Proposition 65	: Not applicable
California Proposition 65 SARA Title III Section 302 Ex Not applicable	
65 SARA Title III Section 302 Ex	tremely Hazardous Substance
65 SARA Title III Section 302 Ex Not applicable SARA Title III Section 313 To Chemical Name	tremely Hazardous Substance oxic Chemicals: CAS-No. Weight %
65 SARA Title III Section 302 Ex Not applicable SARA Title III Section 313 To	tremely Hazardous Substance oxic Chemicals: CAS-No. Weight %
65 SARA Title III Section 302 Ex Not applicable SARA Title III Section 313 To Chemical Name	tremely Hazardous Substance oxic Chemicals: CAS-No. Weight %
65 SARA Title III Section 302 Ex Not applicable SARA Title III Section 313 To Chemical Name ALUMINUM (FUME OR D Canadian Regulations:	tremely Hazardous Substance oxic Chemicals: CAS-No. Weight % PUST) 7429-90-5 10.00 - 30.00
65 SARA Title III Section 302 Ex Not applicable SARA Title III Section 313 To Chemical Name ALUMINUM (FUME OR D	tremely Hazardous Substance oxic Chemicals: CAS-No. Weight % PUST) 7429-90-5 10.00 - 30.00



MATERIAL SAFETY DATA SHEET **SILVER**

Version Number 1.0 Revision Date 06/14/2005

Page 6 of 6 Print Date 11/18/2011

National Inventories:

Australia AICS	: Listed
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Listed
Philippines PICCS	: Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.