## MATERIAL SAFETY DATA SHEET **SANDSTONE GRAY NYL**

Version Number 1.0 Revision Date 06/10/2005 Page 1 of 6 Print Date 11/18/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	SANDSTONE GRAY NYL
Product code	:	CC10071234
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous, precipitated and gel	112926-00-8	1 - 5
Titanium dioxide	13463-67-7	30 - 60

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> </ul>		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure Medical Conditions	<ul><li>Refer to Section 11 for Toxicological Information.</li><li>None known.</li></ul>		
Aggravated by Exposure:			

PolyOne.

# MATERIAL SAFETY DATA SHEET **SANDSTONE GRAY NYL**

Version Number 1.0 Revision Date 06/10/2005 Page 2 of 6 Print Date 11/18/2011

Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	<ul><li>Not applicable</li><li>Not applicable</li></ul>
Autoignition temperature Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

PolyOne.

# MATERIAL SAFETY DATA SHEET **SANDSTONE GRAY NYL**

Version Number 1.0 Revision Date 06/10/2005 Page 3 of 6 Print Date 11/18/2011

8. 1	EXPOSURE	CONTROLS / PERSC	NAL	PROTECTION	
Respiratory protection	: N	o personal respiratory p	rotecti	ve equipment normally	required.
Eye/Face Protection	: S	afety glasses with side-s	hields		
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		andle in accordance wit Vash hands before break			safety practic
Engineering measures		leat only in areas with appropriate exhaust venti			Provide
Exposure limit(s)					
Components	Value	Exposure time		Exposure type	List:
Silica, amorphous,	10 mg/m3	Time Weighted Aver	age	Dust.	ACGIH
precipitated and gel	e	(TWA):	U		
	5 mg/m3	PEL:		Respirable fraction.	OSHA Z
	15 mg/m3	PEL:		Total dust.	OSHA ZI
	0.8 mg/m3	Time Weighted Aver (TWA):	age		Z3
Titanium dioxide	10 mg/m3	Time Weighted Aver (TWA):	age		ACGIH
	15 mg/m3	PEL:		Total dust.	OSHA Z
	9. PHYSIC	CAL AND CHEMICA	L PRC	PERTIES	
Form	: Solid		Fuence	ration rate : Not	applicable
Appearance	: Pelle				t determined
Color	: GRE		Bulk d		t established
Odor	: Very			2	applicable
Melting point/range					applicable
Boiling Point:			рН		applicable
Water solubility	: Insol				
	10. 8	STABILITY AND REA	CTIV	ЛТҮ	
Stability	: S	table.			

<u>PolyOne</u>

# MATERIAL SAFETY DATA SHEET SANDSTONE GRAY NYL

Version Number 1.0 Revision Date 06/10/2005	Page 4 of 6 Print Date <i>11/18/2011</i>
Conditions to avoid	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

**Toxicity Overview** 

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
112926-00-8	Silica, amorphous, precipitated and gel	Irritant	Respiratory system, Eyes.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Persistence and degradability	lot readily biodegradable.	
Environmental Toxicity	Chemicals are not readily available as to olymer matrix.	they are bound within the
Bioaccumulation Potential	Chemicals are not readily available as to olymer matrix.	they are bound within the
Additional advice	lo data available	
	DISPOSAL CONSIDERATIONS	
Product	ike most thermoplastic plastics the prossible recycling is preferred to dispo enerator of waste material has the resp lassification, transportation and dispos pplicable federal, state/provincial and	sal or incineration. The ponsibility for proper waste sal in accordance with
Contaminated packaging	accycling is preferred when possible. as the responsibility for proper waste and disposal in accordance with applicand local regulations.	classification, transportation
	TRANSPORT INFORMATION	

PolyOne.

# MATERIAL SAFETY DATA SHEET **SANDSTONE GRAY NYL**

Version Number 1.0 Revision Date 06/10/2005 Page 5 of 6 Print Date 11/18/2011

U.S. DOT Classification		•	or transportation.		
ICAO/IATA (air)	:	Refer to specific	c regulation.		
IMO / IMDG (maritime)	:	Refer to specific	c regulation.		
	15	5. REGULATOR	<b>XY INFORMATI</b>	ON	
US Regulations:					
OSHA Status	:	Classified as ha	zardous based on	components.	
TSCA Status	:	All components Inventory.	s of this product ar	e listed on or exem	pt from the TS
US. EPA CERCLA Hazardou	s Sub	stances (40 CFR	302)		
Not applicable					
California Proposition	:	Not applicable			
65 SARA Title III Section 302 E Not applicable	xtrem	ely Hazardous Su	ibstance		
65 SARA Title III Section 302 E		-	ibstance		
65 SARA Title III Section 302 E Not applicable SARA Title III Section 313 To Not applicable Canadian Regulations: National Pollutant Rele	oxic (	Chemicals:		Weight %	
65 SARA Title III Section 302 E Not applicable SARA Title III Section 313 To Not applicable Canadian Regulations:	oxic (	Chemicals:	bstance CAS-No. 1344-28-1	Weight % 0.10 - 1.00	NPRI ID# 13
65 SARA Title III Section 302 E Not applicable SARA Title III Section 313 To Not applicable Canadian Regulations: <u>National Pollutant Rele</u> <u>Chemical Name</u>	oxic ( ease I	Chemicals: nventory (NPRI) D2B All component:	CAS-No. 1344-28-1	0.10 - 1.00 re on the Canadian	13
65 SARA Title III Section 302 E Not applicable SARA Title III Section 313 To Not applicable Canadian Regulations: <u>National Pollutant Rele</u> <u>Chemical Name</u> <u>Aluminum oxide</u> WHMIS Classification	oxic ( ease I	Chemicals: nventory (NPRI) D2B All component:	CAS-No. 1344-28-1 s of this product a	0.10 - 1.00 re on the Canadian	13
65 SARA Title III Section 302 E: Not applicable SARA Title III Section 313 To Not applicable Canadian Regulations: <u>National Pollutant Rele</u> <u>Chemical Name</u> <u>Aluminum oxide</u> WHMIS Classification DSL	oxic ( ease I	Chemicals: nventory (NPRI) D2B All component:	CAS-No. 1344-28-1 s of this product a	0.10 - 1.00 re on the Canadian	13

ŀ	bl	vOne.
_		

### MATERIAL SAFETY DATA SHEET SANDSTONE GRAY NYL

Version Number 1.0 Revision Date 06/10/2005 Page 6 of 6 Print Date 11/18/2011

Europe EINECS	: Listed	
Japan ENCS	: Not determine	d
Korea KECI	: Listed	
Philippines PICCS	: Listed	

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.