

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****ORANGE 016**Version Number 1.1
Revision Date 07/09/2007Page 1 of 7
Print Date 11/29/2011**1. PRODUCT AND COMPANY IDENTIFICATION****POLYONE CORPORATION**
33587 Walker Road, Avon Lake, OH 44012Telephone : Product Stewardship (770) 271-5902
Emergency telephone : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**Product name : ORANGE 016
Product code : CC10101037
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications**2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS**

| Components | CAS-No. | Weight % |
|--------------------------------|------------|----------|
| Titanium dioxide | 13463-67-7 | 1 - 5 |
| Rutile, antimony chromium buff | 68186-90-3 | 10 - 30 |

3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS**Routes of Exposure:** : Inhalation, Ingestion, Skin contact**Acute exposure**Inhalation : Resin particles, like other inert materials, can be mechanically irritating.
Ingestion : May be harmful if swallowed.
Eyes : Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin : Experience shows no unusual dermatitis hazard from routine handling.**Chronic exposure** : Refer to Section 11 for Toxicological Information.**Medical Conditions** : None known.**Aggravated by Exposure:**

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

ORANGE 016

Version Number 1.1
Revision Date 07/09/2007

Page 2 of 7
Print Date 11/29/2011

4. FIRST AID MEASURES

- Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
- Ingestion : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
- Eyes : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
- Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIRE-FIGHTING MEASURES

- Flash point : Not applicable
- Flammable Limits
 - Upper explosion limit : Not applicable
 - Lower explosion limit : Not applicable
- Autoignition temperature : Not applicable
- Suitable extinguishing media : Carbon dioxide blanket, Water spray, Dry powder, Foam.
- Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
- Unusual Fire/Explosion Hazards : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
- Environmental precautions : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
- Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

- Handling : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
- Storage : Keep containers dry and tightly closed to avoid moisture absorption

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

ORANGE 016

Version Number 1.1
Revision Date 07/09/2007

Page 3 of 7
Print Date 11/29/2011

and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Respiratory protection : No personal respiratory protective equipment normally required.
- Eye/Face Protection : Safety glasses with side-shields
- Hand protection : Protective gloves
- Skin and body protection : Long sleeved clothing
- Additional Protective Measures : Safety shoes
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
- Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

| Components | Value | Exposure time | Exposure type | List: |
|--------------------------------|-----------|-----------------------------------|---------------|---------|
| Rutile, antimony chromium buff | 0.5 mg/m3 | Time Weighted Average (TWA): | as Cr | ACGIH |
| | 0.5 mg/m3 | PEL: | as Cr | OSHA Z1 |
| | 0.5 mg/m3 | Time Weighted Average (TWA): | | MX OEL |
| | 0.5 mg/m3 | Time Weighted Average (TWA): | as Sb | ACGIH |
| Titanium dioxide | 0.5 mg/m3 | PEL: | as Sb | OSHA Z1 |
| | 0.5 mg/m3 | Time Weighted Average (TWA): | as Sb | MX OEL |
| | 10 mg/m3 | Time Weighted Average (TWA): | | ACGIH |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| Titanium dioxide | 10 mg/m3 | Time Weighted Average (TWA): | as Ti | MX OEL |
| | 20 mg/m3 | Short Term Exposure Limit (STEL): | as Ti | MX OEL |

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form : Solid
- Appearance : pellets
- Color : ORANGE
- Odour : Very faint
- Melting point/range : Not determined
- Evaporation rate : Not applicable
- Specific Gravity : Not determined
- Bulk density : Not established
- Vapour pressure : Not applicable
- Vapour density : Not applicable

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

ORANGE 016

Version Number 1.1
Revision Date 07/09/2007

Page 5 of 7
Print Date 11/29/2011

12. ECOLOGICAL INFORMATION

- Persistence and degradability : Not readily biodegradable.
- Environmental Toxicity : Chemicals are not readily available as they are bound within the polymer matrix.
- Bioaccumulation Potential : Chemicals are not readily available as they are bound within the polymer matrix.
- Additional advice : No data available

13. DISPOSAL CONSIDERATIONS

- Product : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
- Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

- U.S. DOT Classification : Not regulated for transportation.
- ICAO/IATA (air) : Refer to specific regulation.
- IMO / IMDG (maritime) : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

- OSHA Status : Classified as hazardous based on components.
- TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

ORANGE 016

Version Number 1.1
Revision Date 07/09/2007

Page 6 of 7
Print Date 11/29/2011

California Proposition : Not applicable
65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

| Chemical Name | CAS-No. | Weight % |
|--|------------|---------------|
| CHROMIUM III COMPOUNDSANTIMONY COMPOUNDS | 68186-90-3 | 10.00 - 30.00 |

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name | CAS-No. | Weight % | NPRI ID# |
|--------------------------------|------------|---------------|----------|
| Rutile, antimony chromium buff | 68186-90-3 | 10.00 - 30.00 | 69 |
| | | 10.00 - 30.00 | 17 |

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

| |
|------------|
| CAS-No. |
| 68186-90-3 |

DSL : DSL status has not been determined. Quantity use in Canada may be restricted by regulations.

National Inventories:

Australia AICS : Not determined

China IECS : Not determined

Europe EINECS : Not determined

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined



POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

ORANGE 016

Version Number 1.1
Revision Date 07/09/2007

Page 7 of 7
Print Date 11/29/2011

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.