## MATERIAL SAFETY DATA SHEET **PG 142147.02 BU PP SL**

Version Number 1.0 Revision Date 05/20/2008 Page 1 of 6 Print Date 1/3/2012

#### 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	PG 142147.02 BU PP SL
Product code :	CC10111166
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	30 - 60

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: Irritating to eyes and respiratory system.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

# MATERIAL SAFETY DATA SHEET **PG 142147.02 BU PP SL**

Version Number 1.0 Revision Date 05/20/2008 Page 2 of 6 Print Date 1/3/2012

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Seek medical attention after significant exposure.
Ingestion	: Do not induce vomiting without medical advice. Seek medical attention if necessary.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Greater than 200 °F (93 °C)
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Dry powder, Foam.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

PolyOne.

## MATERIAL SAFETY DATA SHEET PG 142147.02 BU PP SL

Version Number 1.0 Revision Date 05/20/2008

Water solubility

Page 3 of 6 Print Date 1/3/2012

8	. EXPOSURE	CONTROLS/PERSONAL	PROTECTION	
Respiratory protection	: U	Inder normal handling condition	ons a respirator may not b	e required.
Eye/Face Protection	: S	afety glasses with side-shields		
Hand protection	: P	rotective gloves		
Skin and body protectio	n : L	ong sleeved clothing		
Additional Protective Measures	: S	afety shoes		
General Hygiene Considerations		landle in accordance with good ractice. Wash hands before br		
Engineering measures		leat only in areas with appropri ppropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Components Silica, amorphous	Value 0.8 mg/m3	Exposure time Time Weighted Average	Exposure type	List: Z3
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
		Time Weighted Average (TWA): Time Weighted Average (TWA):	Exposure type Inhalable particulate.	
Silica, amorphous	0.8 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA):		Z3
	0.8 mg/m3 10 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA):	Inhalable particulate.	Z3 MX OEL MX OEL ACGIH
Silica, amorphous	0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3 15 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL:	Inhalable particulate. Respirable dust. Total dust.	Z3 MX OEL MX OEL ACGIH OSHA Z1
Silica, amorphous	0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA):	Inhalable particulate. Respirable dust.	Z3 MX OEL MX OEL ACGIH
Silica, amorphous	0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3 15 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average	Inhalable particulate. Respirable dust. Total dust.	Z3 MX OEL MX OEL ACGIH OSHA Z1
Silica, amorphous	0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL):	Inhalable particulate. Respirable dust. Total dust. as Ti as Ti	Z3 MX OEL MX OEL ACGIH OSHA Z1 MX OEL
Silica, amorphous	0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit	Inhalable particulate. Respirable dust. Total dust. as Ti as Ti	Z3 MX OEL MX OEL ACGIH OSHA Z1 MX OEL
Silica, amorphous Titanium dioxide Form	0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liquin	Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Inhalable particulate. Respirable dust. Total dust. as Ti as Ti DPERTIES ration rate : Not	Z3 MX OEL MX OEL ACGIH OSHA Z1 MX OEL MX OEL
Silica, amorphous Titanium dioxide Form Appearance	0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liquit : Visco	Time Weighted Average (TWA):         Time Weighted Average (TWA):         Time Weighted Average (TWA):         Time Weighted Average (TWA):         PEL:         Time Weighted Average (TWA):         Short Term Exposure Limit (STEL):         CAL AND CHEMICAL PRO ous, liquid	Inhalable particulate. Respirable dust. Total dust. as Ti as Ti DPERTIES ration rate : Not ic Gravity : Not	Z3 MX OEL MX OEL ACGIH OSHA Z1 MX OEL MX OEL MX OEL
Silica, amorphous Titanium dioxide Form Appearance Color	0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 <b>9. PHYSIC</b> : liquic : Visco : BLU	Time Weighted Average (TWA):         Time Weighted Average (TWA):         Time Weighted Average (TWA):         Time Weighted Average (TWA):         PEL:         Time Weighted Average (TWA):         Short Term Exposure Limit (STEL):         CAL AND CHEMICAL PRODUCTION (STEL):         d       Evapor Specific         bulk d	Inhalable particulate. Respirable dust. Total dust. as Ti as Ti DPERTIES ration rate : Not ic Gravity : Not ensity : Not	Z3 MX OEL MX OEL ACGIH OSHA Z1 MX OEL MX OEL MX OEL
Silica, amorphous Titanium dioxide Form Appearance Color Odour	0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liquic : Visc. : BLU : Very	Time Weighted Average (TWA):         Short Term Exposure Limit (STEL):         CAL AND CHEMICAL PRODUCTION (STEL):         d       Evapor Specific         b       Bulk d         f       f         f       Yapou	Inhalable particulate. Respirable dust. Total dust. as Ti as Ti DPERTIES ration rate : Not ic Gravity : Not ensity : Not r pressure : Not	Z3 MX OEL MX OEL ACGIH OSHA Z1 MX OEL MX OEL MX OEL
Silica, amorphous Titanium dioxide Form Appearance Color Odour Melting point/range	0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liquit : Viscu : BLU : Very : Not a	Time Weighted Average (TWA):         Time Weighted Average (TWA):         Time Weighted Average (TWA):         Time Weighted Average (TWA):         PEL:         Time Weighted Average (TWA):         PEL:         Time Weighted Average (TWA):         Short Term Exposure Limit (STEL):         CAL AND CHEMICAL PRO d         E       Bulk d         faint       Vapou         applicable       Vapou	Inhalable particulate. Respirable dust. Total dust. as Ti as Ti DPERTIES ration rate : Not ic Gravity : Not ensity : Not r pressure : Not r density : Not	Z3 MX OEL MX OEL ACGIH OSHA Z1 MX OEL MX OEL MX OEL established determined applicable determined
Silica, amorphous Titanium dioxide Form Appearance Color Odour	0.8 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3 10 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3 9. PHYSIC : liquit : Visco : BLU : Very : Not a : Not a	Time Weighted Average (TWA):         Short Term Exposure Limit (STEL):         CAL AND CHEMICAL PRODUCTION (STEL):         d       Evapor Specific         b       Bulk d         f       f         f       Yapou	Inhalable particulate. Respirable dust. Total dust. as Ti as Ti DPERTIES ration rate : Not ic Gravity : Not ensity : Not r pressure : Not r density : Not	Z3 MX OEL MX OEL ACGIH OSHA Z1 MX OEL MX OEL MX OEL

### **10. STABILITY AND REACTIVITY**

: Immiscible

# MATERIAL SAFETY DATA SHEET **PG 142147.02 BU PP SL**

Version Number 1.0 Revision Date 05/20/2008 Page 4 of 6 Print Date 1/3/2012

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
7631-86-9	Silica, amorphous	Oral LD50Oral	15,000 mg/kg22,500	mouserat
		LD50	mg/kg	

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

### **12. ECOLOGICAL INFORMATION**

PolyOne.

# MATERIAL SAFETY DATA SHEET **PG 142147.02 BU PP SL**

eadily biodegradable. rse ecological impact is not known or expected under normal not bioaccumulate. ta available POSAL CONSIDERATIONS e possible recycling is preferred to disposal or incineration. Thator of waste material has the responsibility for proper waste fication, transportation and disposal in accordance with eable federal, state/provincial and local regulations. cling is preferred when possible. The generator of waste ial has the responsibility for proper waste classification, ortation and disposal in accordance with applicable federal, provincial and local regulations.
not bioaccumulate. ta available <b>POSAL CONSIDERATIONS</b> e possible recycling is preferred to disposal or incineration. Thator of waste material has the responsibility for proper waste fication, transportation and disposal in accordance with vable federal, state/provincial and local regulations. eling is preferred when possible. The generator of waste ial has the responsibility for proper waste classification, ortation and disposal in accordance with applicable federal,
ta available <b>POSAL CONSIDERATIONS</b> e possible recycling is preferred to disposal or incineration. Th ator of waste material has the responsibility for proper waste fication, transportation and disposal in accordance with vable federal, state/provincial and local regulations. eling is preferred when possible. The generator of waste ial has the responsibility for proper waste classification, ortation and disposal in accordance with applicable federal,
POSAL CONSIDERATIONS e possible recycling is preferred to disposal or incineration. Thator of waste material has the responsibility for proper waste fication, transportation and disposal in accordance with able federal, state/provincial and local regulations. Eling is preferred when possible. The generator of waste ial has the responsibility for proper waste classification, ortation and disposal in accordance with applicable federal,
e possible recycling is preferred to disposal or incineration. Thator of waste material has the responsibility for proper waste fication, transportation and disposal in accordance with table federal, state/provincial and local regulations.
ator of waste material has the responsibility for proper waste fication, transportation and disposal in accordance with able federal, state/provincial and local regulations. Eling is preferred when possible. The generator of waste ial has the responsibility for proper waste classification, ortation and disposal in accordance with applicable federal,
ial has the responsibility for proper waste classification, ortation and disposal in accordance with applicable federal,
ANSPORT INFORMATION
gulated for transportation.
gulated for transportation.
egulated for transportation.
ULATORY INFORMATION
fied as hazardous based on components.
omponents of this product are listed on or exempt from the Inventory.
(40 CFR 302)
5

# MATERIAL SAFETY DATA SHEET **PG 142147.02 BU PP SL**

Version Number 1.0 Revision Date 05/20/2008

Page 6 of 6 Print Date 1/3/2012

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Phenol, nonyl-, phosphite (3:1)	26523-78-4	1.00 - 5.00	
Phthalocyanine blue	147-14-8	0.10 - 1.00	

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
7631-86-9

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Listed
China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Listed
Philippines PICCS	: Listed

:

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.