## MATERIAL SAFETY DATA SHEET SILVER SATIN TRANSLUCENT

Version Number 1.0 Revision Date 06/10/2008 Page 1 of 6 Print Date 1/4/2012

## 1. PRODUCT AND COMPANY IDENTIFICATION

## POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	SILVER SATIN TRANSLUCENT
Product code	:	CC10111208
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

## 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Aluminum	7429-90-5	1 - 5

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

## POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

# MATERIAL SAFETY DATA SHEET SILVER SATIN TRANSLUCENT

Version Number 1.0 Revision Date 06/10/2008 Page 2 of 6 Print Date 1/4/2012

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit	:	Not applicable
Lower explosion limit	:	Not applicable
Autoignition temperature	:	Not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

PolyOne.

# MATERIAL SAFETY DATA SHEET SILVER SATIN TRANSLUCENT

Version Number 1.0 Revision Date 06/10/2008 Page 3 of 6 Print Date 1/4/2012

8. 1	EXPOSURE	CONTROLS/PERSO	NAL PROTECT	ION	
Respiratory protection	: N	lo personal respiratory p	rotective equipme	nt normally r	equired.
Eye/Face Protection	: S	afety glasses with side-	hields		
Hand protection	: P	rotective gloves			
Skin and body protection	: L	ong sleeved clothing			
Additional Protective Measures	: S	afety shoes			
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures	asures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure time	Expos	ure type	List:
Aluminum	10 mg/m3	Time Weighted Ave (TWA):		ust.	ACGIH
	5 mg/m3	Time Weighted Ave (TWA):	• • •	c powder. as Al	ACGIH
	15 mg/m3	PEL:	Total di	ust. as Al	OSHA Z
	5 mg/m3	PEL:	Respirable	e dust. as Al	OSHA ZI
	5 mg/m3	Time Weighted Ave (TWA):	rage Pyrophor	ric powder.	MX OEL
	10 mg/m3	Time Weighted Ave (TWA):	rage D	ust.	MX OEL
	9. PHYSIC	CAL AND CHEMICA	L PROPERTIES		
Form	: Solic	1	Evaporation rate	: Not	applicable
Appearance	: pelle		Specific Gravity : Not		determined
Color	: GRE		Bulk density : Not esta		established
Odour		faint	Vapour pressure		
Melting point/range			Vapour density		applicable
Boiling Point:			pН	: Not	applicable
Water solubility	: Insol	uble			
	10.5	STABILITY AND REA	CTIVITY		

# MATERIAL SAFETY DATA SHEET SILVER SATIN TRANSLUCENT

 Version Number 1.0
 Page 4 of 6

 Revision Date 06/10/2008
 Print Date 1/4/2012

 Hazardous Polymerization
 : Will not occur.

 Conditions to avoid
 : Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.Incompatible Materials:Hazardous decomposition<br/>products:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen<br/>(NOx), other hazardous materials, and smoke are all possible.

## 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory
			system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION

# MATERIAL SAFETY DATA SHEET SILVER SATIN TRANSLUCENT

Version Number 1.0 Page 5 of 6 Print Date 1/4/2012 Revision Date 06/10/2008 U.S. DOT Classification : Not regulated for transportation. Refer to specific regulation. ICAO/IATA (air) : IMO / IMDG (maritime) : Refer to specific regulation. **15. REGULATORY INFORMATION US Regulations: OSHA Status** · Classified as hazardous based on components. **TSCA Status** All components of this product are listed on or exempt from the : TSCA Inventory. US. EPA CERCLA Hazardous Substances (40 CFR 302) Not applicable California Proposition : Not applicable 65 SARA Title III Section 302 Extremely Hazardous Substance Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation SARA Title III Section 313 Toxic Chemicals: Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation Chemical Name CAS-No. Weight % ALUMINUM (FUME OR DUST) 7429-90-5 1.00 - 5.00 Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name CAS-No. Weight % NPRI ID# 1.00 - 5.00 Aluminum 7429-90-5 WHMIS Classification : D2B WHMIS Ingredient Disclosure List

PolyOne

# MATERIAL SAFETY DATA SHEET SILVER SATIN TRANSLUCENT

Version Number 1.0 Revision Date 06/10/2008 Page 6 of 6 Print Date 1/4/2012

CAS-No. 7429-90-5	
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS	: Not determined
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Listed
Philippines PICCS	: Not determined
	16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.