PolvOne

MATERIAL SAFETY DATA SHEET SHARPIE GRAY

Version Number 1.0 Revision Date 06/03/2008 Page 1 of 7 Print Date 1/4/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	SHARPIE GRAY
Product code :	CC10111946
Chemical Name :	Mixture
CAS-No.	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	0.1 - 1
Calcium carbonate	1317-65-3	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **SHARPIE GRAY**

Version Number 1.0 Revision Date 06/03/2008 Page 2 of 7 Print Date 1/4/2012

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat



MATERIAL SAFETY DATA SHEET SHARPIE GRAY

Version Number 1.0	Page 3 of 7
Revision Date 06/03/2008	Print Date 1/4/2012
	only in areas with appropriate exhaust ventilation.
Storage :	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXPOSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection :	No personal respiratory protective equipment normally required.
Eye/Face Protection :	Safety glasses with side-shields
Hand protection :	Protective gloves
Skin and body protection :	Long sleeved clothing
Additional Protective : Measures	Safety shoes
General Hygiene : Considerations	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures :	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	te 5 mg/m3 PEL:		Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit		MX OEL
		(STEL):		
Silica, amorphous	0.8 mg/m3	Time Weighted Average		Z3
		(TWA):		
	10 mg/m3	Time Weighted Average	Inhalable particulate.	MX OEL
		(TWA):		
	3 mg/m3	Time Weighted Average	Respirable dust.	MX OEL
		(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average	as Ti	MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
		(STEL):		

9. PHYSICAL AND CHEMICAL PROPERTIES

P<u>olyOne</u>

MATERIAL SAFETY DATA SHEET SHARPIE GRAY

Version Number 1.0 Revision Date 06/03/2008			Page 4 of 7 Print Date <i>1/4/2012</i>			
Form Appearance Color Odour Melting point/range Boiling Point: Water solubility	 Solid pellets GREY Very faint Not determined Not applicable Insoluble 	Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH	Not establishedNot applicable			
	10. STABILITY AND REACTIVITY					
Stability	: Stable.					
Hazardous Polymerization	Hazardous Polymerization : Will not occur.					
Conditions to avoid	e avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.					
Incompatible Materials	: Incompatible with	strong acids and oxidizing	g agents.			
Hazardous decomposition products		D2), carbon monoxide (C0 dous materials, and smoke	· ·			

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
7631-86-9	Silica, amorphous	Oral	15,000	mouserat
		LD50Oral	mg/kg22,500	
		LD50	mg/kg	

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP

PolyOne.

MATERIAL SAFETY DATA SHEET **SHARPIE GRAY**

13463-67-7 Т	itanium dioxide	no	2B	no	
2B - The component is po NTP Carcinogen Classific 1 - The component is know	inogenic to humans. obably carcinogenic to hum ossibly carcinogenic to huma	nns. en.			
	12. ECOLOGICA	L INFORMATION	N		
Persistence and degradabi	lity : Not readily biod	egradable.			
Environmental Toxicity	: Chemicals are no polymer matrix.	ot readily available	as they are bound	within the	
Bioaccumulation Potentia	l : Chemicals are no polymer matrix.	ot readily available	as they are bound	within the	
Additional advice	: No data availabl	e			
	13. DISPOSAL CO	ONSIDERATIONS	5		
Product Contaminated packaging	possible recyclin generator of was classification, tra applicable federa : Recycling is pret material has the transportation an	oplastic plastics the ng is preferred to dis the material has the ransportation and dis al, state/provincial a ferred when possibl responsibility for pr ad disposal in accord and local regulation	sposal or incinerat responsibility for p sposal in accordan- und local regulation e. The generator roper waste classif dance with applica	ion. The proper waste ce with ns. of waste fication,	
	14. TRANSPORT	INFORMATION			
U.S. DOT Classification	: Not regulated for	r transportation.			
ICAO/IATA (air)	: Refer to specific	: Refer to specific regulation.			
IMO / IMDG (maritime)	: Refer to specific	regulation.			
	15. REGULATOR	Y INFORMATIO	N		
US Regulations:					

P<u>olyOne</u>

MATERIAL SAFETY DATA SHEET SHARPIE GRAY

Version Number 1.0 Revision Date 06/03/2008 Page 6 of 7 Print Date 1/4/2012

TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight %	NPRI ID#
Aluminum oxide	1344-28-1	0.10 - 1.00	

	WHMIS Classification	:	D2A
	DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:			
	Australia AICS	:	Listed
	China IECS	:	Listed
	Europe EINECS	:	Listed
	Japan ENCS	:	Not determined
	Korea KECI	:	Listed
	Philippines PICCS	:	Listed

PolyOne

MATERIAL SAFETY DATA SHEET SHARPIE GRAY

Version Number 1.0 Revision Date 06/03/2008 Page 7 of 7 Print Date 1/4/2012

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.