### MATERIAL SAFETY DATA SHEET 114194 BNA LLDPE MASTERBATCH

Version Number 1.0 Revision Date 04/01/2014 Page 1 of 8 Print Date 4/9/2014

#### 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone : Emergency telephone : number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	114194 BNA LLDPE MASTERBATCH
Product code	:	CC10114194
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Carbon black	1333-86-4	1 - 5
Silica, amorphous	7631-86-9	1 - 5
Iron oxide	1309-37-1	5 - 10
Rutile, antimony chromium buff	68186-90-3	10 - 30
Titanium dioxide	13463-67-7	10 - 30

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.

PolyOne.

### MATERIAL SAFETY DATA SHEET 114194 BNA LLDPE MASTERBATCH

Version Number 1.0 Revision Date 04/01/2014 Page 2 of 8 Print Date 4/9/2014

	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits	
Upper explosion limit	: not applicable
Lower explosion limit	: not applicable
Auto-ignition temperature	: not applicable
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Hazards	(NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	<ul> <li>6. ACCIDENTAL RELEASE MEASURES</li> <li>Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.</li> </ul>
	: Wear appropriate personal protection during cleanup, such as

PolyOne.

# MATERIAL SAFETY DATA SHEET 114194 BNA LLDPE MASTERBATCH

### Version Number 1.0 Revision Date 04/01/2014

### Page 3 of 8 Print Date 4/9/2014

		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne.

# MATERIAL SAFETY DATA SHEET 114194 BNA LLDPE MASTERBATCH

Version Number 1.0 Revision Date 04/01/2014 Page 4 of 8 Print Date 4/9/2014

Components	Value	Exposure time	Exposure type	List:
Carbon black	3.5 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.1 mg/m3	Recommended exposure limit (REL):		NIOSH
	3.5 mg/m3	PEL:		OSHA Z1
	3.5 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	3.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	7 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Inhalable fraction.	ACGIH
Iron oxide	10 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
Rutile, antimony chromium buff	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Silica, amorphous	6 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL



### MATERIAL SAFETY DATA SHEET 114194 BNA LLDPE MASTERBATCH

#### Version Number 1.0 Revision Date 04/01/2014

\_

\_

	20 mg/m3	Short Term Exposure L (STEL):	imit as T	Гі	MX OEL
	9. PHYSIC	CAL AND CHEMICAL	PROPERTIES		
Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility		ts S WN E faint V determined V pplicable p	Evapouration rate Specific Gravity Bulk density Japour pressure Japour density H	: Not : Not : not : not	applicable determined established applicable applicable applicable
	10. 5	STABILITY AND REA	CTIVITY		
Stability Hazardous Polymerizatior		he product is stable if sto	ored and handled as	prescribed	
Conditions to avoid	: K	Leep away from oxidizing ecomposition, do not ove		ame. To a	void thermal
Incompatible Materials	: Iı	ncompatible with strong a	acids and oxidizing	agents.	
Hazardous decomposition products		°arbon dioxide (CO2), ca NOx), other hazardous m			

PolyOne

Page 5 of 8 Print Date 4/9/2014

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
68186-90-3	Rutile, antimony chromium buff	Irritant	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

## MATERIAL SAFETY DATA SHEET 114194 BNA LLDPE MASTERBATCH

Version Number 1.0 Revision Date 04/01/2014 Page 6 of 8 Print Date *4/9/2014* 

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste

PolyOne.

### MATERIAL SAFETY DATA SHEET 114194 BNA LLDPE MASTERBATCH

Version Number 1.0 Revision Date 04/01/2014

\_\_\_\_

\_

Page 7 of 8 Print Date 4/9/2014

	material has the respo transportation and dis state/provincial and h	sposal in accordance	waste classification, with applicable federal	l,
	14. TRANSPORT INF	FORMATION		
U.S. DOT Classification	: Not regulated for tran	nsportation.		
ICAO/IATA	: Refer to specific regu	lation.		
IMO/IMDG (maritime)	: Refer to specific regu	ilation.		
	15. REGULATORY IN	FORMATION		
US Regulations:				
OSHA Status	: Classified as hazardo	us based on compor	ients.	
TSCA Status	: All components of th TSCA Inventory.	nis product are listed	on or exempt from the	
US. EPA CERCLA Hazardou	us Substances (40 CFR 302)			
not applicable				
California Proposition 65	i : Not applicable			
SARA Title III Section 302 E	Extremely Hazardous Substan	ice		
Unless specific chemicals are	identified under this section,	, this product is Not	Applicable under this re	egulatio
SARA Title III Section 313 T	oxic Chemicals:			
Unless specific chemicals are	identified under this section,	, this product is Not	Applicable under this re	egulatic
Chemical Name		CAS-No.	Weight percent	
ZINC COMPOUNDS		68187-51-9	1.00 - 5.00	
CHROMIUM III COMPO COMPOUNDSANTIMON		68186-90-3	10.00 - 30.00	
COMPOUNDSCHROMIL				
Canadian Regulations:				
-				
National Pollutant Rel	ease Inventory (NPRI)			

P<u>olyOne</u>

# MATERIAL SAFETY DATA SHEET 114194 BNA LLDPE MASTERBATCH

Version Number 1.0 Revision Date 04/01/2014

### Page 8 of 8 Print Date 4/9/2014

Chemical Name		CAS-No.	Weight	NPRI ID#
Zinc ferrite brown spinel (C 119)	.I. Pigment Yellow	68187-51-9	percent 1.00 - 5.00	
Rutile, antimony chromium buff		68186-90-3	10.00 - 30.00	
WHMIS Classification WHMIS Ingredient Dis CAS-No. 1333-86-4 1309-37-1 68186-90-3 7631-86-9 DSL Jational Inventories:	closure List	ts of this product a t (DSL) or are exer	re on the Canadian mpt.	n Domestic
Australia AICS	: Listed			
Australia AICS				
China IECS	: Listed			
	: Listed : Listed			
China IECS		1		
China IECS Europe EINECS	: Listed	1		
China IECS Europe EINECS Japan ENCS	: Listed : Not determined	I		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.