PolvOne.

## MATERIAL SAFETY DATA SHEET **BLACK**

Version Number 1.3 Revision Date 03/13/2014

Page 1 of 7 Print Date 3/20/2014

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	BLACK
Product code	:	CC10127874
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Miscellaneous Irritant	0-32-8	1 - 5
Carbon black	1333-86-4	1 - 5
Titanium dioxide	13463-67-7	1 - 5

### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

# MATERIAL SAFETY DATA SHEET **BLACK**

Version Number 1.3 Revision Date 03/13/2014 Page 2 of 7 Print Date 3/20/2014

Medical Conditions Aggravated by Exposure:	: None known.
Aggravateu by Exposure.	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits	
Upper explosion limit	: not applicable
Lower explosion limit	: not applicable
Auto-ignition temperature	: not applicable
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	<ul> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE



# MATERIAL SAFETY DATA SHEET **BLACK**

/ersion Number 1.3 Revision Date 03/13/2014		Page 3 of 7 Print Date 3/20/2014
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

<u>PolyOne</u>

## MATERIAL SAFETY DATA SHEET **BLACK**

Version Number 1.3

Page 4 of 7 Print Date 3/20/2014

Revision Date 03/13/2014

Components	Value	Exposure	e time	Exposure type	e List:
Carbon black	3.5 mg/m3	/m3 Recommended exposure limit (REL):			NIOSH
	0.1 mg/m3	Recommende limit (R			NIOSH
	3.5 mg/m3	PEL	.:		OSHA Z1
	3.5 mg/m3	Time Weighte (TWA			OSHA Z1A
	3.5 mg/m3	Time Weighte (TWA	0		MX OEL
	7 mg/m3	Short Term Exp (STE)	posure Limit		MX OEL
	3 mg/m3	Time Weighte (TWA		Inhalable fraction	on. ACGIH
Titanium dioxide	10 mg/m3	Time Weighte (TWA	-		ACGIH
	15 mg/m3	PEL	.:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighte (TWA	-	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighte (TWA	0	as Ti	MX OEL
	20 mg/m3	Short Term Exp (STE)		as Ti	MX OEL
	9. PHYSIC	CAL AND CHE	MICAL PRO	PERTIES	
Form	: solid			aration rate :	Not applicable
Appearance	: pelle			c Gravity :	Not determined
Colour	: BLA		Bulk de		Not established
Odour	: very			r pressure :	not applicable
Melting point/range		letermined	-	r density :	not applicable
Boiling Point:		pplicable	pH	:	not applicable
Water solubility	: insol	uble			

**10. STABILITY AND REACTIVITY** 

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
 Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

## MATERIAL SAFETY DATA SHEET **BLACK**

Version Number 1.3 Revision Date 03/13/2014

Page 5 of 7 Print Date 3/20/2014

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
0-32-8	Miscellaneous Irritant	sensitizer	Skin.
		Irritant	Eyes, Skin.
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

## 12. ECOLOGICAL INFORMATION



# MATERIAL SAFETY DATA SHEET **BLACK**

readily biodegradable. emicals are not readily available as they are bound within the ymer matrix. emicals are not readily available as they are bound within the ymer matrix. data available <b>SPOSAL CONSIDERATIONS</b> e most thermoplastic plastics the product can be recycled. Where sible recycling is preferred to disposal or incineration. The erator of waste material has the responsibility for proper waste sification, transportation and disposal in accordance with licable federal, state/provincial and local regulations. expeling is preferred when possible. The generator of waste erial has the responsibility for proper waste erial has the responsibility for proper waste erial has the responsibility for proper waste classification, has the responsibility
emicals are not readily available as they are bound within the ymer matrix. emicals are not readily available as they are bound within the ymer matrix. data available <b>SPOSAL CONSIDERATIONS</b> e most thermoplastic plastics the product can be recycled. Where sible recycling is preferred to disposal or incineration. The erator of waste material has the responsibility for proper waste sification, transportation and disposal in accordance with licable federal, state/provincial and local regulations. eycling is preferred when possible. The generator of waste erate and disposal in accordance with applicable federal, state/accordance with applicable federal, st
ymer matrix. emicals are not readily available as they are bound within the ymer matrix. data available <b>SPOSAL CONSIDERATIONS</b> e most thermoplastic plastics the product can be recycled. Where sible recycling is preferred to disposal or incineration. The erator of waste material has the responsibility for proper waste ssification, transportation and disposal in accordance with licable federal, state/provincial and local regulations. eycling is preferred when possible. The generator of waste erial has the responsibility for proper waste classification, asportation and disposal in accordance with applicable federal,
ymer matrix. data available SPOSAL CONSIDERATIONS e most thermoplastic plastics the product can be recycled. Where sible recycling is preferred to disposal or incineration. The erator of waste material has the responsibility for proper waste ssification, transportation and disposal in accordance with licable federal, state/provincial and local regulations. cycling is preferred when possible. The generator of waste erial has the responsibility for proper waste classification, isportation and disposal in accordance with applicable federal,
<b>SPOSAL CONSIDERATIONS</b> e most thermoplastic plastics the product can be recycled. Where sible recycling is preferred to disposal or incineration. The erator of waste material has the responsibility for proper waste ssification, transportation and disposal in accordance with licable federal, state/provincial and local regulations. cycling is preferred when possible. The generator of waste erial has the responsibility for proper waste classification, asportation and disposal in accordance with applicable federal,
e most thermoplastic plastics the product can be recycled. Where sible recycling is preferred to disposal or incineration. The erator of waste material has the responsibility for proper waste ssification, transportation and disposal in accordance with licable federal, state/provincial and local regulations. cycling is preferred when possible. The generator of waste erial has the responsibility for proper waste classification, asportation and disposal in accordance with applicable federal,
sible recycling is preferred to disposal or incineration. The erator of waste material has the responsibility for proper waste sification, transportation and disposal in accordance with licable federal, state/provincial and local regulations. cycling is preferred when possible. The generator of waste erail has the responsibility for proper waste classification, asportation and disposal in accordance with applicable federal,
serial has the responsibility for proper waste classification, asportation and disposal in accordance with applicable federal,
RANSPORT INFORMATION
regulated for transportation.
er to specific regulation.
er to specific regulation.
GULATORY INFORMATION
ssified as hazardous based on components.
components of this product are listed on or exempt from the CA Inventory.
es (40 CFR 302)

POLYONE CORPORATION

PolyOne.

## MATERIAL SAFETY DATA SHEET **BLACK**

Version Number 1.3	
Revision Date 03/13/2014	

Page 7 of 7 Print Date 3/20/2014

SARA Title III Section 302 Extremely Hazardous Substance	
Unless specific chemicals are ic	lentified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 To:	xic Chemicals:
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation	
Canadian Regulations:	
National Pollutant Release Inventory (NPRI)	
not applicable	
WHMIS Classification	: D2A
WHMIS Ingredient Disclosure List	
CAS-No. 1333-86-4	
DSL	: DSL status has not been determined. Quantity use in Canada may be restricted by regulations.
National Inventories:	
Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.