MATERIAL SAFETY DATA SHEET **PROFESSIONAL DARK GREEN**

Version Number 1.1 Revision Date 03/13/2014 Page 1 of 6 Print Date 3/20/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PROFESSIONAL DARK GREEN
Product code	:	CC10129077
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Chromium (III) oxide	1308-38-9	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne

MATERIAL SAFETY DATA SHEET PROFESSIONAL DARK GREEN

Version Number 1.1 Revision Date 03/13/2014 Page 2 of 6 Print Date 3/20/2014

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

PolyOne.

MATERIAL SAFETY DATA SHEET PROFESSIONAL DARK GREEN

Version Number 1.1 Revision Date 03/13/2014 Page 3 of 6 Print Date 3/20/2014

Storage		eep containers dry and tightl nd contamination. Keep in a		e absorption
8.1	EXPOSURE	CONTROLS/PERSONAL	PROTECTION	
Respiratory protection	: N	o personal respiratory protec	tive equipment normally	required.
Eye/Face Protection : Safety glasses with side-shields				
Hand protection	: P:	rotective gloves		
Skin and body protection	: L	ong sleeved clothing		
Additional Protective Measures	: S	afety shoes		
General Hygiene Considerations		andle in accordance with goo ractice. Wash hands before b		
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)				
Components	Value			
Componento	varue	Exposure time	Exposure type	List:
Chromium (III) oxide	0.5 mg/m3	Exposure time Recommended exposure limit (REL):	Exposure type as Cr	List: NIOSH
*		Recommended exposure		
*	0.5 mg/m3 0.5 mg/m3	Recommended exposure limit (REL):	as Cr as Cr	NIOSH
Chromium (III) oxide	0.5 mg/m3 0.5 mg/m3 9. PHYSIC	Recommended exposure limit (REL): PEL: CAL AND CHEMICAL PR	as Cr as Cr OPERTIES	NIOSH OSHA Z1
*	0.5 mg/m3 0.5 mg/m3	Recommended exposure limit (REL): PEL: CAL AND CHEMICAL PR Evap	as Cr as Cr OPERTIES ouration rate : Not	NIOSH
Chromium (III) oxide	0.5 mg/m3 0.5 mg/m3 9. PHYSIC : solid : pelle : GRE	Recommended exposure limit (REL): PEL: CAL AND CHEMICAL PR Evap ts Spect EN Bulk	as Cr as Cr OPERTIES ouration rate : Not fic Gravity : Not density : Not	NIOSH OSHA Z1 applicable determined established
Chromium (III) oxide Form Appearance Colour Odour	0.5 mg/m3 0.5 mg/m3 9. PHYSIC : solid : pelle : GRE : very	Recommended exposure limit (REL): PEL: CAL AND CHEMICAL PR Evap ts Spec EN Bulk faint Vapo	as Cr as Cr OPERTIES ouration rate : Not fic Gravity : Not density : Not ur pressure : not	applicable established applicable
Chromium (III) oxide Form Appearance Colour Odour Melting point/range	0.5 mg/m3 0.5 mg/m3 9. PHYSIC : solid : pelle : GRE : very : Not c	Recommended exposure limit (REL): PEL: CAL AND CHEMICAL PR Evap ts Spec EN Bulk faint Vapo letermined Vapo	as Cr as Cr OPERTIES ouration rate : Not fic Gravity : Not density : Not ur pressure : not ur density : not	applicable established applicable applicable applicable
Chromium (III) oxide Chromium (III) oxide Form Appearance Colour Odour Melting point/range Boiling Point:	0.5 mg/m3 0.5 mg/m3 9. PHYSIC : solid : pelle : GRE : very : Not c : not a	Recommended exposure limit (REL): PEL: CAL AND CHEMICAL PR Evap ts Spec EN Bulk faint Vapo letermined Vapo pplicable pH	as Cr as Cr OPERTIES ouration rate : Not fic Gravity : Not density : Not ur pressure : not ur density : not	applicable established applicable
Chromium (III) oxide Form Appearance Colour Odour Melting point/range	0.5 mg/m3 0.5 mg/m3 9. PHYSIC : solid : pelle : GRE : very : Not c	Recommended exposure limit (REL): PEL: CAL AND CHEMICAL PR Evap ts Spec EN Bulk faint Vapo letermined Vapo pplicable pH	as Cr as Cr OPERTIES ouration rate : Not fic Gravity : Not density : Not ur pressure : not ur density : not	applicable established applicable applicable applicable
Chromium (III) oxide Chromium (III) oxide Form Appearance Colour Odour Melting point/range Boiling Point:	0.5 mg/m3 0.5 mg/m3 9. PHYSIC : solid : pelle : GRE : very : Not c : not a : insol	Recommended exposure limit (REL): PEL: CAL AND CHEMICAL PR Evap ts Spec EN Bulk faint Vapo letermined Vapo pplicable pH	as Cr as Cr OPERTIES ouration rate : Not fic Gravity : Not density : Not ur pressure : not ur density : not : not	applicable established applicable applicable applicable
Chromium (III) oxide Chromium (III) oxide Form Appearance Colour Odour Melting point/range Boiling Point:	0.5 mg/m3 0.5 mg/m3 9. PHYSIC : solid : pelle : GRE : very : Not c : not a : insol 10. S	Recommended exposure limit (REL): PEL: CAL AND CHEMICAL PR Evap ts Spec: EN Bulk faint Vapo pplicable pH uble Description	as Cr as Cr OPERTIES ouration rate : Not fic Gravity : Not density : Not ur pressure : not ur density : not : not	NIOSH OSHA Z1 applicable determined established applicable applicable applicable
Chromium (III) oxide Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility	0.5 mg/m3 0.5 mg/m3 9. PHYSIC : solid : pelle : GRE : very : Not c : not a : insol 10. S : T	Recommended exposure limit (REL): PEL: CAL AND CHEMICAL PR Evap ts Spec EN Bulk faint Vapo determined Vapo pplicable pH uble STABILITY AND REACTI	as Cr as Cr OPERTIES ouration rate : Not fic Gravity : Not density : Not ur pressure : not ur density : not : not	NIOSH OSHA Z1 applicable determined established applicable applicable applicable
Chromium (III) oxide Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility Stability	0.5 mg/m3 0.5 mg/m3 9. PHYSIC : solid : pelle : GRE : very : Not c : not a : insol 10. S : T n : W : K	Recommended exposure limit (REL): PEL: CAL AND CHEMICAL PR Evap ts Spec EN Bulk faint Vapo letermined pH uble TABILITY AND REACTI he product is stable if stored	as Cr as Cr OPERTIES ouration rate : Not fic Gravity : Not density : Not ur pressure : not ur density : not VITY and handled as prescribed ents and open flame. To a	NIOSH OSHA Z1 applicable established applicable applicable applicable

MATERIAL SAFETY DATA SHEET **PROFESSIONAL DARK GREEN**

Version Number 1.1 Revision Date 03/13/2014 Page 4 of 6 Print Date 3/20/2014

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1308-38-9	Chromium (III) oxide	Irritant	Eyes, Skin.
		sensitizer	Skin.

Additional Health Hazard Information:

Chromium (III) oxide 1308-38-9 The bi- and trivalent forms of chrome have a low order of acute toxicity, but may cause skin sensitization and irritation to the eyes. No effects have been reported for chromium (III) oxide. Chromium (III) compounds are not considered carcinogenic in animals or humans.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.

PolyOne.

MATERIAL SAFETY DATA SHEET **PROFESSIONAL DARK GREEN**

Version Number 1.1 Revision Date 03/13/2014

Page 5 of 6 Print Date 3/20/2014

ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component	RQ for
			Mixture/Product
Chromium (III)	1308-38-9	010 lbs	45 LB
oxide			

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent
CHROMIUM III COMPOUNDSCHROMIUM	1308-38-9	10.00 - 30.00
COMPOUNDS		

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Chromium (III) oxide	1308-38-9	10.00 - 30.00	
Phthalocyanine green	1328-53-6	1.00 - 5.00	

PolyOne

MATERIAL SAFETY DATA SHEET **PROFESSIONAL DARK GREEN**

Version Number 1.1 Revision Date 03/13/2014 Page 6 of 6 Print Date 3/20/2014

WHMIS Classification	: D2B
WHMIS Ingredient Dis	closure List
CAS-No. 1308-38-9 1328-53-6	
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS	: Listed
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Listed
Philippines PICCS	: Listed
	16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.