## MATERIAL SAFETY DATA SHEET **FRPS 132447**

Version Number 1.2 Revision Date 03/20/2014

CAS-No.

Product Use

Page 1 of 7 Print Date 3/23/2014

#### **1. PRODUCT AND COMPANY IDENTIFICATION** POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012 1 (440) 930-1000 or 1 (866) POLYONE Telephone : **Emergency telephone** : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure number or accident). Product name : FRPS 132447 CC10132447 Product code : Chemical Name Mixture :

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

: Industrial Applications

:

Components	CAS-No.	Weight percent
1,1'-(Ethane-1,2-	84852-53-9	30 - 60
diyl)bis[pentabromobenzene]		
Antimony trioxide	1309-64-4	10 - 30

#### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

### MATERIAL SAFETY DATA SHEET FRPS 132447

Version Number 1.2 Revision Date 03/20/2014 Page 2 of 7 Print Date 3/23/2014

Medical Conditions		None known.			
Aggravated by Exposure:					
		4. FIRST AID MEASURES			
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.			
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.			
		5. FIREFIGHTING MEASURES			
Flash point	:	not applicable			
Flammable Limits					
Upper explosion limit	:	not applicable			
Lower explosion limit	:	not applicable			
Auto-ignition temperature	:	not applicable			
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.			
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.			
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.			
	6. AC	CCIDENTAL RELEASE MEASURES			
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.			
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.			
		7. HANDLING AND STORAGE			
Handling		Take measures to prevent the build up of electrostatic charge. Heat			



# MATERIAL SAFETY DATA SHEET **FRPS 132447**

			Phh	t Date 3/23/2	
	or	ly in areas with appropriate	exhaust ventilation.		
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.				
8.	EXPOSURE	CONTROLS/PERSONAI	PROTECTION		
Respiratory protection	: N	o personal respiratory protec	ctive equipment normally	required.	
Eye/Face Protection	: Sa	fety glasses with side-shield	ls		
Hand protection	: P1	otective gloves			
Skin and body protection	: Lo	ong sleeved clothing			
Additional Protective Measures	: Sa	afety shoes			
General Hygiene Considerations		andle in accordance with go actice. Wash hands before			
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Exposure limit(s) Components	Value	Exposure time	Exposure type	List:	
	0.5 mg/m3	Time Weighted Average (TWA):	Exposure type as Sb	MX OEL	
Components		Time Weighted Average			
Components	0.5 mg/m3	Time Weighted Average (TWA): Time Weighted Average	as Sb	MX OEL	
Components	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA): Recommended exposure limit (REL): PEL:	as Sb as Sb as Sb as Sb	MX OEL ACGIH NIOSH OSHA ZI	
Components	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA): Recommended exposure limit (REL):	as Sb as Sb as Sb	MX OEL ACGIH	
Components	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA): Recommended exposure limit (REL): PEL: Time Weighted Average	as Sb as Sb as Sb as Sb as Sb as Sb	MX OEL ACGIH NIOSH OSHA ZI	
Components Antimony trioxide	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 9. PHYSIC	Time Weighted Average (TWA): Time Weighted Average (TWA): Recommended exposure limit (REL): PEL: Time Weighted Average (TWA):	as Sb as Sb as Sb as Sb as Sb as Sb as Sb	MX OEL ACGIH NIOSH OSHA Z1 OSHA Z1	
Components Antimony trioxide	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 9. PHYSIC : solid	Time Weighted Average (TWA): Time Weighted Average (TWA): Recommended exposure limit (REL): PEL: Time Weighted Average (TWA): EAL AND CHEMICAL PR	as Sb as Sb as Sb as Sb as Sb as Sb as Sb as Sb coveration rate : No	MX OEL ACGIH NIOSH OSHA Z1 OSHA Z1	
Components Antimony trioxide	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 9. PHYSIC : solid : pellet	Time Weighted Average (TWA): Time Weighted Average (TWA): Recommended exposure limit (REL): PEL: Time Weighted Average (TWA): EAL AND CHEMICAL PR Evap s Spec	as Sb as Sb as Sb as Sb as Sb as Sb as Sb as Sb couration rate : No ific Gravity : No	MX OEL ACGIH NIOSH OSHA ZI OSHA ZI	
Components Antimony trioxide	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 9. PHYSIC : solid : pellet : NO F	Time Weighted Average (TWA): Time Weighted Average (TWA): Recommended exposure limit (REL): PEL: Time Weighted Average (TWA): CAL AND CHEMICAL PR Evap s Spec IGMENT Bulk	as Sb as Sb as Sb as Sb as Sb as Sb as Sb couration rate : No ific Gravity : No density : No	MX OEL ACGIH NIOSH OSHA ZI OSHA ZI	
Components Antimony trioxide	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 9. PHYSIC : solid : pellet : NO P : very :	Time Weighted Average (TWA): Time Weighted Average (TWA): Recommended exposure limit (REL): PEL: Time Weighted Average (TWA): EAL AND CHEMICAL PR S Spec IGMENT Bulk faint Vapo	as Sb as Sb as Sb as Sb as Sb as Sb <b>ROPERTIES</b>	MX OEL ACGIH NIOSH OSHA ZI OSHA ZI	
Components Antimony trioxide	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 9. PHYSIC : solid : pellet : NO P : very : : Not d	Time Weighted Average (TWA):         Time Weighted Average (TWA):         Recommended exposure limit (REL):         PEL:         Time Weighted Average (TWA):         Evap         Second Average         Below         Evap         Second Average         IGMENT         Bulk         faint       Vapo         etermined       Vapo	as Sb         couration rate         ific Gravity         ific Gravity         if consity         as Sb         as Sb         as Sb         as Sb         as Sb         convertion rate         as Sb         as Sb </td <td>MX OEL ACGIH NIOSH OSHA ZI OSHA ZI OSHA ZI</td>	MX OEL ACGIH NIOSH OSHA ZI OSHA ZI OSHA ZI	
Components Antimony trioxide	0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3 9. PHYSIC : solid : pellet : NO P : very : : Not d	Time Weighted Average (TWA):         Time Weighted Average (TWA):         Recommended exposure limit (REL):         PEL:         Time Weighted Average (TWA):         Event         Second Average (TWA):         Event         Event         Time Weighted Average (TWA):         Event         Event         Second Average         IGMENT         Bulk         faint       Vapor         pelicable       pH	as Sb         couration rate         ific Gravity         ific Gravity         if consity         as Sb         as Sb         as Sb         as Sb         as Sb         convertion rate         as Sb         as Sb </td <td>MX OEL ACGIH NIOSH OSHA ZI OSHA ZI</td>	MX OEL ACGIH NIOSH OSHA ZI OSHA ZI	



## MATERIAL SAFETY DATA SHEET FRPS 132447

Version Number 1.2 Revision Date 03/20/2014

Page 4 of 7 Print Date 3/23/2014

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
84852-53-9	1,1'-(Ethane-1,2- diyl)bis[pentabromobenze ne]	Chronic effects	Skin, Respiratory system.
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
84852-53-9	1,1'-(Ethane-1,2-	Oral LD 50	> 5,000 mg/kg	Rat
	diyl)bis[pentabromobenze	Dermal LD 50	> 2,000 mg/kg	rabbit
	ne]			
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1309-64-4	Antimony trioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

PolyOne

### **MATERIAL SAFETY DATA SHEET** FRPS 132447

Version Number 1.2 Revision Date 03/20/2014 Page 5 of 7 Print Date 3/23/2014

2 - The component is reasonably anticipated to be a human carcinogen.

### Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
	5/7

Polv<u>One</u>

### MATERIAL SAFETY DATA SHEET FRPS 132447

Version Number 1.2 Revision Date 03/20/2014 Page 6 of 7 Print Date 3/23/2014

not applicable

California Proposition : WARNING! This product contains a chemical known to the State of California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name CAS	-No. Weight percent
ANTIMONY COMPOUNDS 1309-	64-4 10.00 - 30.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Antimony trioxide	1309-64-4	10.00 - 30.00	

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
1309-64-4	

DSL

DSL status has not been determined. Quantity use in Canada may be restricted by regulations.

National Inventories:

Australia AICS	:	Not determined
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined

:



## MATERIAL SAFETY DATA SHEET FRPS 132447

Version Number 1.2 Revision Date 03/20/2014

Page 7 of 7 Print Date 3/23/2014

Korea KECI : Listed

Philippines PICCS : Listed

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.