PolyOne

MATERIAL SAFETY DATA SHEET LT. BEIGE ABS

Version Number 1.1 Revision Date 03/23/2014 Page 1 of 7 Print Date 3/29/2014

| 1. PRODUCT AND COMPANY IDENTIFICATION POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012 Telephone : 1 (440) 930-1000 or 1 (866) POLYONE Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). | | | | |
|---|---|-------------------------|--|--|
| | | | | |
| Product code | : | CC10139275 | | |
| Chemical Name | : | Mixture | | |
| CAS-No. | : | Mixture | | |
| Product Use | | Industrial Applications | | |

2. COMPOSITION/INFORMATION ON INGREDIENTS

| Components | CAS-No. | Weight percent |
|--------------------------------|------------|----------------|
| Rutile, antimony chromium buff | 68186-90-3 | 1 - 5 |
| Titanium dioxide | 13463-67-7 | 30 - 60 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Ingestion, Skin contact |
|----------------------------|---|
| Acute exposure | |
| Inhalation | : Resin particles, like other inert materials, can be mechanically irritating. |
| Ingestion | : May be harmful if swallowed. |
| Eyes | : Resin particles, like other inert materials, are mechanically irritating to eyes. |
| Skin | : Experience shows no unusual dermatitis hazard from routine handling. |
| Chronic exposure | : Refer to Section 11 for Toxicological Information. |

PolyOne.

MATERIAL SAFETY DATA SHEET LT. BEIGE ABS

Version Number 1.1 Revision Date 03/23/2014 Page 2 of 7 Print Date 3/29/2014

| Medical Conditions Aggravated by Exposure: | : None known. |
|--|--|
| | 4. FIRST AID MEASURES |
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice. |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. |
| Eyes | : Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention. |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists seek medical attention. |
| | 5. FIREFIGHTING MEASURES |
| Flash point | : not applicable |
| Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures | not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne |
| Unusual Fire/Explosion Hazards | contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. |
| | 6. ACCIDENTAL RELEASE MEASURES |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. |
| Environmental precautions | : Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil. |
| Methods for cleaning up | : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. |
| | 7. HANDLING AND STORAGE |
| Handling | : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. |



MATERIAL SAFETY DATA SHEET LT. BEIGE ABS

Version Number 1.1 Revision Date 03/23/2014 Page 3 of 7 Print Date 3/29/2014

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

| Respiratory protection | : | No personal respiratory protective equipment normally required. |
|-----------------------------------|---|--|
| Eye/Face Protection | : | Safety glasses with side-shields |
| Hand protection | : | Protective gloves |
| Skin and body protection | : | Long sleeved clothing |
| Additional Protective Measures | : | Safety shoes |
| General Hygiene Considerations | | Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. |
| Engineering measures | : | Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. |
| Exposure limit(s) | | |

PolyOne

MATERIAL SAFETY DATA SHEET *LT. BEIGE ABS*

Version Number 1.1 Revision Date 03/23/2014 Page 4 of 7 Print Date 3/29/2014

: Not applicable

: Not determined

: Not established

: not applicable

: not applicable

:

not applicable

| Components | Value | Exposure time | Exposure type | List: |
|--------------------------------|-----------|--------------------------------------|---------------|----------|
| Rutile, antimony chromium buff | 0.5 mg/m3 | Recommended exposure limit (REL): | as Cr | NIOSH |
| | 0.5 mg/m3 | PEL: | as Cr | OSHA Z1 |
| | 0.5 mg/m3 | Time Weighted Average (TWA): | as Sb | ACGIH |
| | 0.5 mg/m3 | Recommended exposure limit (REL): | as Sb | NIOSH |
| | 0.5 mg/m3 | PEL: | as Sb | OSHA Z1 |
| | 0.5 mg/m3 | Time Weighted Average (TWA): | as Sb | OSHA Z1A |
| | 0.5 mg/m3 | Time Weighted Average (TWA): | as Sb | MX OEL |
| Titanium dioxide | 10 mg/m3 | Time Weighted Average (TWA): | | ACGIH |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| | 10 mg/m3 | Time Weighted Average (TWA): | Total dust. | OSHA Z1A |
| | 10 mg/m3 | Time Weighted Average (TWA): | as Ti | MX OEL |
| | 20 mg/m3 | Short Term Exposure Limit (STEL): | as Ti | MX OEL |

9. PHYSICAL AND CHEMICAL PROPERTIES

Evapouration rate

Specific Gravity

Vapour pressure

Vapour density

Bulk density

pН

: solid

: pellets

: very faint

: Not determined

: not applicable

: TAN

| Form |
|---------------------|
| Appearance |
| Colour |
| Odour |
| Melting point/range |
| Boiling Point: |
| Water solubility |

: insoluble 10. STABILITY AND REACTIVITY

| Stability | : The | e product is stable if stored and handled as prescribed. |
|----------------------------------|-------|---|
| Hazardous Polymerization | : Wi | ll not occur. |
| Conditions to avoid | | ep away from oxidizing agents and open flame. To avoid thermal omposition, do not overheat. |
| Incompatible Materials | : Inc | ompatible with strong acids and oxidizing agents. |
| Hazardous decomposition products | | bon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen Dx), other hazardous materials, and smoke are all possible. |

11. TOXICOLOGICAL INFORMATION

MATERIAL SAFETY DATA SHEET LT. BEIGE ABS

Version Number 1.1 Revision Date 03/23/2014 Page 5 of 7 Print Date 3/29/2014

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|------------|------------------|------------------|-------------------------|
| 68186-90-3 | Rutile, antimony | Irritant | Eyes, Skin, Respiratory |
| | chromium buff | | system. |
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. |

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|------------|------------------|------|------|-----|
| 13463-67-7 | Titanium dioxide | no | 2B | no |

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

| : Not readily biodegradable. |
|---|
| : Chemicals are not readily available as they are bound within the polymer matrix. |
| : Chemicals are not readily available as they are bound within the polymer matrix. |
| : no data available |
| 13. DISPOSAL CONSIDERATIONS |
| : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, |
| |

POLYONE CORPORATION

Page 6 of 7

MATERIAL SAFETY DATA SHEET *LT. BEIGE ABS*

Version Number 1.1

Aluminum oxide

Print Date 3/29/2014 Revision Date 03/23/2014 state/provincial and local regulations. **14. TRANSPORT INFORMATION** U.S. DOT Classification : Not regulated for transportation. ICAO/IATA Refer to specific regulation. : IMO/IMDG (maritime) Refer to specific regulation. : **15. REGULATORY INFORMATION US Regulations: OSHA Status** : Classified as hazardous based on components. **TSCA Status** All components of this product are listed on or exempt from the : TSCA Inventory. US. EPA CERCLA Hazardous Substances (40 CFR 302) not applicable California Proposition : Not applicable 65 SARA Title III Section 302 Extremely Hazardous Substance Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation SARA Title III Section 313 Toxic Chemicals: Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation Weight percent Chemical Name CAS-No. CHROMIUM III COMPOUNDSCHROMIUM III 68186-90-3 1.00 - 5.00 COMPOUNDSANTIMONY COMPOUNDSCHROMIUM COMPOUNDS Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name CAS-No. NPRI ID# Weight percent

1344-28-1

0.10 - 1.00

P<u>olyOne</u>

MATERIAL SAFETY DATA SHEET *LT. BEIGE ABS*

Version Number 1.1 Revision Date 03/23/2014 Page 7 of 7 Print Date 3/29/2014

| Rutile, antimony chromium b | uff | | 68186-90-3 | 1.00 - 5.00 | |
|-----------------------------|-----|-------------------|-------------------|--------------------|----------|
| · · · | | | • | | • |
| | | | | | |
| WHMIS Classification | : | D2A | | | |
| WHMIS Ingredient Discl | osı | ire List | | | |
| CAS-No. | | | | | |
| 68186-90-3 | | | | | |
| DSL | : | | | re on the Canadian | Domestic |
| | | Substances List | (DSL) or are exer | npt. | |
| National Inventories: | | | | | |
| Australia AICS | : | Listed | | | |
| China IECS | : | Listed | | | |
| Europe EINECS | : | Listed | | | |
| Japan ENCS | : | Not determined | | | |
| Korea KECI | : | Listed | | | |
| Philippines PICCS | : | Listed | | | |
| | | 16 ОТЦЕР И | NFORMATION | | |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.