

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****DK. GRAY 1**Version Number 1.1
Revision Date 03/23/2014Page 1 of 8
Print Date 3/31/2014**1. PRODUCT AND COMPANY IDENTIFICATION****POLYONE CORPORATION**
33587 Walker Road, Avon Lake, OH 44012Telephone : 1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure number or accident).**Product name : DK. GRAY 1
Product code : CC10142081
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications**2. COMPOSITION/INFORMATION ON INGREDIENTS**

| Components | CAS-No. | Weight percent |
|--|-------------|----------------|
| 1,3,5-Triazine-2,4,6-triamine,N,N"-1,2-ethanediybis[N-[3-[[4,6-bis[butyl(1,2,2,6,6-pentamethyl-4-piperidiny)amino]-1,3,5-triazin | 106990-43-6 | 1 - 5 |
| Phenol, 2-(2H-benzotriazol-2-yl)-4,6-bis(1,1-dimethylpropyl)- | 25973-55-1 | 5 - 10 |
| Silica, amorphous | 7631-86-9 | 1 - 5 |
| Xylenes (o-, m-, p- isomers) | 1330-20-7 | 1 - 5 |
| Titanium dioxide | 13463-67-7 | 10 - 30 |
| Iron chromite brown spinel | 12737-27-8 | 10 - 30 |

3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS**Routes of Exposure:** : Inhalation, Ingestion, Skin contact**Acute exposure**

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

DK. GRAY 1

Version Number 1.1
Revision Date 03/23/2014

Page 2 of 8
Print Date 3/31/2014

- Inhalation : Resin particles, like other inert materials, can be mechanically irritating.
- Ingestion : May be harmful if swallowed.
- Eyes : Resin particles, like other inert materials, are mechanically irritating to eyes.
- Skin : Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure : Refer to Section 11 for Toxicological Information.

Medical Conditions Aggravated by Exposure: : None known.

4. FIRST AID MEASURES

- Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
- Ingestion : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
- Eyes : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
- Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIREFIGHTING MEASURES

- Flash point : not applicable
- Flammable Limits
 - Upper explosion limit : not applicable
 - Lower explosion limit : not applicable
- Auto-ignition temperature : not applicable
- Suitable extinguishing media : Carbon dioxide blanket, Water spray, Dry powder, Foam.
- Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
- Unusual Fire/Explosion Hazards : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
- Environmental precautions : Should not be released into the environment. The product should not

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

DK. GRAY 1

Version Number 1.1
Revision Date 03/23/2014

Page 3 of 8
Print Date 3/31/2014

be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.

7. HANDLING AND STORAGE

Handling : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection : No personal respiratory protective equipment normally required.

Eye/Face Protection : Safety glasses with side-shields

Hand protection : Protective gloves

Skin and body protection : Long sleeved clothing

Additional Protective Measures : Safety shoes

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

DK. GRAY 1

Version Number 1.1
Revision Date 03/23/2014

Page 4 of 8
Print Date 3/31/2014

| Components | Value | Exposure time | Exposure type | List: |
|----------------------------|-----------------------------|-----------------------------------|------------------------------|----------|
| Silica, amorphous | 6 mg/m3 | Recommended exposure limit (REL): | | NIOSH |
| | 0.8 mg/m3 | Time Weighted Average (TWA): | | Z3 |
| | 10 mg/m3 | Time Weighted Average (TWA): | Inhalable particulate. | MX OEL |
| | 3 mg/m3 | Time Weighted Average (TWA): | Respirable dust. | MX OEL |
| Titanium dioxide | 10 mg/m3 | Time Weighted Average (TWA): | | ACGIH |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| | 10 mg/m3 | Time Weighted Average (TWA): | Total dust. | OSHA Z1A |
| | 10 mg/m3 | Time Weighted Average (TWA): | as Ti | MX OEL |
| | 20 mg/m3 | Short Term Exposure Limit (STEL): | as Ti | MX OEL |
| | Xylenes (o-, m-, p-isomers) | 100 ppm | Time Weighted Average (TWA): | |
| 150 ppm | | Short Term Exposure Limit (STEL): | | ACGIH |
| 100 ppm | | PEL: | | OSHA Z1 |
| 435 mg/m3 | | | | |
| 100 ppm | | Time Weighted Average (TWA): | | OSHA Z1A |
| 435 mg/m3 | | | | |
| 150 ppm | | Short Term Exposure Limit (STEL): | | OSHA Z1A |
| 655 mg/m3 | | | | |
| Iron chromite brown spinel | 100 ppm | Time Weighted Average (TWA): | | MX OEL |
| | 435 mg/m3 | | | |
| | 150 ppm | Short Term Exposure Limit (STEL): | | MX OEL |
| | 655 mg/m3 | | | |
| Iron chromite brown spinel | 0.5 mg/m3 | Recommended exposure limit (REL): | as Cr | NIOSH |
| | 0.5 mg/m3 | PEL: | as Cr | OSHA Z1 |

9. PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|---------------------|------------------|------------------|-------------------|
| Form | : solid | Evaporation rate | : Not applicable |
| Appearance | : pellets | Specific Gravity | : Not determined |
| Colour | : GREY | Bulk density | : Not established |
| Odour | : very faint | Vapour pressure | : not applicable |
| Melting point/range | : Not determined | Vapour density | : not applicable |
| Boiling Point: | : not applicable | pH | : not applicable |
| Water solubility | : insoluble | | |

10. STABILITY AND REACTIVITY

Stability : The product is stable if stored and handled as prescribed.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

DK. GRAY 1

Version Number 1.1
Revision Date 03/23/2014

Page 5 of 8
Print Date 3/31/2014

- Hazardous Polymerization : Will not occur.
- Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
- Incompatible Materials : Incompatible with strong acids and oxidizing agents.
- Hazardous decomposition products : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|------------|---|------------------|--|
| 25973-55-1 | Phenol, 2-(2H-benzotriazol-2-yl)-4,6-bis(1,1-dimethylpropyl)- | Systemic effects | Kidney, Liver, reproductive system. |
| 7631-86-9 | Silica, amorphous | Irritant | Eyes, Respiratory system. |
| 1330-20-7 | Xylenes (o-, m-, p-isomers) | Irritant | Eyes, Respiratory system. |
| | | Systemic effects | Eyes, Skin, Respiratory system, blood and blood forming system, Liver, Kidney, central nervous system (CNS), digestive system. |
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. |
| 12737-27-8 | Iron chromite brown spinel | Irritant | Eyes, Skin, Respiratory system. |

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No. | Chemical Name | Route | Value | Species |
|-----------|-----------------------------|-------------|---------------|---------|
| 1330-20-7 | Xylenes (o-, m-, p-isomers) | LC50 | 5000 ppm/4H | rat |
| | | LC50 | | rat |
| | | Oral | 4,300 | rat |
| | | LD50Oral | mg/kg4,300 | rabbit |
| | | LD50 | mg/kg | rabbit |
| | | Dermal LD50 | > 1,700 mg/kg | |
| | | Dermal LD50 | 43 g/kg | |

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

DK. GRAY 1

Version Number 1.1
Revision Date 03/23/2014

Page 6 of 8
Print Date 3/31/2014

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|------------|------------------|------|------|-----|
| 13463-67-7 | Titanium dioxide | no | 2B | no |

IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Iron chromite brown spinel 12737-27-8 The bi- and trivalent forms of chrome have a low order of acute toxicity, but may cause skin sensitization and irritation to the eyes. No effects have been reported for chromium (III) oxide. Chromium (III) compounds are not considered carcinogenic in animals or humans.

12. ECOLOGICAL INFORMATION

- Persistence and degradability : Not readily biodegradable.
- Environmental Toxicity : Chemicals are not readily available as they are bound within the polymer matrix.
- Bioaccumulation Potential : Chemicals are not readily available as they are bound within the polymer matrix.
- Additional advice : no data available

13. DISPOSAL CONSIDERATIONS

- Product : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
- Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

- U.S. DOT Classification : Not regulated for transportation.
- ICAO/IATA : Refer to specific regulation.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

DK. GRAY 1

Version Number 1.1
 Revision Date 03/23/2014

Page 7 of 8
 Print Date 3/31/2014

IMO/IMDG (maritime) : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

| Chemical Name | CAS-No. | RQ for component | RQ for Mixture/Product |
|-----------------------------|-----------|------------------|------------------------|
| Xylenes (o-, m-, p-isomers) | 1330-20-7 | 100 lbs | 2,727 LB |

California Proposition : Not applicable
 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

| Chemical Name | CAS-No. | Weight percent |
|--|------------|----------------|
| ZINC COMPOUNDS | 68187-51-9 | 5.00 - 10.00 |
| XYLENE (MIXED ISOMERS) | 1330-20-7 | 1.00 - 5.00 |
| CHROMIUM III COMPOUNDS CHROMIUM COMPOUNDS | 12737-27-8 | 10.00 - 30.00 |

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name | CAS-No. | Weight percent | NPRI ID# |
|---|------------|----------------|----------|
| Zinc ferrite brown spinel (C.I. Pigment Yellow 119) | 68187-51-9 | 5.00 - 10.00 | |
| Xylenes (o-, m-, p-isomers) | 1330-20-7 | 1.00 - 5.00 | |
| Manganese oxide (MnO ₂) | 1313-13-9 | 0.10 - 1.00 | |
| Iron chromite brown spinel | 12737-27-8 | 10.00 - 30.00 | |

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

DK. GRAY 1

Version Number 1.1
Revision Date 03/23/2014

Page 8 of 8
Print Date 3/31/2014

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

| CAS-No. |
|------------|
| 7631-86-9 |
| 12737-27-8 |

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Listed
China IECS : Listed
Europe EINECS : Listed
Japan ENCS : Not determined
Korea KECI : Listed
Philippines PICCS : Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.