PolvOne

MATERIAL SAFETY DATA SHEET 139M BEIGE PVC

Version Number 1.0 Revision Date 04/10/2012

Page 1 of 8 Print Date 8/25/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:		1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	139M BEIGE PVC
Product code	:	CC10161546
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Calcium stearate	1592-23-0	1 - 5
Rutile, antimony chromium buff	68186-90-3	1 - 5
Calcium carbonate	1317-65-3	5 - 10
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion Eyes	May be harmful if swallowed.Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET **139M BEIGE PVC**

Version Number 1.0 Revision Date 04/10/2012 Page 2 of 8 Print Date 8/25/2012

Iedical Conditions : None known.		
Aggravated by Exposure:		
		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	not applicable
Flammable Limits		
Upper explosion limit	:	not applicable
Lower explosion limit	:	not applicable
Autoignition temperature	:	not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting	:	Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures		pressure mode should be worn to prevent inhalation of airborne
		contaminants.
Unusual Fire/Explosion	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Hazards		(NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section



MATERIAL SAFETY DATA SHEET **139M BEIGE PVC**

ion Number 1.0 sion Date 04/10/2012	Page Print Date 8/2
	13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSURE CONTROLS/PERSONAL PROTECTION
Respiratory protection	: No personal respiratory protective equipment normally required.
Eye/Face Protection	: Safety glasses with side-shields
Hand protection	: Protective gloves
Skin and body protection	: Long sleeved clothing
Additional Protective Measures	: Safety shoes
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)	

PolvOn<u>e</u>

MATERIAL SAFETY DATA SHEET 139M BEIGE PVC

Version Number 1.0 Revision Date 04/10/2012 Page 4 of 8 Print Date 8/25/2012

Components	Value	Exposure time	Exposure type	List:
	* *		Respirable fraction.	OSHA Z1
Calcium carbonate	15 mg/m3	PEL: PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Calcium stearate	10 mg/m3	Time Weighted Average (TWA):		ACGIH
Rutile, antimony chromium buff	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- solid
 pellets
 TAN
 very faint
 Not determined
 not applicable
 insoluble

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not applicableNot determined

- : Not established
- : not applicable
 - not applicable

:

: not applicable

10. STABILITY AND REACTIVITY

Stability

: Stable

:

Will not occur.

Hazardous Polymerization

Conditions to avoid

: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.

PolyOne

MATERIAL SAFETY DATA SHEET 139M BEIGE PVC

Version Number 1.0 Revision Date 04/10/2012	Page 5 of 8 Print Date <i>8/25/2012</i>
Incompatible Materials	: Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory
	chromium buff		system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1592-23-0	Calcium stearate	Oral LD50	> 10 gm/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

PolyOne.

MATERIAL SAFETY DATA SHEET 139M BEIGE PVC

Version Number 1.0 Revision Date 04/10/2012 Page 6 of 8 Print Date 8/25/2012

NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

	12. ECOLOGICAL INFORMATION		
Persistence and degradability	: Not readily biodegradable.		
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.		
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.		
Additional advice	: no data available		
	13. DISPOSAL CONSIDERATIONS		
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
	14. TRANSPORT INFORMATION		
U.S. DOT Classification	: Not regulated for transportation.		
ICAO/IATA	: Refer to specific regulation.		
IMO/IMDG (maritime)	: Refer to specific regulation.		
	15. REGULATORY INFORMATION		
US Regulations:			
OSHA Status	: Classified as hazardous based on components.		
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.			
US. EPA CERCLA Hazardous	Substances (40 CFR 302)		
Chemical Name C	AS-No. RQ for component RQ for Mixture/Product		

PolvOne

MATERIAL SAFETY DATA SHEET 139M BEIGE PVC

Version Number 1.0 Revision Date 04/10/2012 Page 7 of 8 Print Date 8/25/2012

Chromium (III)	1308-38-9	010 lbs	2,838 LB
oxide			

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent
CHROMIUM III COMPOUNDSCHROMIUM	1308-38-9	0.10 - 1.00
COMPOUNDS		
CHROMIUM III COMPOUNDSCHROMIUM III	68186-90-3	0.10 - 1.00
COMPOUNDSANTIMONY		
COMPOUNDSCHROMIUM COMPOUNDS		

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Aluminum oxide	1344-28-1	0.10 - 1.00	
Chromium (III) oxide	1308-38-9	0.10 - 1.00	
Rutile, antimony chromium buff	68186-90-3	0.10 - 1.00	

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
68186-90-3	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS

: Listed

:

PolyOne

MATERIAL SAFETY DATA SHEET 139M BEIGE PVC

Version Number 1.0 Revision Date 04/10/2012 Page 8 of 8 Print Date 8/25/2012

	16. OTHER INFORMATION	
Philippines PICCS	: Listed	
Korea KECI	: Listed	
Japan ENCS	: Not determined	
Europe EINECS	: Listed	
China IECS	: Not determined	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.