PolvOn<u>e</u>

### MATERIAL SAFETY DATA SHEET XAMAX OFF WHITE

Version Number 1.2 Revision Date 08/03/2012

Page 1 of 6 Print Date 8/28/2012

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012					
Telephone E <b>mergency telephone</b>	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).			
Product name	:	XAMAX OFF WHITE			
Product code	:	CC10167117			
Chemical Name	:	Mixture			
CAS-No.	:	Mixture			
Product Use	:	Industrial Applications			

# ComponentsCAS-No.Weight percent1,6-Hexanediamine, N,N'-bis(2,2,6,6-<br/>tetramethyl-4-piperidinyl)-, polymer with<br/>2,4-dichloro-6-(4-morpholinyl)-1,3,5-<br/>triazine82451-48-71 - 5Titanium dioxide13463-67-730 - 60

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

# MATERIAL SAFETY DATA SHEET **XAMAX OFF WHITE**

Version Number 1.2 Revision Date 08/03/2012 Page 2 of 6 Print Date 8/28/2012

Medical Conditions : None known.						
Aggravated by Exposure:						
		4. FIRST AID MEASURES				
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.				
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.				
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.				
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.				
		5. FIRE-FIGHTING MEASURES				
Flash point	:	not applicable				
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	: : :	not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.				
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.				
	6. A	CCIDENTAL RELEASE MEASURES				
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.				
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.				
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.				

P<u>olyOne</u>

# MATERIAL SAFETY DATA SHEET **XAMAX OFF WHITE**

Version Number 1.2 Revision Date 08/03/2012 Page 3 of 6 Print Date *8/28/2012* 

		7. HANDLING AND STORAGE			
Handling		Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.			
Storage	:	: Keep containers dry and tightly closed to avoid moisture absorpti and contamination. Keep in a dry, cool place.			
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION			
Respiratory protection	:	No personal respiratory protective equipment normally required.			
Eye/Face Protection	:	Safety glasses with side-shields			
Hand protection	:	Protective gloves			
Skin and body protection	:	Long sleeved clothing			
Additional Protective Measures	:	Safety shoes			
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average	Total dust.	OSHA Z1A
		(TWA):		
	10 mg/m3	Time Weighted Average	as Ti	MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
		(STEL):		

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point:
- : solid
  : pellets
  : WHITE
  : very faint
  : Not determined
  : not applicable
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
  Not determined
  Not established
  not applicable
  not applicable
  not applicable
  not applicable

# **MATERIAL SAFETY DATA SHEET** XAMAX OFF WHITE

Version Number 1.2 Revision Date 08/03/2012

Page 4 of 6 Print Date 8/28/2012

Water solubility : insoluble				
10. STABILITY AND REACTIVITY				
Stability	: Stable			
Hazardous Polymerization	: Will not occur.			
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.			
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.			
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.			

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
82451-48-7	1,6-Hexanediamine, N,N'- bis(2,2,6,6-tetramethyl-4- piperidinyl)-, polymer with 2,4-dichloro-6-(4- morpholinyl)-1,3,5- triazine	Irritant	Eyes.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### **12. ECOLOGICAL INFORMATION**

# MATERIAL SAFETY DATA SHEET XAMAX OFF WHITE

Version Number 1.2 Page 5 of 6 Print Date 8/28/2012 Revision Date 08/03/2012 Persistence and degradability : Not readily biodegradable. Environmental Toxicity Chemicals are not readily available as they are bound within the : polymer matrix. **Bioaccumulation Potential** : Chemicals are not readily available as they are bound within the polymer matrix. : no data available Additional advice 13. DISPOSAL CONSIDERATIONS Product : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Contaminated packaging Recycling is preferred when possible. The generator of waste : material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. **14. TRANSPORT INFORMATION** U.S. DOT Classification : Not regulated for transportation. ICAO/IATA Refer to specific regulation. ÷ IMO/IMDG (maritime) Refer to specific regulation. ÷ **15. REGULATORY INFORMATION US Regulations: OSHA Status** : Classified as hazardous based on components. **TSCA Status** All components of this product are listed on or exempt from the : TSCA Inventory. US. EPA CERCLA Hazardous Substances (40 CFR 302) not applicable California Proposition : Not applicable 65

blvUne

## MATERIAL SAFETY DATA SHEET XAMAX OFF WHITE

Version Number 1.2 Revision Date 08/03/2012 Page 6 of 6 Print Date 8/28/2012

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Releas		iventory (INI KI)	CACN	XX7 . 1 . 1 . 4	
Chemical Name		CAS-No.	Weight	NPRI ID#	
Aluminum oxide		1344-28-1	0.10 - 1.00		
Rutile, antimony chromium bu	uff		68186-90-3	0.10 - 1.00	
WHMIS Classification	:	D2A			
DSL	:		s of this product a (DSL) or are exe	re on the Canadian mpt.	n Domestic
lational Inventories:					
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Listed			
Japan ENCS	:	Not determined			
Korea KECI	:	Listed			
Philippines PICCS	:	Not determined			

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.