ne

GARAGE DOOR TRIM PROFILES

Version Number 1.1 Revision Date 02/26/2019 Page 1 of 16 Print Date 06/04/2019

SAFETY DATA SHEET

GARAGE DOOR TRIM PROFILES

Section 1. Identification			
GHS product identifier Chemical name CAS number Other means of identification Product type	:	GARAGE DOOR TRIM PROFILES Mixture Mixture CC10212221 liquid	
Relevant identified uses of the substance or mixture and uses advised againstProduct use:Industrial applications. Plastics.			
Supplier's details	:	POLYONE CORPORATION ColorMatrix Group Inc. 680 North Rocky River Drive, Berea, Ohio, 44017-1628, USA	
		+1 216 622 0100	
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).	

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	SKIN IRRITATION - Category 2

GHS label elements



GARAGE DOOR TRIM PROFILES

Version Number 1.1 Revision Date 02/26/2019 Page 2 of 16 Print Date 06/04/2019

Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	Causes skin irritation.
<u>Precautionary statements</u> General	:	Not applicable.
Prevention	:	Wear protective gloves. Wash hands thoroughly after handling.
Response	:	IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention.
Storage	:	Not applicable.
Disposal	:	Not applicable.

Hazards not otherwise classified : None known.

:

:

:

:

Section 3. Composition/information on ingredients

Substance/mixture Chemical name Other means of identification

Supplemental label elements

Mixture Mixture CC10212221

None known.

CAS number/other identifiers

Ingredient name	%	CAS number
Miscellaneous Compounds Distillates, petroleum, hydrotreated	10 - 25	Not available.
middle		
Carbon black	1 - 3	1333-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

<u>vOne</u>

GARAGE DOOR TRIM PROFILES

Version Number 1.1 Revision Date 02/26/2019

Page 3 of 16 Print Date 06/04/2019

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Eye contact	:	No known significant effects or critical hazards
Inhalation	:	No known significant effects or critical hazards
Skin contact	:	Causes skin irritation.
Ingestion	:	No known significant effects or critical hazards

Over-exposure signs/symptoms

Potential acute health effects



GARAGE DOOR TRIM PROFILES

Version Number 1.1	Page 4 of 16
Revision Date 02/26/2019	Print Date 06/04/2019

Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Indication of immediate medical at	tentio	on and special treatment needed, if necessary
Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or CO_2 . None known.
Specific hazards arising from the chemical Hazardous thermal decomposition products	:	In a fire or if heated, a pressure increase will occur and the container may burst. Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
Special protective actions for fire- fighters Special protective equipment for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated

P<u>olyOne</u>

GARAGE DOOR TRIM PROFILES

Version Number 1.1 Revision Date 02/26/2019 Page 5 of 16 Print Date 06/04/2019

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containn	nent a	nd cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling		
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid
		540



GARAGE DOOR TRIM PROFILES

Version Number 1.1	Page 6 of 16
Revision Date 02/26/2019	Print Date 06/04/2019

Advice on general occupational hygiene	:	breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Miscellaneous Compounds Distillates, petroleum, hydrotreated middle	None.
Carbon black	OSHA PEL 1989 (1989-03-01) TWA 3.5 mg/m3 OSHA PEL (1993-06-30) TWA 3.5 mg/m3 NIOSH REL (1994-06-01) TWA 3.5 mg/m3 TWA 0.1 mgPAH/m³ ACGIH TLV (2010-12-06) TWA 3 mg/m3 Form: Inhalable fraction
Appropriate engineering controls Environmental exposure controls	 Good general ventilation should be sufficient to control worker exposure to airborne contaminants. Emissions from ventilation or work process equipment should be abacked to ensure they comply with the requirements of
	checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers,

)n<u>e</u>.

GARAGE DOOR TRIM PROFILES

Version Number 1.1 Revision Date 02/26/2019 Page 7 of 16 Print Date 06/04/2019

		filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures Eye/face protection	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state

: liquid [liquid]

<u>PolyOne</u>

GARAGE DOOR TRIM PROFILES

Version Number 1.1 Revision Date 02/26/2019

Page 8 of 16 Print Date 06/04/2019

Color		BROWN
Odor	:	Faint odor.
0 401	:	
Odor threshold	:	Not available.
pH	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	insoluble in water.
Partition coefficient: n- octanol/water	:	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature		Not available.
SADT		Not available.
Viscosity	:	Dynamic: Not available.
1000029	•	Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Keep away from strong acids. Oxidizer.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

<u>vOne</u>

GARAGE DOOR TRIM PROFILES

Version Number 1.1 Revision Date 02/26/2019 Page 9 of 16 Print Date 06/04/2019

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Carbon black				
	LD50 Oral	Rat	15,400 mg/	/kg -
Remarks - Inhalation:	No applicable t	oxicity data		
Remarks - Dermal:	No applicable t	oxicity data		
Miscellaneous Compounds Di	stillates, petroleu	m, hydrotreated	middle	
Remarks - Oral:	No applicable t	oxicity data		
Remarks - Inhalation:	No applicable t	oxicity data		
Remarks - Dermal:	No applicable t	oxicity data		
Conclusion/Summary	: M	ixture.Not fully	tested.	
Irritation/Corrosion				
Conclusion/Summary				
Skin		ixture.Not fully		
Eyes		ixture.Not fully		
Respiratory	: M	ixture.Not fully	tested.	
<u>Sensitization</u>				
Conclusion/Summary				
Skin	: M	ixture.Not fully	tested.	
Respiratory	: M	ixture.Not fully	tested.	
<u>Mutagenicity</u>				
Conclusion/Summary	: M	ixture.Not fully	tested.	
Carcinogenicity				
Conclusion/Summary Classification	: M	ixture.Not fully	tested.	
Product/ingredient	OSHA	IARC	NTP	
name				
Carbon black		2B		

Reproductive toxicity

<u>lyOne</u>

GARAGE DOOR TRIM PROFILES

Version Number 1.1 Revision Date 02/26/2019 Page 10 of 16 Print Date 06/04/2019

Conclusion/Summary	:	Mixture.Not	fully tested.	
<u>Teratogenicity</u>				
Conclusion/Summary	:	Mixture.Not	fully tested.	
Specific target organ toxicity (single Not available.	e exp	<u>osure)</u>		
Specific target organ toxicity (repea Not available.	ted e	exposure)		
Aspiration hazard				
Product/ingredient name			Result	
Miscellaneous Compounds Distillates, hydrotreated middle	petro	oleum,	ASPIRATION HAZARD - Category 1	
Information on likely routes of exposure	:	Not available		
Potential acute health effects				
Eye contact	:	No known sig	gnificant effects or critical hazards.	
Inhalation	:		gnificant effects or critical hazards.	
Skin contact	:	Causes skin irritation.		
Ingestion	:	No known significant effects or critical hazards.		
Symptoms related to the physical, ch	nemi	cal and toxicol	ogical characteristics	
		A 1		

Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.

<u>PolyOne</u>

GARAGE DOOR TRIM PROFILES

Version Number 1.1 Revision Date 02/26/2019 Page 11 of 16 Print Date 06/04/2019

Long term exposure **Potential immediate effects** Not available. : **Potential delayed effects** Not available. : Potential chronic health effects **Conclusion/Summary** Mixture.Not fully tested. : General No known significant effects or critical hazards. : Carcinogenicity No known significant effects or critical hazards. : No known significant effects or critical hazards. Mutagenicity : Teratogenicity No known significant effects or critical hazards. : **Developmental effects** No known significant effects or critical hazards. : **Fertility effects** No known significant effects or critical hazards. :

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Inhalation (dusts and mists)	8.933 mg/l

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Carbon black			
Remarks - Acute - Fish:	No applicable toxicity data		
	Acute EC50 37.563 Mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
Remarks - Acute - Aquatic	Acute		
invertebrates.:			
Remarks - Acute - Aquatic	No applicable toxicity data		
plants:			
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:			
Miscellaneous Compounds Dis	stillates, petroleum, hydrotreated midd	le	
Remarks - Acute - Fish:	No applicable toxicity data		
Remarks - Acute - Aquatic	No applicable toxicity data		



GARAGE DOOR TRIM PROFILES

Version Number 1.1 Revision Date 02/26/2019 Page 12 of 16 Print Date 06/04/2019

invertebrates.:		
Remarks - Acute - Aquatic	No applicable toxicity data	
plants:		
Remarks - Chronic - Fish:	No applicable toxicity data	
Remarks - Chronic -	No applicable toxicity data	
Aquatic invertebrates.:		
Conclusion/Summary	: Not available.	
<u>Persistence and degradability</u> Conclusion/Summary	: Not available.	
Bioaccumulative potential Not available.		
Mobility in soil		
Soil/water partition coefficie (KOC)	nt : Not available.	
Other adverse effects	: No known significant effects or critical hazards.	

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

PolyOne

GARAGE DOOR TRIM PROFILES

Version Number 1.1 Revision Date 02/26/2019 Page 13 of 16 Print Date 06/04/2019

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	: Not regulated for transportation.
International Air ICAO/IATA	: Not classified as dangerous goods under transport regulations.
International Water IMO/IMDG	: Not classified as dangerous goods under transport regulations.

Section 15. Regulatory information

U.S. Federal regulations	 United States - TSCA 12(b) - Chemical export notification: None of the components are listed. United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not listed United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined Unitel States - TSCA 8(a) - Division
	 United States - TSCA 8(a) - Preliminary assessment report (PAIR): Listed Quinacridone (C.I. Pigment Violet 19) United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Rutile, antimony chromium buff United States - EPA Clean water act (CWA) section 311 - Hazardous substances: Not listed

GARAGE DOOR TRIM PROFILES

Version Number 1.1 Revision Date 02/26/2019 Page 14 of 16 Print Date 06/04/2019

United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed

Clean Air Act Section 112(b)	:	Listed
Hazardous Air Pollutants (HAPs) Clean Air Act Section 602 Class I	:	Not listed
Substances		NT - 11 - 1
Clean Air Act Section 602 Class II Substances	:	Not listed
DEA List I Chemicals (Precursor	:	Not listed
Chemicals) DEA List II Chemicals (Essential	:	Not listed
Chemicals)		

US. EPA CERCLA Hazardous Substances (40 CFR 302)

:

not applicable

SARA 311/312

Classification

SKIN IRRITATION - Category 2

Composition/information on ingredients

Name	%	Classification
Carbon black	>= 1 - <= 3	CARCINOGENICITY - Category 2
Miscellaneous Compounds	>= 10 - <= 25	Immediate (acute) health hazard
Distillates, petroleum,		
hydrotreated middle		

SARA 313

	Product name	CAS number	%
Form R - Reporting	Rutile, antimony chromium	68186-90-3	50 - 75
requirements	buff		
Supplier notification	Rutile, antimony chromium	68186-90-3	50 - 75
	buff		

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.



GARAGE DOOR TRIM PROFILES

Version Number 1.1 Revision Date 02/26/2019

Page 15 of 16 Print Date 06/04/2019

State regulations		
Massachusetts	:	None of the components are listed.
New York	:	None of the components are listed.
New Jersey	:	The following components are listed:
		Carbon black Rutile, antimony chromium buff
Pennsylvania	:	The following components are listed: Rutile, antimony chromium buff
		Carbon black

California Prop. 65

WARNING: This product can expose you to Carbon black, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Carbon black	No.	No.

United States inventory (TSCA 8b)		All components are listed or exempted.
Clinted States Inventory (15CA 80)	•	An components are listed of exempted.
Canada inventory	:	All components are listed or exempted.
International regulations		
Inventory list		
Australia	:	All components are listed or exempted.
Canada	:	All components are listed or exempted.
China	:	All components are listed or exempted.
Europe inventory	:	Not determined.
Japan	:	Not determined.
New Zealand	:	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	Not determined.
Turkey	:	Not determined.
United States	:	All components are listed or exempted.

Section 16. Other information

GARAGE DOOR TRIM PROFILES

Version Number 1.1 Revision Date 02/26/2019 Page 16 of 16 Print Date 06/04/2019

Hazardous Material Information System (U.S.A.)

Health	/	2
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

History		
Date of printing	:	06/04/2019
Date of issue/Date of revision	:	02/26/2019
Date of previous issue	:	05/20/2015
Version	:	1.1
Key to abbreviations	:	ATE = Acute Toxicity Estimate
·		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From
		Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)
		UN = United Nations
References	:	Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.