## 16045 MIROLIN WHITE ACRYLIC W/ UV

Version Number 1.0 Revision Date 02/15/2018 Page 1 of 17 Print Date 04/23/2018

# SAFETY DATA SHEET

### 16045 MIROLIN WHITE ACRYLIC W/ UV

Section 1. Identification		
GHS product identifier Chemical name CAS number Other means of identification Product type	: : :	16045 MIROLIN WHITE ACRYLIC W/ UV Mixture Mixture CC10244019 liquid
<u>Relevant identified uses of the subs</u> Product use	stance :	e or mixture and uses advised against Industrial applications. Plastics.
Supplier's details	:	<b>POLYONE CORPORATION</b> ColorMatrix Group Inc. 680 North Rocky River Drive, Berea, Ohio, 44017-1628, USA
		+1 216 622 0100
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

# Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	SERIOUS EYE DAMAGE - Category 1
GHS label elements		



## 16045 MIROLIN WHITE ACRYLIC W/ UV

Version Number 1.0 Revision Date 02/15/2018 Page 2 of 17 Print Date 04/23/2018

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	Causes serious eye damage.
Precautionary statements		
General	:	Not applicable.
Prevention	:	Wear eye or face protection.
Response	:	IF IN EYES: Rinse cautiously with water for several minutes.
		Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known.

# Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	CC10244019

### CAS number/other identifiers

Ingredient name	%	CAS number
Titanium dioxide	50 - 75	13463-67-7
Decanedioic acid, bis(2,2,6,6-tetramethyl-4-piperidinyl) ester	3 - 5	52829-07-9

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.



# 16045 MIROLIN WHITE ACRYLIC W/ UV

Version Number 1.0 Revision Date 02/15/2018

### Page 3 of 17 Print Date 04/23/2018

# Section 4. First aid measures

### Description of necessary first aid measures

Eye contact	:	Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	:	Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

### Potential acute health effects



# 16045 MIROLIN WHITE ACRYLIC W/ UV

Version Number 1.0 Revision Date 02/15/2018 Page 4 of 17 Print Date 04/23/2018

Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symptoms	
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness
	blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains
Indication of immediate medica	l attention and special treatment needed, if necessary
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Firefighting measures

### Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or $\rm CO_2$ . None known.
Specific hazards arising from the chemical	:	In a fire or if heated, a pressure increase will occur and the container may burst.
		4/17



# 16045 MIROLIN WHITE ACRYLIC W/ UV

Version Number 1.0	Page 5 of 17
Revision Date 02/15/2018	Print Date 04/23/2018

Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.		
Environmental precautions	:	See also the information in "For non-emergency personnel". Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the		
		product has caused environmental pollution (sewers, waterways, soil or air).		
Methods and materials for containm	Methods and materials for containment and cleaning up			
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.		
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to		



# 16045 MIROLIN WHITE ACRYLIC W/ UV

Version Number 1.0 Revision Date 02/15/2018 Page 6 of 17 Print Date 04/23/2018

local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

### Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits
Titanium dioxide	OSHA PEL 1989 (1989-03-01)
	PEL: Permissible Exposure Level 10 mg/m3 Form: Total dust
	OSHA PEL (1993-06-30)
	PEL: Permissible Exposure Level 15 mg/m3 Form: Total dust



# 16045 MIROLIN WHITE ACRYLIC W/ UV

Version Number 1.0 Revision Date 02/15/2018 Page 7 of 17 Print Date 04/23/2018

		NIOSH REL (1994-06-01)
		ACGIH TLV (1996-05-18) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 10 mg/m3
Decanedioic acid, bis(2,2,6,6- tetramethyl-4-piperidinyl) ester		
Appropriate engineering controls Environmental exposure controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures,



# 16045 MIROLIN WHITE ACRYLIC W/ UV

Version Number 1.0	Page 8 of 17
Revision Date 02/15/2018	Print Date 04/23/2018

		consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based
		on the task being performed and the risks involved and should be
		approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures
		should be selected based on the task being performed and the risks
		involved and should be approved by a specialist before handling this
		product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper
		fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

### Appearance

Physical state	:	liquid [liquid]
Color	:	WHITE
Odor	:	Faint odor.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	insoluble in water.
Partition coefficient: n-	:	Not available.
octanol/water		
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	<b>Dynamic:</b> Not available.
		Kinematic: Not available.



# 16045 MIROLIN WHITE ACRYLIC W/ UV

Version Number 1.0 Revision Date 02/15/2018 Page 9 of 17 Print Date 04/23/2018

# Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Keep away from strong acids. Oxidizer.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

### Information on toxicological effects

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure				
Remarks - Oral:	No applicable toxic	No applicable toxicity data						
<b>Remarks - Inhalation:</b>	No applicable toxic	No applicable toxicity data						
<b>Remarks - Dermal:</b>	No applicable toxic	No applicable toxicity data						
Titanium dioxide								
Remarks - Oral:	No applicable toxic	No applicable toxicity data						
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h				
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-				
Conclusion/Summary Mixture Not fully tested								

Conclusion/Summary

Mixture.Not fully tested.

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium dioxide	Skin - Mild irritant	Human		72 hrs	-
<b>Conclusion/Summary</b>					
Skin	: M	ixture.Not full	y tested.		
Eyes	: M	ixture.Not full	y tested.		
Respiratory	: M	ixture.Not full	y tested.		



# 16045 MIROLIN WHITE ACRYLIC W/ UV

Version Number 1.0 Revision Date 02/15/2018 Page 10 of 17 Print Date 04/23/2018

<b>Sensitization</b>				
Conclusion/Summary Skin Respiratory		fixture.Not fully fixture.Not fully		
Mutagenicity				
Conclusion/Summary	: N	lixture.Not fully	tested.	
<b>Carcinogenicity</b>				
Conclusion/Summary <u>Classification</u>	: N	fixture.Not fully	tested.	
Product/ingredient name	OSHA	IARC	NTP	
Titanium dioxide		2B		
<u>Reproductive toxicity</u> Conclusion/Summary <u>Teratogenicity</u> Conclusion/Summary	: N	fixture.Not fully fixture.Not fully		
Specific target organ toxicity Not available.				
Specific target organ toxicity Not available.	(repeated exp	<u>osure)</u>		
Aspiration hazard Not available.				
Information on likely routes exposure	of : N	ot available.		
Potential acute health effects				
Eye contact Inhalation Skin contact Ingestion	: N : N	lo known signific	e damage. cant effects or critical hazards. cant effects or critical hazards. cant effects or critical hazards.	



# 16045 MIROLIN WHITE ACRYLIC W/ UV

Version Number 1.0 Revision Date 02/15/2018

### Page 11 of 17 Print Date 04/23/2018

### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	:	Adverse symptoms may include the following: pain watering redness
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	:	Adverse symptoms may include the following: stomach pains

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

:	Not available. Not available.
:	Not available. Not available.
:	Mixture.Not fully tested.
:::::::::::::::::::::::::::::::::::::::	No known significant effects or critical hazards. No known significant effects or critical hazards.

### Numerical measures of toxicity

### Acute toxicity estimates

Not available.



## 16045 MIROLIN WHITE ACRYLIC W/ UV

Version Number 1.0 Revision Date 02/15/2018

Page 12 of 17 Print Date 04/23/2018

# Section 12. Ecological information

### **Toxicity**

Product/ingredient name	Result	Species	Exposure			
Decanedioic acid, bis(2,2,6,6-t	etramethyl-4-piperidinyl) ester					
Remarks - Acute - Fish:	No applicable toxicity data					
	Acute EC50 8.6 Mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h			
Remarks - Acute - Aquatic	Acute					
invertebrates.:						
Remarks - Acute - Aquatic	No applicable toxicity data					
plants:						
Remarks - Chronic - Fish:	No applicable toxicity data					
Remarks - Chronic -	No applicable toxicity data					
Aquatic invertebrates.:						
Titanium dioxide						
	Acute LC50 > 1,000 Mg/l Marine water	Fish - Fish	96 h			
Remarks - Acute - Fish:	Acute					
	Acute LC50 3 Mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h			
Remarks - Acute - Aquatic invertebrates.:	Acute					
	Acute LC50 6.5 Mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h			
Remarks - Acute - Aquatic invertebrates.:	Acute					
Remarks - Acute - Aquatic plants:	No applicable toxicity data					
Remarks - Chronic - Fish:	No applicable toxicity data					
<b>Remarks - Chronic -</b>	No applicable toxicity data					
Aquatic invertebrates.:						
Conclusion/Summary	: Not available.					

Conclusion/Summary

Not available.

### Persistence and degradability

Conclusion/Summary

: Not available.

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
	4	0/47	



## 16045 MIROLIN WHITE ACRYLIC W/ UV

Version Number 1.0 Revision Date 02/15/2018

### Page 13 of 17 Print Date 04/23/2018

Decanedioic acid, 1,10-bis(2,2,6,6-	0.35	-	low
tetramethyl-4-piperidinyl) ester			

### Mobility in soil

Soil/water partition coefficient	:	Not available.
(KOC) Other adverse effects	:	No known significant effects or critical hazards.

:

## Section 13. Disposal considerations

**Disposal methods** 

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

# Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	:	Not regulated for transportation.
International Air ICAO/IATA	:	Not classified as dangerous goods under transport regulations.
International Water IMO/IMDG	:	Not classified as dangerous goods under transport regulations.



# 16045 MIROLIN WHITE ACRYLIC W/ UV

Version Number 1.0 Revision Date 02/15/2018 Page 14 of 17 Print Date 04/23/2018

# Section 15. Regulatory information

U.S. Federal regulations	:	United States - TSCA 12(b) - Chemical export notification: None of the components are listed. United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a) - Final significant new use rules: Not listed United States - TSCA 5(a) - Proposed significant new use rules: Not listed United States - TSCA 5(a) - Proposed significant new use rules: Not listed United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Rutile, antimony chromium buff
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	:	Listed
Clean Air Act Section 602 Class I Substances	:	Not listed
Clean Air Act Section 602 Class II Substances	:	Not listed
DEA List I Chemicals (Precursor Chemicals)	:	Not listed



## 16045 MIROLIN WHITE ACRYLIC W/ UV

Version Number 1.0 Revision Date 02/15/2018 Page 15 of 17 Print Date 04/23/2018

**DEA List II Chemicals (Essential** : Not listed **Chemicals**)

### US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

### SARA 311/312

Classification

: Immediate (acute) health hazard

### **Composition/information on ingredients**

Name	%	Classification
Decanedioic acid, bis(2,2,6,6- tetramethyl-4-piperidinyl) ester	3 - 5	АН
Titanium dioxide	50 - 75	СН

#### SARA 313

	Product name	CAS number	%
Form R - Reporting	Aluminum oxide	1344-28-1	3 - 5
requirements			
Supplier notification	Aluminum oxide	1344-28-1	3 - 5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations	
Massachusetts	: None of the components are listed.
New York	: None of the components are listed.
New Jersey	: The following components are listed:
	Aluminum oxide
	Titanium dioxide
Pennsylvania	: The following components are listed:
	Aluminum oxide
	Titanium dioxide

#### i namum (

### <u>California Prop. 65</u>

WARNING: This product contains a chemical known to the State of California to cause cancer.

United States inventory (TSCA 8b) : All components are listed or exempted.

15/17



## 16045 MIROLIN WHITE ACRYLIC W/ UV

Version Number 1.0 Revision Date 02/15/2018 Page 16 of 17 Print Date 04/23/2018

All components are listed or exempted. **Canada** inventory • **International regulations Inventory list** Australia All components are listed or exempted. : Canada All components are listed or exempted. : China All components are listed or exempted. : **Europe inventory** All components are listed or exempted. : Not determined. Japan : All components are listed or exempted. New Zealand : **Philippines** All components are listed or exempted. : **Republic of Korea** All components are listed or exempted. : Taiwan All components are listed or exempted. : Turkev Not determined. : **United States** All components are listed or exempted. :

# Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

Date of printing	:	04/23/2018
Date of issue/Date of revision	:	02/15/2018
Date of previous issue	:	00/00/0000
Version	:	1.0
Key to abbreviations	:	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association



## 16045 MIROLIN WHITE ACRYLIC W/ UV

Version Number 1.0 Revision Date 02/15/2018 Page 17 of 17 Print Date 04/23/2018

IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations Not available.

References

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.