UV SLATE GRAY 2050HG

Version Number 1.0 Revision Date 04/11/2017 Page 1 of 15 Print Date 04/11/2018

SAFETY DATA SHEET

UV SLATE GRAY 2050HG

Section 1. Identification	on	
GHS product identifier Chemical name CAS number Other means of identification Product type		UV SLATE GRAY 2050HG Mixture Mixture CC10260112 solid
	tance :	e or mixture and uses advised against Industrial applications. Plastics.
Supplier's details	:	POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012 1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.
Classification of the substance or mixture	:	Not classified.
GHS label elements		
Signal word	:	No signal word.
		1/15

UV SLATE GRAY 2050HG

Version Number 1.0 Revision Date 04/11/2017 Page 2 of 15 Print Date 04/11/2018

Hazard statements

No known significant effects or critical hazards.

Precautionary statements

General	:	Not applicable.
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known.

Section 3. Composition/information on ingredients

:

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	CC10260112

CAS number/other identifiers

Ingredient name	%	CAS number
Titanium dioxide	10 - 30	13463-67-7
Carbon black	1 - 5	1333-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses.



UV SLATE GRAY 2050HG

Version Number 1.0	Page 3 of 15
Revision Date 04/11/2017	Print Date 04/11/2018

	Get medical attention if irritation occurs.
:	Remove victim to fresh air and keep at rest in a position comfortable
	for breathing. Get medical attention if symptoms occur. In case of
	inhalation of decomposition products in a fire, symptoms may be
	delayed. The exposed person may need to be kept under medical
	surveillance for 48 hours.
:	Flush contaminated skin with plenty of water. Remove contaminated
	clothing and shoes. Get medical attention if symptoms occur.
:	Wash out mouth with water. Remove victim to fresh air and keep at
	rest in a position comfortable for breathing. If material has been
	swallowed and the exposed person is conscious, give small quantities
	of water to drink. Do not induce vomiting unless directed to do so by
	medical personnel. Get medical attention if symptoms occur.
	:

Most important symptoms/effects, acute and delayed

Potential acute health effects	
Eye contact Inhalation Skin contact Ingestion <u>Over-exposure signs/symptoms</u>	 No known significant effects or critical hazards.
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate medical	attention and special treatment needed, if necessary
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Firefighting measures



UV SLATE GRAY 2050HG

Version Number 1.0 Revision Date 04/11/2017 Page 4 of 15 Print Date 04/11/2018

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or CO_2 . None known.
Specific hazards arising from the chemical	:	No specific fire or explosion hazard.
Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides phosphorus oxides halogenated compounds metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containme	ent a	nd cleaning up
Small spill	:	Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Move containers from spill area. Prevent entry into sewers, water
4/15		

olvOne

UV SLATE GRAY 2050HG

Version Number 1.0 Revision Date 04/11/2017 Page 5 of 15 Print Date 04/11/2018

courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures Advice on general occupational hygiene	:	Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Carbon black	OSHA PEL 1989 (1989-03-01)
	PEL: Permissible Exposure Level 3.5 mg/m3
	OSHA PEL (1993-06-30)
	PEL: Permissible Exposure Level 3.5 mg/m3
	NIOSH REL (1994-06-01)
	Time Weighted Average (TWA) 3.5 mg/m3
	Time Weighted Average (TWA)
	ACGIH TLV (2010-12-06)
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:
	Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction



UV SLATE GRAY 2050HG

Version Number 1.0 Revision Date 04/11/2017

Titanium dioxide		OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 15 mg/m3 Form: Total dust NIOSH REL (1994-06-01) ACGIH TLV (1996-05-18) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 10 mg/m3
Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker
Environmental exposure controls	:	exposure to airborne contaminants. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures Eye/face protection	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that

6/15

lyOne.

UV SLATE GRAY 2050HG

Version Number 1.0 Revision Date 04/11/2017 Page 7 of 15 Print Date 04/11/2018

meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state	:	solid [Pellets.]
Color		GREY
Odor		Faint odor.
Odor threshold	:	Not available.
pH	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	insoluble in water.
Partition coefficient: n- octanol/water	:	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	Dynamic: Not available.
-		Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.		
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).		
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.		
-//-				



UV SLATE GRAY 2050HG

Version Number 1.0 Revision Date 04/11/2017

Page 8 of 15 Print Date 04/11/2018

Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Keep away from strong acids.
		Oxidizer.
Hazardous decomposition	:	Under normal conditions of storage and use, hazardous decomposition
products		products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Carbon black				
	LD50 Oral	Rat	15,400 mg/kg	-
Titanium dioxide	•			· ·
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-
Conclusion/Summary	: Mixtu	re.Not fully tested.	· · · ·	•

Conclusion/Summary

Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium dioxide	Skin - Mild	Human		72 hrs	-
	irritant				
Conclusion/Summary					
Skin		/ixture.Not fu			
Eyes		/ixture.Not fu			
Respiratory	: N	lixture.Not fu	Illy tested.		
<u>Sensitization</u>					
Conclusion/Summary					
Skin		/lixture.Not fu	•		
Respiratory	: N	lixture.Not fu	Illy tested.		
<u>Mutagenicity</u>					
Conclusion/Summary	: N	/lixture.Not fu	ally tested.		
Carcinogenicity					



UV SLATE GRAY 2050HG

Version Number 1.0 Revision Date 04/11/2017 Page 9 of 15 Print Date 04/11/2018

Conclusion/Summary	: 1	Mixture.Not fu	Illy tested.
<u>Classification</u>			
Product/ingredient	OSHA	IARC	NTP
name			
Carbon black		2B	
<u>Reproductive toxicity</u>			
Conclusion/Summary	: 1	Mixture.Not fu	illy tested.
Teratogenicity			
Conclusion/Summary	:]	Mixture.Not fu	ally tested.
Specific target organ toxicity Not available.	(single expos	<u>ure)</u>	
Specific target organ toxicity Not available.	(repeated ex	posure)	
Aspiration hazard Not available.			
Information on likely routes of exposure	of :]	Not available.	
Potential acute health effects			
Eye contact	: 1	No known sigr	hificant effects or critical hazards.
Inhalation			nificant effects or critical hazards.
Skin contact			nificant effects or critical hazards.
Ingestion	: 1	No known sigr	nificant effects or critical hazards.
Symptoms related to the phys	ical, chemica	l and toxicolo	gical characteristics
Eye contact	: 1	No specific dat	a.
Inhalation		No specific dat	
Skin contact		No specific dat	
Ingestion	: 1	No specific dat	a.
Delayed and immediate effect Short term exposure	s as well as cl	hronic effects	from short and long-term exposure

P<u>olyOne</u>

UV SLATE GRAY 2050HG

Version Number 1.0 Revision Date 04/11/2017

Page 10 of 15 Print Date 04/11/2018

:	Not available. Not available.
:	Not available. Not available.
:	Mixture.Not fully tested.
::	No known significant effects or critical hazards. No known significant effects or critical hazards.
	:

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Carbon black			
	Acute EC50 37.563 mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
	Acute LC50 61.547 mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
Titanium dioxide			
	Acute LC50 > 1,000,000 μg/l	Fish - Fish	96 h
	Marine water		
	Acute LC50 > 1,000 mg/l Fresh	Fish - Fish	96 h
	water		
	Acute LC50 13 mg/l Fresh water	Aquatic invertebrates.	48 h
		Daphnia	
	Acute LC50 6.5 mg/l Fresh water	Aquatic invertebrates.	48 h
	10/15		



UV SLATE GRAY 2050HG

Version Number 1.0 Revision Date 04/11/2017

		Daphnia	
	Acute LC50 3 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute LC50 15.9 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute LC50 3.6 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute LC50 11 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute LC50 13.4 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute EC50 27.8 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
	Acute EC50 19.3 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
	Acute EC50 35.306 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
UV SLATE GRAY 2050HG			
Remarks - Acute - Aquatic invertebrates.:	Chemicals are not readily available a	s they are bound within the	e polymer matrix.
Conclusion/Summary	: Chemicals are not readil polymer matrix.	ly available as they are bound	nd within the
Persistence and degradability	<u>v</u>		
Conclusion/Summary	: Chemicals are not readil polymer matrix.	y available as they are bound	nd within the
Conclusion/Summary	: Chemicals are not readil polymer matrix.	y available as they are bound	nd within the

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Titanium dioxide		-	low

<u>Mobility in soil</u>

Soil/water partition coefficient	:	Not available.
(KOC)		
Other adverse effects	:	No known significant effects or critical hazards.

Section 13. Disposal considerations

vOne

UV SLATE GRAY 2050HG

Version Number 1.0	Page 12 of 15
Revision Date 04/11/2017	Print Date 04/11/2018

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	:	Not regulated for transportation.
International Air ICAO/IATA	:	Not classified as dangerous goods under transport regulations.
International Water IMO/IMDG	:	Not classified as dangerous goods under transport regulations.

Section 15. Regulatory information

U.S. Federal regulations	:	United States - TSCA 12(b) - Chemical export notification: None of the components are listed.
		United States - TSCA 4(a) - Final Test Rules: Not listed
		United States - TSCA 4(a) - ITC Priority list: Not listed
		United States - TSCA 4(a) - Proposed test rules: Not listed
		United States - TSCA 4(f) - Priority risk review: Not listed
		United States - TSCA 5(a)2 - Final significant new use rules: Not listed
		United States - TSCA 5(a)2 - Proposed significant new use rules:
		Not listed
		United States - TSCA 5(e) - Substances consent order: Not listed

12/15

P<u>olyOne</u>

UV SLATE GRAY 2050HG

Version Number 1.0	Page 13 of 15
Revision Date 04/11/2017	Print Date 04/11/2018

		United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined
		United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed
		United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed
		United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority
		pollutants: Not listed United States - EPA Clean water act (CWA) section 311 - Hazardous substances: Not listed
		United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed
		United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed
		United States - Department of commerce - Precursor chemical: Not listed
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	:	Not listed
Clean Air Act Section 602 Class I Substances	:	Not listed

Clean Air Act Section 602 Class I	:	Not listed
Substances Clean Air Act Section 602 Class II		Not listed
Substances		
DEA List I Chemicals (Precursor Chemicals)	:	Not listed
DEA List II Chemicals (Essential	:	Not listed
Chemicals)		

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification

: Not applicable.

Composition/information on ingredients

Name	%	Classification
Carbon black	1 - 5	СН



UV SLATE GRAY 2050HG

Version Number 1.0 Revision Date 04/11/2017

Page 14 of 15 Print Date 04/11/2018

Titanium dioxide	10 -	- 30	СН
SARA 313 Not applicable.			
State regulations			
Massachusetts	:	None of the components are listed	
New York	:	None of the components are listed	
New Jersey Pennsylvania	:	The following components are liss Titanium dioxide Carbon black Iron oxide The following components are liss	
		Titanium dioxide	
		Carbon black	
		Iron oxide	
		Silica, amorphous	
California Prop. 65 WARNING: This product contains a c	hemi	cal known to the State of Californi	a to cause cancer.
United States inventory (TSCA 8b)	:	All components are listed or exer	npted.
Canada inventory	:	All components are listed or exer	npted.
International regulations			
nventory list			
Australia	:	All components are listed or exer	
Canada	:	All components are listed or exer	
China	:	All components are listed or exer	
Europe inventory	:	All components are listed or exer	
Japan Norr Zaaland	:	All components are listed or exer	
New Zealand	:	All components are listed or exer	
Philippines Republic of Korea	:	All components are listed or exer All components are listed or exer	
Taiwan	:	All components are listed or exer	
			inpres.
Turkey	:	Not determined.	



UV SLATE GRAY 2050HG

Version Number 1.0 Revision Date 04/11/2017 Page 15 of 15 Print Date 04/11/2018

Section 16. Other information

Hazardous Material Information System (U.S.A.) :			
Health	*	1	
Flammability		0	
Physical hazards		0	

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868. The customer is responsible for determining the PPE code for this material.

History		
Date of printing	:	04/11/2018
Date of issue/Date of revision	:	04/11/2017
Date of previous issue	:	00/00/0000
Version	:	1.0
Key to abbreviations	:	ATE = Acute Toxicity Estimate
		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From
		Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)
		UN = United Nations
References	•	Not available.
	•	

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.