

PULVERIZED YELLOW-F

Version Number 1.0 Revision Date 05/10/2017

Page 1 of 17 Print Date 05/16/2017

SAFETY DATA SHEET

PULVERIZED YELLOW-F

Section 1. Identification

GHS product identifier PULVERIZED YELLOW-F

Chemical name Mixture CAS number Mixture Other means of identification CC10262145

Product type solid

Relevant identified uses of the substance or mixture and uses advised against

Product use Industrial applications. Plastics.

POLYONE CORPORATION Supplier's details

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number (with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

COMBUSTIBLE DUSTS

GHS label elements

Signal word Warning

Hazard statements May form combustible dust concentrations in air.



PULVERIZED YELLOW-F

Version Number 1.0 Page 2 of 17 Revision Date 05/10/2017 Print Date 05/16/2017

Precautionary statements

General: Not applicable.Prevention: Not applicable.Response: Not applicable.Storage: Not applicable.Disposal: Not applicable.

Supplemental label elements : Keep container tightly closed.

Hazards not otherwise classified : Handling and/or processing of this material may generate a dust which

can cause mechanical irritation of the eyes, skin, nose and throat.

Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: CC10262145

CAS number/other identifiers

Ingredient name	%	CAS number
Titanium dioxide	10 - 30	13463-67-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if

irritation occurs.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If not breathing, if breathing is irregular or if respiratory

arrest occurs, provide artificial respiration or oxygen by trained



PULVERIZED YELLOW-F

Version Number 1.0 Revision Date 05/10/2017 Page 3 of 17 Print Date 05/16/2017

personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated

clothing and shoes. Get medical attention if symptoms occur. Wash

clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion: Wash out mouth with water. Remove dentures if any. Remove victim

to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie,

belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Exposure to airborne concentrations above statutory or recommended

exposure limits may cause irritation of the eyes.

Inhalation : Exposure to airborne concentrations above statutory or recommended

exposure limits may cause irritation of the nose, throat and lungs.

Skin contact

No known significant effects or critical hazards.

Ingestion

No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

irritation redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact: No specific data.Ingestion: No specific data.



PULVERIZED YELLOW-F

Version Number 1.0 Revision Date 05/10/2017 Page 4 of 17 Print Date 05/16/2017

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without

suitable training. It may be dangerous to the person providing aid to

give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Hazardous thermal

decomposition products

Suitable extinguishing media Unsuitable extinguishing media Use dry chemical powder.

: Avoid high pressure media which could cause the formation of a

potentially explosible dust-air mixture.

Specific hazards arising from the

chemical

: Decomposition products may include the following materials:

May form explosible dust-air mixture if dispersed.

carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

Special protective actions for fire-

fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-

exposed containers cool.

Special protective equipment for

fire-fighters

: Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without



PULVERIZED YELLOW-F

Version Number 1.0 Revision Date 05/10/2017

Page 5 of 17 Print Date 05/16/2017

unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

suitable training. Evacuate surrounding areas. Keep unnecessary and

For emergency responders If specialized clothing is required to deal with the spillage, take note

of any information in Section 8 on suitable and unsuitable materials.

See also the information in "For non-emergency personnel".

Avoid dispersal of spilled material and runoff and contact with soil, **Environmental precautions**

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

Methods and materials for containment and cleaning up

Small spill Move containers from spill area. Use spark-proof tools and explosion-

> proof equipment. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste

disposal contractor.

Large spill Move containers from spill area. Use spark-proof tools and explosion-

proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency

contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures Put on appropriate personal protective equipment (see Section 8). Do

> not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid the creation of dust when handling and avoid all

possible sources of ignition (spark or flame). Prevent dust

accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding

5/17



PULVERIZED YELLOW-F

Version Number 1.0 Revision Date 05/10/2017 Page 6 of 17 Print Date 05/16/2017

Advice on general occupational hygiene

and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Titanium dioxide	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 15 mg/m3 Form: Total dust
	NIOSH REL (1994-06-01) ACGIH TLV (1996-05-18) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 10 mg/m3

Appropriate engineering controls

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.



PULVERIZED YELLOW-F

Version Number 1.0 Revision Date 05/10/2017 Page 7 of 17 Print Date 05/16/2017

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. If operating conditions cause high dust concentrations to be produced, use dust goggles.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.



PULVERIZED YELLOW-F

Version Number 1.0 Revision Date 05/10/2017 Page 8 of 17 Print Date 05/16/2017

Section 9. Physical and chemical properties

Appearance

Physical state : solid [Very fine powder.]

Color YELLOW Odor Not available. **Odor threshold** Not available. Hq Not available. **Melting point** Not available. **Boiling point** Not available. Flash point Not available. **Burning time** Not available. **Burning rate** Not available. Not available. **Evaporation rate** Flammability (solid, gas) Not available.

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressure

Vapor density

Relative density

Solubility

Solubility in water

Partition coefficient: n
Not available.

Not available.

Not available.

Not available.

Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : Avoid the creation of dust when handling and avoid all possible

sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers

and equipment before transferring material. Prevent dust



PULVERIZED YELLOW-F

Version Number 1.0 Page 9 of 17 Revision Date 05/10/2017 Print Date 05/16/2017

accumulation.

Incompatible materials: Reactive or incompatible with the following materials:

oxidizing materials

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Titanium dioxide				
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-

Conclusion/Summary : Mixture. Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium dioxide	Skin - Mild	Human		72 hrs	=
	irritant				

Conclusion/Summary

Skin: Mixture.Not fully tested.Eyes: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin : Mixture.Not fully tested.
Respiratory : Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture. Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.



PULVERIZED YELLOW-F

Version Number 1.0 Page 10 of 17 Revision Date 05/10/2017 Print Date 05/16/2017

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of

exposure

Not available.

Potential acute health effects

Eye contact : Exposure to airborne concentrations above statutory or recommended

exposure limits may cause irritation of the eyes.

Inhalation : Exposure to airborne concentrations above statutory or recommended

exposure limits may cause irritation of the nose, throat and lungs.

Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

irritation redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No specific data.

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.



PULVERIZED YELLOW-F

Version Number 1.0 Revision Date 05/10/2017 Page 11 of 17 Print Date 05/16/2017

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary: Mixture. Not fully tested.

General: Repeated or prolonged inhalation of dust may lead to chronic

respiratory irritation.

Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium dioxide			
	Acute LC50 > 1,000,000 μ g/l	Fish - Fish	96 h
	Marine water		
	Acute LC50 > 1,000 mg/l Fresh	Fish - Fish	96 h
	water		
	Acute LC50 13 mg/l Fresh water	Aquatic invertebrates.	48 h
		Daphnia	
	Acute LC50 6.5 mg/l Fresh water	Aquatic invertebrates.	48 h
		Daphnia	
	Acute LC50 3 mg/l Fresh water	Aquatic invertebrates.	48 h
		Crustaceans	
	Acute LC50 15.9 mg/l Fresh water	Aquatic invertebrates.	48 h
		Crustaceans	

11/17



PULVERIZED YELLOW-F

Version Number 1.0 Revision Date 05/10/2017 Page 12 of 17 Print Date 05/16/2017

Acute LC50 3.6 mg/l Fresh water	Aquatic invertebrates.	48 h
	Crustaceans	
Acute LC50 11 mg/l Fresh water	Aquatic invertebrates.	48 h
	Crustaceans	
Acute LC50 13.4 mg/l Fresh water	Aquatic invertebrates.	48 h
	Crustaceans	
Acute EC50 27.8 mg/l Fresh water	Aquatic invertebrates.	48 h
	Daphnia	
Acute EC50 19.3 mg/l Fresh water	Aquatic invertebrates.	48 h
	Daphnia	
Acute EC50 35.306 mg/l Fresh	Aquatic invertebrates.	48 h
water	Daphnia	

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Titanium dioxide		-	low

Mobility in soil

Soil/water partition coefficient

(KOC)

Other adverse effects

Not available.

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal



PULVERIZED YELLOW-F

Version Number 1.0 Revision Date 05/10/2017 Page 13 of 17 Print Date 05/16/2017

of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water : Not regulated for transportation.

International Air ICAO/IATA

: Consult mode specific transport rules

International Water

IMO/IMDG

: Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations : United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed

United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not

determined

United States - TSCA 8(a) - Preliminary assessment report

(PAIR): Not listed

United States - TSCA 8(c) - Significant adverse reaction (SAR):

Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed



PULVERIZED YELLOW-F

Version Number 1.0 Revision Date 05/10/2017 Page 14 of 17 Print Date 05/16/2017

 $\label{lem:condition} \textbf{United States - EPA Clean water act (CWA) section 307 - Priority }$

pollutants: Listed Zinc stearate

Chromium (III) oxide

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

United States - Department of commerce - Precursor chemical:

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

Substances

Clean Air Act Section 602 Class II

Substances

DEA List I Chemicals (Precursor

Chemicals)

DEA List II Chemicals (Essential

Chemicals)

Listed

Not listed

Not listed

Not listed

Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification : Fire hazard

Composition/information on ingredients

Name	%	Classification
Titanium dioxide	10 - 30	СН

SARA 313

	Product name	CAS number	%
Form R - Reporting	Zinc stearate	557-05-1	10 - 30
requirements			
	Chromium (III) oxide	1308-38-9	1 - 5
Supplier notification	Zinc stearate	557-05-1	10 - 30



PULVERIZED YELLOW-F

Version Number 1.0 Revision Date 05/10/2017 Page 15 of 17 Print Date 05/16/2017

Chromium (III) oxide 1308-38-9 1 - 5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts: None of the components are listed.New York: None of the components are listed.New Jersey: The following components are listed:

Zinc stearate Titanium dioxide

Silica, amorphous, precipitated and gel

Chromium (III) oxide

Pennsylvania : The following components are listed:

Zinc stearate

Titanium dioxide

Silica, amorphous, precipitated and gel

Chromium (III) oxide

Silica, amorphous

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

United States inventory (TSCA 8b) : All components are listed or exempted.

Canada inventory : All components are listed or exempted.

International regulations

Inventory list

Australia All components are listed or exempted. Canada All components are listed or exempted. All components are listed or exempted. China **Europe inventory** All components are listed or exempted. All components are listed or exempted. Japan All components are listed or exempted. **New Zealand Philippines** All components are listed or exempted. Republic of Korea All components are listed or exempted. All components are listed or exempted. **Taiwan**



PULVERIZED YELLOW-F

Version Number 1.0 Page 16 of 17 Revision Date 05/10/2017 Print Date 05/16/2017

Turkey : All components are listed or exempted.
United States : All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.):

Health	*	1
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868. The customer is responsible for determining the PPE code for this material.

History

Date of printing: 05/16/2017Date of issue/Date of revision: 05/10/2017Date of previous issue: 00/00/0000

Version : 1.0

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

 $IBC = Intermediate \ Bulk \ Container$

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

 $MARPOL = International \ Convention \ for \ the \ Prevention \ of \ Pollution \ From$

Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.



PULVERIZED YELLOW-F

 Version Number 1.0
 Page 17 of 17

 Revision Date 05/10/2017
 Print Date 05/16/2017