FA-96

Version Number 1.0 Revision Date 01/17/2018

vOne

Page 1 of 18 Print Date 01/18/2018

SAFETY DATA SHEET

FA-96

Section 1. Identification		
GHS product identifier Chemical name CAS number Other means of identification Product type	:	FA-96 Mixture Mixture CC10276291 liquid
<u>Relevant identified uses of the sub</u> Product use	stance :	or mixture and uses advised against Industrial applications. Plastics.
Supplier's details	:	POLYONE CORPORATION ColorMatrix Group Inc. 680 North Rocky River Drive, Berea, Ohio, 44017-1628, USA
Emergency telephone number (with hours of operation)	:	+1 216 622 0100 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	SERIOUS EYE DAMAGE - Category 1
GHS label elements		

FA-96

Version Number 1.0 Revision Date 01/17/2018 ____

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	Causes serious eye damage.
<u>Precautionary statements</u> General		Not applicable
	:	Not applicable.
Prevention	:	Wear eye or face protection.
Response	:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
		Immediately call a POISON CENTER or physician.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	None known.
		N I

None known.

Section 3. Composition/information on ingredients

:

Substance/mixture:MixtureChemical name:MixtureOther means of identification:CC10276291

CAS number/other identifiers

Hazards not otherwise classified

Ingredient name	%	CAS number
Calcium oxide	5 - 10	1305-78-8
Sodium bicarbonate	3 - 5	144-55-8
Quartz	0.3 - 1	14808-60-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Page 2 of 18 Print Date 01/18/2018

FA-96

Version Number 1.0 Revision Date 01/17/2018 <u>PolyOne</u>

Page 3 of 18 Print Date 01/18/2018

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	:	Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

FA-96



Version Number 1.0 Revision Date 01/17/2018

Potential acute health effects

Page 4 of 18 Print Date 01/18/2018

Most important symptoms/effects, acute and delayed

Totential acute neurin eneces		
Eye contact	:	Causes serious eye damage.
Inhalation	-	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.
Over-exposure signs/symptoms		
Eye contact	:	Adverse symptoms may include the following: pain watering redness
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: pain or irritation redness
Ingestion	:	blistering may occur Adverse symptoms may include the following: stomach pains
Indication of immediate medical atte	entio	n and special treatment needed, if necessary
Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under
Specific treatments	:	medical surveillance for 48 hours. No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media :	:	In case of fire, use water spray (fog), foam, dry chemical or CO_2 .
Unsuitable extinguishing media :	:	None known.

FA-96

PolyOne

Version Number 1.0	Page 5 of 18
Revision Date 01/17/2018	Print Date 01/18/2018

Specific hazards arising from the chemical Hazardous thermal decomposition products	:	In a fire or if heated, a pressure increase will occur and the container may burst. Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containme	ent a	nd cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment
5/18		

FA-96

Version Number 1.0 Revision Date 01/17/2018

vOne

Page 6 of 18 Print Date 01/18/2018

plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name

Exposure limits

FA-96

Version Number 1.0 Revision Date 01/17/2018

Page 7 of 18 Print Date 01/18/2018

Permissible Exposure Level 2 mg/m3 Sodium bicarbonate Quartz OSHA PEL 1989 (1989-03-01) Calculated as Quartz PEL: Permissible Exposure Level 0.1 mg/m3 Form: Respirable dust OSHA PEL 23 (1997-09-03) Time Weighted Average (TWA) 10 mg/m3 Form: Respirable Time Weighted Average (TWA) 30 mg/m3 Form: Total dust NIOSH REL (1994-06-01) Time Weighted Average (TWA) 0.05 mg/m3 Form: Respirable dust ACCHI TLV (2005-12-09) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 0.025 mg/m3 Form: Respirable fraction OSHA PEL (2016-06-23) PEL: Permissible Exposure Level 0.05 mg/m3 Form: Respirable dust ACCHI TLV (2005-12-09) Appropriate engineering controls : If user operations generate dust, fumes, gas, vapor or mist, use proces enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Environmental exposure controls : Environmental exposure controls : Environmental exposure controls : Individual protection measures : Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the en- of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated	Calcium oxide	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 5 mg/m3 OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 5 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 2 mg/m3 ACGIH TLV (1994-09-01) TLV-TWA: Threshold Limit Value - Time weighted average PEL:
Quartz OSHA PEL 1989 (1989-03-01) Calculated as Quartz PEL: Permissible Exposure Level 0.1 mg/m3 Form: Respirable dust OSHA PEL Z3 (1997-09-03) Time Weighted Average (TWA) 10 mg/m3 Form: Respirable Time Weighted Average (TWA) 10 mg/m3 Form: Total dust NIOSH REL (1994-06-01) Time Weighted Average (TWA) 0.05 mg/m3 Form: Respirable dust ACGHI TLV (2005-12-09) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 0.025 mg/m3 Form: Respirable fraction OSHA PEL (2016-06-23) PEL: Permissible Exposure Level 0.05 mg/m3 Form: Respirable dust Acegin true operations generate dust, fumes, gas, vapor or mist, use proces enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Environmental exposure controls : Individual protection measures : Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the en- of the working period. Appropriate techniques should be used to remove potentially contaminanta clothing. Wash contaminantad		
PEL: Permissible Exposure Level 0.1 mg/m3 Form: Respirable dust OSHA PEL Z3 (1997-09-03) Time Weighted Average (TWA) 10 mg/m3 Form: Respirable Time Weighted Average (TWA) 10 mg/m3 Form: Total dust NIOSH REL (1994-06-01) Time Weighted Average (TWA) 0.05 mg/m3 Form: Total dust NIOSH REL (1994-06-01) Time Weighted Average (TWA) 0.05 mg/m3 Form: Respirable dust ACGIH TLV (2005-12-09) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 0.025 mg/m3 Form: Respirable fraction OSHA PEL (2016-06-23) PEL: Permissible Exposure Level 0.05 mg/m3 Form: Respirable dust declared average PEL: Permissible Exposure Level 0.05 mg/m3 Form: Respirable dust enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.Environmental exposure controls:If user operations generate dust, fumes, gas, vapor or mist, use proces enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommented or statutory limits.Environmental exposure controls:Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.Individual protection measures:Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the en of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated	Sodium bicarbonate	
 enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Environmental exposure controls Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Individual protection measures Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the enof the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated 	Quartz	 PEL: Permissible Exposure Level 0.1 mg/m3 Form: Respirable dust OSHA PEL Z3 (1997-09-03) Time Weighted Average (TWA) Form: Respirable Time Weighted Average (TWA) 10 mg/m3 Form: Respirable Time Weighted Average (TWA) 30 mg/m3 Form: Total dust NIOSH REL (1994-06-01) Time Weighted Average (TWA) 0.05 mg/m3 Form: Respirable dust ACGIH TLV (2005-12-09) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 0.025 mg/m3 Form: Respirable fraction
 Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Individual protection measures Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the enoif the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated 	Appropriate engineering controls	enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any
Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated	Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be
products, before eating, smoking and using the lavatory and at the en- of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated	Individual protection measures	
7/18	Hygiene measures	products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

PolyOne.

FA-96



Version Number 1.0 Revision Date 01/17/2018	Page 8 of 18 Print Date 01/18/2018
Eye/face protection	 showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Approved by a specialist before handling this product. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	 Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be

Section 9. Physical and chemical properties

Appearance

Physical state	: liquid [liquid]
Color	: NOT APPLICABLE
Odor	: Faint odor.
Odor threshold	: Not available.
рН	: Not available.
Melting point	: Not available.
Boiling point	: Not available.
Flash point	: Not available.
Burning time	: Not available.

used according to a respiratory protection program to ensure proper

fitting, training, and other important aspects of use.

FA-96

Version Number 1.0 Revision Date 01/17/2018

PolyOne

Page 9 of 18 Print Date 01/18/2018

Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	insoluble in water.
Partition coefficient: n- octanol/water	:	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature		Not available.
SADT	:	Not available.
~	•	
Viscosity	:	Dynamic: Not available.
		Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Keep away from strong acids. Oxidizer.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure	
Remarks - Oral:	No applicable toxic	No applicable toxicity data			



Version Number 1.0 Revision Date 01/17/2018 PolyOne.

Remarks - Inhalation:	No applicable toxicity data					
Remarks - Dermal:	No applicable toxicity data					
Sodium bicarbonate						
	LD50 Oral	Rat	4,220 mg/kg	-		
Remarks - Inhalation:	No applicable toxi	city data				
Remarks - Dermal:	No applicable toxicity data					
Calcium oxide						
Remarks - Oral:	No applicable toxi	city data				
Remarks - Inhalation:	No applicable toxi	No applicable toxicity data				
Remarks - Dermal:	No applicable toxi	city data				

Conclusion/Summary

: Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Sodium bicarbonate	Eyes - Mild	Rabbit		0.008 hrs	-
	irritant				
	Skin - Mild	Human		72 hrs	-
	irritant				
Conclusion/Summary					
Skin		ixture.Not full	•		
Eyes		ixture.Not full			
Respiratory	: M	ixture.Not full	ly tested.		
Sensitization					
Conclusion/Summary					
Skin		ixture.Not full	•		
Respiratory	: M	ixture.Not full	ly tested.		
<u>Mutagenicity</u>					
Conclusion/Summary	: M	ixture.Not full	ly tested.		
Carcinogenicity					
Conclusion/Summary	: M	ixture.Not full	ly tested.		
Classification					
Product/ingredient	OSHA	IARC	NTP		
name					
Quartz		1	Known	to be a human carc	cinogen.

Reproductive toxicity

FA-96

Version Number 1.0 Revision Date 01/17/2018 Page 11 of 18 Print Date 01/18/2018

One

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary

Mixture.Not fully tested.

:

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Calcium oxide	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category		Route of exposure	Target organs			
Quartz	Category 1						
Aspiration hazard							
Not available.							
Information on likely route	s of 🛛 :	Not available	2.				
exposure							
Potential acute health effect	te						
i otentiar actate neurin ente							
Eye contact	:		us eye damage.				
Inhalation	:	: No known significant effects or critical hazards.					
Skin contact	:	: No known significant effects or critical hazards.					
Ingestion	: No known significant effects or critical hazards.						
Symptoms related to the ph	vsical chemi	cal and toxico	logical characteristics				
Symptoms related to the ph	ysical, chemio	cal and toxico	logical characteristics				
<u>Symptoms related to the ph</u> Eye contact	ysical, chemio		logical characteristics				
		Adverse sym pain watering					
Eye contact	:	Adverse sym pain watering redness	ptoms may include the				
Eye contact Inhalation		Adverse sym pain watering redness No specific d	ptoms may include the ata.	following:			
Eye contact	:	Adverse sym pain watering redness No specific d Adverse sym	ptoms may include the ata. ptoms may include the	following:			
Eye contact Inhalation	:	Adverse sym pain watering redness No specific d Adverse sym pain or irritat	ptoms may include the ata. ptoms may include the	following:			
Eye contact Inhalation	:	Adverse sym pain watering redness No specific d Adverse sym pain or irritat redness	ptoms may include the ata. ptoms may include the ion	following:			
Inhalation	:	Adverse sym pain watering redness No specific d Adverse sym pain or irritat redness blistering ma	ptoms may include the ata. ptoms may include the ion	following: following:			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

FA-96

Version Number 1.0 Revision Date 01/17/2018

<u>PolyOne</u>

Page 12 of 18 Print Date 01/18/2018

Short term exposure

Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	No known significant effects or critical hazards.
Developmental effects	:	No known significant effects or critical hazards.
Fertility effects	:	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	107,917.3 mg/kg

Section 12. Ecological information

Toxicity

Result	Species	Exposure
No applicable toxicity data		
No applicable toxicity data		
No applicable toxicity data		
No applicable toxicity data		
No applicable toxicity data		
	No applicable toxicity data No applicable toxicity data No applicable toxicity data No applicable toxicity data	No applicable toxicity data No applicable toxicity data No applicable toxicity data No applicable toxicity data



Version Number 1.0 Revision Date 01/17/2018 Page 13 of 18 Print Date 01/18/2018

<u>PolyOne</u>

Sodium bicarbonate				
	Acute LC50 7,550 Mg/l Fresh	Fish - Fish	96 h	
	water			
Remarks - Acute - Fish:	Acute			
	Acute LC50 767.87 Mg/l Marine	Aquatic invertebrates.	48 h	
	water	Crustaceans		
Remarks - Acute - Aquatic	Acute			
invertebrates.:				
	Acute EC50 650 Mg/l Fresh water	Aquatic plants - Algae	96 h	
Remarks - Acute - Aquatic	Acute			
plants:				
Remarks - Chronic - Fish:	No applicable toxicity data			
	Chronic NOEC 576 Mg/l Fresh	Aquatic invertebrates.	21 d	
	water	Daphnia		
Remarks - Chronic -	Chronic			
Aquatic invertebrates.:				
Calcium oxide				
Remarks - Acute - Fish:	No applicable toxicity data			
Remarks - Acute - Aquatic	No applicable toxicity data			
invertebrates.:				
Remarks - Acute - Aquatic	No applicable toxicity data			
plants:				
	Chronic NOEC 100 Mg/l Fresh	Fish - Fish	46 d	
	water			
Remarks - Chronic - Fish:	Chronic			
Remarks - Chronic -	No applicable toxicity data			
Aquatic invertebrates.:				
FA-96				
Remarks - Acute - Aquatic	Dangerous for the environment: May	cause long term adverse e	ffects in the aquatic	
invertebrates.:	environment.			
Conclusion/Summary		onment: May cause long te	rm adverse effects	
	in the aquatic environme	ent.		
Persistence and degradability	<u>v</u>			
	Niet and lable			
Conclusion/Summary	: Not available.			
Conclusion/Summary	Dencency for the envir	onment: May cause long te	rm adverse offects	
Conclusion/Summary			LUL AUVELNE ELLECIN	
	in the aquatic environme			

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential

FA-96

Version Number 1.0 Revision Date 01/17/2018

<u>PolyOne</u>

Page 14 of 18 Print Date 01/18/2018

Calcium oxide	-		2.34	low
<u>Mobility in soil</u>				
Soil/water partition coefficient (KOC)	:	Not available.		

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods The generation of waste should be avoided or minimized wherever : possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	:	Not regulated for transportation.
International Air ICAO/IATA	:	Not classified as dangerous goods under transport regulations.
International Water IMO/IMDG	:	Not classified as dangerous goods under transport regulations.

FA-96

Version Number 1.0 Revision Date 01/17/2018

<u>PolyOne</u>

Page 15 of 18 Print Date 01/18/2018

Section 15. Regulatory information

U.S. Federal regulations	:	United States - TSCA 12(b) - Chemical export notification: None of the components are listed. United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not listed United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed United States - TSCA 8(d) - Health and safety studies: Not listed
		United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Zinc oxide United States - EPA Clean water act (CWA) section 311 - Hazardous substances: Listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	:	Not listed
Clean Air Act Section 602 Class I Substances	:	Not listed
Clean Air Act Section 602 Class II Substances	:	Not listed
DEA List I Chemicals (Precursor Chemicals)	:	Not listed
DEA List II Chemicals (Essential	:	Not listed

FA-96

Version Number 1.0 Revision Date 01/17/2018

Page 16 of 18 Print Date 01/18/2018

Chemicals)

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification

: Immediate (acute) health hazard

Composition/information on ingredients

Name	%	Classification
Quartz	0.3 - 1	СН
Sodium bicarbonate	3 - 5	AH
Calcium oxide	5 - 10	AH

SARA 313 Not applicable.

State regulations		
Massachusetts	:	None of the components are listed.
New York	:	None of the components are listed.
New Jersey	:	The following components are listed: Quartz Calcium oxide
Pennsylvania	:	The following components are listed: Quartz
		Calcium oxide
<u>California Prop. 65</u> WARNING: This product contains a c	hemi	ical known to the State of California to cause cancer.
United States inventory (TSCA 8b)	:	All components are listed or exempted.
Canada inventory	:	All components are listed or exempted.
International regulations		
Inventory list		
Australia	:	All components are listed or exempted.
Canada	:	All components are listed or exempted.
		16/18



FA-96

Po	lyOne.	

Version Number 1.0 Revision Date 01/17/2018

Page 17 of 18 Print Date 01/18/2018

:	All components are listed or exempted.
:	All components are listed or exempted.
:	All components are listed or exempted.
:	All components are listed or exempted.
:	All components are listed or exempted.
:	All components are listed or exempted.
:	Not determined.
:	Not determined.
:	All components are listed or exempted.
	:

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	3
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

HISTOLY		
Date of printing	:	01/18/2018
Date of issue/Date of revision	:	01/17/2018
Date of previous issue	:	00/00/0000
Version	:	1.0
Key to abbreviations	:	ATE = Acute Toxicity Estimate
·		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From
		Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)
		$\hat{U}N = United Nations$
References	:	Not available.

17/18

FA-96

Version Number 1.0 Revision Date 01/17/2018

ne

Page 18 of 18 Print Date 01/18/2018

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.