### MATERIAL SAFETY DATA SHEET

### x150-258-083-2

Version Number 1.0 Revision Date 01/12/2005 Page 1 of 6 Print Date 11/16/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	x150-258-083-2
Product code	:	EM10007701
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

## 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Misc00039 - Miscellaneous Irritant	Not Available	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Eyes, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> <li>Avoid skin contact. Product contains unreacted organic peroxides which may cause mild skin irritation.</li> </ul>
Chronic exposure Medical Conditions Aggravated by Exposure:	<ul> <li>Refer to Section 11 for Toxicological Information.</li> <li>Individuals with chronic respiratory disorders (i.e. asthma, chronic bronchitis, etc.) may be adversely affected by any airborne contaminant.</li> </ul>



MATERIAL SAFETY DATA SHEET **x150-258-083-2** 

Version Number 1.0 Revision Date 01/12/2005 Page 2 of 6 Print Date 11/16/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not relevant</li> <li>Carbon dioxide blanket, water spray, dry powder, foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> </ul>
Unusual Fire/Explosion Hazards	<ul> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

PolvOne

MATERIAL SAFETY DATA SHEET

## x150-258-083-2

Version Number 1.0 Revision Date 01/12/2005 Page 3 of 6 Print Date 11/16/2011

and contamination. Keep in a dry, cool place. Keep away from heat. Excessive storage temperature and humidity can degrade product performance. Store below 149 °F (65 °C). Rotate stock. Product shelf life is normally 1 year maximum.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required when handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this material.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. During processing and cross-linking, product can give off by-products such as alcohols, acetophenone, alpha-methylstyrene, acetone, methane, and ethane. By-product vapors may be flammable. User must provide necessary precautions such as adequate ventilation to prevent accumulation and ignition of vapors. Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.
Exposure $limit(s)$		

Exposure limit(s)

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility

Pellets
NO PIGMENT
characteristic
Not determined
Not applicable
Insoluble

: Solid

- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH
- Not applicable
  Not determined
  Not established
  Not applicable
  Not applicable
  Not applicable
  Not applicable

#### **10. STABILITY AND REACTIVITY**

Stability

: Stable.



## MATERIAL SAFETY DATA SHEET **x150-258-083-2**

Version Number 1.0 Revision Date 01/12/2005 Page 4 of 6 Print Date 11/16/2011

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	strong acids, oxidizing agents, reducing agents
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Traces of alcohols, acetophenone, alpha-methylstyrene, acetone, methane, ethane, or other byproducts may be liberated during processing or decomposition.

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

## Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ		
	12. ECOLOGICA	L INFORMATION			
Persistence and degrada	ability : Not readily bio	degradable.			
Environmental Toxicity		<ul><li>Chemicals are not readily available as they are bound within the polymer matrix.</li><li>Chemicals are not readily available as they are bound within the polymer matrix.</li></ul>			
Bioaccumulation Poten					
Additional advice	: Not applicable				
	13. DISPOSAL C	CONSIDERATIONS			
Product	possible recycl generator of wa classification, t	ing is preferred to dispo			
Contaminated packagir	has the response	ibility for proper waste accordance with applic	The generator of waste materia classification, transportation able federal, state/provincial		
	14 TRANSPOR	T INFORMATION			

PolyOne.

# MATERIAL SAFETY DATA SHEET **x150-258-083-2**

sion Number 1.0		Page 5
ision Date 01/12/2005		Print Date 11/16/2
U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA (air)	:	Refer to specific regulation.
IMO / IMDG (maritime)	:	Refer to specific regulation.
	15	5. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 Ext Not applicable	rem	ely Hazardous Substance
SARA Title III Section 313 Tox	cic (	Chemicals:
Not applicable Canadian Regulations:		
National Pollutant Relea	se Iı	nventory (NPRI)
Not applicable		
WHMIS Classification	:	Not controlled.
DSL	:	DSL status has not been determined. Quantity use in Canada may be restricted by regulations.
National Inventories:		
Australia AICS	:	Not determined
		Not determined
China IECS	:	Not determined

POLYONE	CORPORATION



## MATERIAL SAFETY DATA SHEET **x150-258-083-2**

Version Number 1.0 Revision Date 01/12/2005

Page 6 of 6 Print Date 11/16/2011

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

## **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.