MATERIAL SAFETY DATA SHEET

34-1520 Daytona Orange 5710 TF

Version Number 1.0 Revision Date 01/21/2005 Page 1 of 6 Print Date 11/17/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	34-1520 Daytona Orange 5710 TF
Product code	:	EM10007849
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Talc	14807-96-6	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Eyes, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. Avoid skin contact. Product contains unreacted organic peroxides which may cause mild skin irritation.
Chronic exposure Medical Conditions Aggravated by Exposure:	 Refer to Section 11 for Toxicological Information. Individuals with chronic respiratory disorders (i.e. asthma, chronic bronchitis, etc.) may be adversely affected by any airborne contaminant.

PolyOne

MATERIAL SAFETY DATA SHEET

34-1520 Daytona Orange 5710 TF

Version Number 1.0 Revision Date 01/21/2005 Page 2 of 6 Print Date 11/17/2011

		4. FIRST AID MEASURES	
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.	
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.	
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.	
		5. FIRE-FIGHTING MEASURES	
Flash point	:	Not applicable	
Flammable Limits			
Upper explosion limit	:	Not applicable	
Lower explosion limit	:	Not applicable	
Autoignition temperature	: Not relevant		
Suitable extinguishing media	:	Carbon dioxide blanket, water spray, dry powder, foam.	
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.	
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.	
	6. A(CCIDENTAL RELEASE MEASURES	
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.	
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.	
		7. HANDLING AND STORAGE	
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.	
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption	

2/6

PolyOne.

MATERIAL SAFETY DATA SHEET **34-1520 Daytona Orange 5710 TF**

Version Number 1.0 Revision Date 01/21/2005 Page 3 of 6 Print Date 11/17/2011

and contamination. Keep in a dry, cool place. Keep away from heat. Excessive storage temperature and humidity can degrade product performance. Store below 149 °F (65 °C). Rotate stock. Product shelf life is normally 1 year maximum.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required when handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this material.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. During processing and cross-linking, product can give off by-products such as alcohols, acetophenone, alpha-methylstyrene, acetone, methane, and ethane. By-product vapors may be flammable. User must provide necessary precautions such as adequate ventilation to prevent accumulation and ignition of vapors. Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.

Exposure limit(s)

Components	Value Exposure time			Exposure type Respirable fraction.		List:
Talc	2 mg/m3	2 mg/m3 Time Weighted Average (TWA):				. ACGIH
	9. PHYSIC	CAL AND CHEM	ICAL PROP	ERTIES		
Form	: Solid	1	Evaporat	tion rate	: N	ot applicable
Appearance	: Pelle	ts	Specific	Gravity:	: N	ot determined
Color	: ORANGE Bulk of		Bulk den	isity	: N	ot established
Odor	: characteristic Vapor		Vapor pr	ressure	: N	ot applicable
Melting point/range	: Not o	: Not determined Vapour			: N	ot applicable
Boiling Point:	: Not a	: Not applicable pH		•		ot applicable
Water solubility	: Insol	uble	-			**
U		11	pН		: N	ot applicab

PolyOne

MATERIAL SAFETY DATA SHEET **34-1520 Daytona Orange 5710 TF**

Version Number 1.0 Revision Date 01/21/2005

_

Page 4 of 6 Print Date 11/17/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: strong acids, oxidizing agents, reducing agents
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Traces of alcohols, acetophenone, alpha-methylstyrene, acetone, methane, ethane, or other byproducts may be liberated during processing or decomposition.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ		
14807-96-6	Talc	Systemic effects	Eyes, Respiratory system, Skin		
	12. ECOLOG	GICAL INFORMATION	N		
Persistence and degradat	oility : Not readily	y biodegradable.			
Environmental Toxicity	: Chemicals polymer m	-	as they are bound within the		
Bioaccumulation Potenti	al : Chemicals polymer m	-	as they are bound within the		
Additional advice	: Not applic	: Not applicable			
	13. DISPOSA	AL CONSIDERATIONS	8		
Product	possible re generator o classificati	cycling is preferred to dis			
Contaminated packaging	: Recycling	is preferred when possible	e. The generator of waste materia		

<u>PolyOne</u>.

MATERIAL SAFETY DATA SHEET

34-1520 Daytona Orange 5710 TF

Version Number 1.0 Revision Date 01/21/2005 Page 5 of 6 Print Date 11/17/2011

has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification	: Not regulated for transportation.			
ICAO/IATA (air)	: Refer to specific regulation.			
IMO / IMDG (maritime)	: Refer to specific regulation.			
	15. REGULATORY INFORMATION			
US Regulations:				
OSHA Status	: Classified as hazardous based on components.			
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.			
US. EPA CERCLA Hazardous S	Substances (40 CFR 302)			
Not applicable				
California Proposition 65	: WARNING! This product contains a chemical known to the State of California to cause cancer.			
SARA Title III Section 302 Extr Not applicable	emely Hazardous Substance			
SARA Title III Section 313 Tox	ic Chemicals:			
Not applicable Canadian Regulations:				
National Pollutant Releas	e Inventory (NPRI) CAS-No. Weight % NPRI ID#			
Zinc stearate	557-05-1 0.10 231			
WHMIS Classification : D2A WHMIS Ingredient Disclosure List				

PolyOne

MATERIAL SAFETY DATA SHEET 34-1520 Daytona Orange 5710 TF

Version Number 1.0 Revision Date 01/21/2005 Page 6 of 6 Print Date 11/17/2011

CAS-No. 14807-96-6		
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.