

**POLYONE CORPORATION****MATERIAL SAFETY DATA SHEET****EXP LST 615-2012-25**Version Number 1.1  
Revision Date 12/19/2006Page 1 of 7  
Print Date 11/25/2011**1. PRODUCT AND COMPANY IDENTIFICATION****POLYONE CORPORATION**  
33587 Walker Road, Avon Lake, OH 44012

Telephone : Product Stewardship (440) 930-1395  
Emergency telephone : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure number or accident).**

Product name : EXP LST 615-2012-25  
Product code : EM10008964  
Chemical Name : Mixture  
CAS-No. : Mixture  
Product Use : Industrial Applications

**2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS**

Components	CAS-No.	Weight %
Quartz	14808-60-7	0.1 - 1

**3. HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

**POTENTIAL HEALTH EFFECTS****Routes of Exposure:** : Inhalation, Ingestion, Eyes, Skin contact**Acute exposure**

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.  
Ingestion : May be harmful if swallowed.  
Eyes : Resin particles, like other inert materials, are mechanically irritating to eyes.  
Skin : Avoid skin contact. Product contains unreacted organic peroxides which may cause mild skin irritation.

**Chronic exposure** : Refer to Section 11 for Toxicological Information.**Medical Conditions Aggravated by Exposure:** : Individuals with chronic respiratory disorders (i.e. asthma, chronic bronchitis, etc.) may be adversely affected by any airborne contaminant.

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**EXP LST 615-2012-25**

Version Number 1.1  
Revision Date 12/19/2006

Page 2 of 7  
Print Date 11/25/2011

**4. FIRST AID MEASURES**

- Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
- Ingestion : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
- Eyes : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
- Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

**5. FIRE-FIGHTING MEASURES**

- Flash point : Not applicable
- Flammable Limits
  - Upper explosion limit : Not applicable
  - Lower explosion limit : Not applicable
- Autoignition temperature : Not relevant
- Suitable extinguishing media : Carbon dioxide blanket, water spray, dry powder, foam.
- Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
- Unusual Fire/Explosion Hazards : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), other hazardous materials, and smoke are all possible.

**6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
- Environmental precautions : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
- Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

**7. HANDLING AND STORAGE**

- Handling : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
- Storage : Keep containers dry and tightly closed to avoid moisture absorption

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**EXP LST 615-2012-25**

Version Number 1.1  
Revision Date 12/19/2006

Page 3 of 7  
Print Date 11/25/2011

and contamination. Keep in a dry, cool place. Keep away from heat. Excessive storage temperature and humidity can degrade product performance. Store below 149 °F (65 °C). Rotate stock. Product shelf life is normally 1 year maximum.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

- Respiratory protection : No personal respiratory protective equipment normally required when handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this material.
- Eye/Face Protection : Safety glasses with side-shields.
- Hand protection : Protective gloves.
- Skin and body protection : Long sleeved clothing.
- Additional Protective Measures : Safety shoes.
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
- Engineering measures : Heat only in areas with appropriate exhaust ventilation. During processing and cross-linking, product can give off by-products such as alcohols, acetophenone, alpha-methylstyrene, acetone, methane, and ethane. By-product vapors may be flammable. User must provide necessary precautions such as adequate ventilation to prevent accumulation and ignition of vapors. Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Quartz	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	0.1 mg/m3	Time Weighted Average (TWA):	Respirable.	Z3
	0.3 mg/m3	Time Weighted Average (TWA):	Total dust.	Z3
	0.1 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.025 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**EXP LST 615-2012-25**

Version Number 1.1  
Revision Date 12/19/2006

Page 4 of 7  
Print Date 11/25/2011

Form	: Solid	Evaporation rate	: Not applicable
Appearance	: Pellets	Specific Gravity:	: Not determined
Color	: NO PIGMENT	Bulk density	: Not established
Odor	: characteristic	Vapor pressure	: Not applicable
Melting point/range	: Not determined	Vapour density	: Not applicable
Boiling Point:	: Not applicable	pH	: Not applicable
Water solubility	: Insoluble		

**10. STABILITY AND REACTIVITY**

Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: strong acids, oxidizing agents, reducing agents
Hazardous decomposition products	: Carbon dioxide (CO <sub>2</sub> ), carbon monoxide (CO), oxides of nitrogen (NO <sub>x</sub> ), other hazardous materials, and smoke are all possible. Traces of alcohols, acetophenone, alpha-methylstyrene, acetone, methane, ethane, or other byproducts may be liberated during processing or decomposition.

**11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
14808-60-7	Quartz	no	1	no

IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**EXP LST 615-2012-25**

Version Number 1.1  
Revision Date 12/19/2006

Page 5 of 7  
Print Date 11/25/2011

2 - The component is reasonably anticipated to be a human carcinogen.

**Additional Health Hazard Information:**

**Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation. Long-term exposure may cause coughing, chest pain, diminished chest expansion and possibly silicosis, which is a scarring of the lungs.**

**12. ECOLOGICAL INFORMATION**

Persistence and degradability : Not readily biodegradable.  
Environmental Toxicity : Chemicals are not readily available as they are bound within the polymer matrix.  
Bioaccumulation Potential : Chemicals are not readily available as they are bound within the polymer matrix.  
Additional advice : Not applicable

**13. DISPOSAL CONSIDERATIONS**

Product : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.  
Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

**14. TRANSPORT INFORMATION**

U.S. DOT Classification : Not regulated for transportation.  
ICAO/IATA (air) : Refer to specific regulation.  
IMO / IMDG (maritime) : Refer to specific regulation.

**15. REGULATORY INFORMATION**

US Regulations:

OSHA Status : Classified as hazardous based on components.  
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**EXP LST 615-2012-25**

Version Number 1.1  
Revision Date 12/19/2006

Page 6 of 7  
Print Date 11/25/2011

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition : WARNING! This product contains a chemical known to the State of  
65 California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Not applicable

WHMIS Classification : D2A

DSL : All components of this product are on the Canadian Domestic  
Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Listed

China IECS : Listed

Europe EINECS : Listed

Japan ENCS : Not determined

Korea KECI : Listed

Philippines PICCS : Not determined

**16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The



**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**EXP LST 615-2012-25**

Version Number 1.1

Revision Date 12/19/2006

Page 7 of 7

Print Date 11/25/2011

information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.