



# POLYONE CORPORATION

## MATERIAL SAFETY DATA SHEET

### 3-E-6-S VULTEX

Version Number 1.3  
Revision Date 10/09/2013

Page 1 of 9  
Print Date 10/9/2013

#### 1. PRODUCT AND COMPANY IDENTIFICATION

**POLYONE CORPORATION**  
8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone : 1 (440) 930-1000 or 1 (866) POLYONE  
Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure  
number or accident).  
Product name : 3-E-6-S VULTEX  
Product code : FO00001056  
Chemical Name : Mixture  
CAS-No. : Mixture  
Product Use : Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Ethyl alcohol	64-17-5	0.1 - 1
Kaolin	1332-58-7	1 - 5
Zinc oxide	1314-13-2	1 - 5

#### 3. HAZARDS IDENTIFICATION

##### EMERGENCY OVERVIEW

This product is a water based mixture with an ammonia odor. The mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. The product is not combustible, but it will burn if involved in a fire, releasing hydrocarbon products of combustion. Inhalation of the ammonia from this product may cause respiratory irritation, coughing, sore throat, and labored breathing.

##### POTENTIAL HEALTH EFFECTS

**Routes of Exposure:** : Skin contact, Inhalation, Ingestion

##### Acute exposure

Inhalation : Symptoms of breathing ammonia vapor concentrated from this product may include laryngitis, tracheitis, pulmonary edema, dyspnea, bronchospasms, and chest pains or pneumonitis. Symptoms are typically reversible.  
Ingestion : May be harmful if swallowed.  
Eyes : Liquid, aerosol, or vapors of this product are irritating and may cause tearing, reddening, and swelling accompanied by a stinging sensation

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**3-E-6-S VULTEX**

Version Number 1.3  
Revision Date 10/09/2013

Page 2 of 9  
Print Date 10/9/2013

Skin : and/or a feeling like that of fine dust in the eyes.  
: Skin contact may cause redness, irritation, and burns.

**Chronic exposure** : Refer to Section 11 for Toxicological Information.

**Medical Conditions** : None known.  
**Aggravated by Exposure:**

**4. FIRST AID MEASURES**

Inhalation : Move to fresh air in case of accidental inhalation of vapors or fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Seek medical attention if necessary.

Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

**5. FIREFIGHTING MEASURES**

Flash point : no data available

Flammable Limits  
Upper explosion limit : no data available  
Lower explosion limit : no data available  
Auto-ignition temperature : no data available  
Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>), Water, Foam, Dry chemical.

Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.

Unusual Fire/Explosion Hazards : Burning dry latex produces dense black smoke with the possibility of toxic vapors. Residual latex material contained in empty drums may decompose when burned producing toxic or irritating fumes. Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), other hazardous materials, and smoke are all possible.

**6. ACCIDENTAL RELEASE MEASURES**

Personal precautions : Ensure response personnel are properly protected (see section 8 for respiratory or other protection guidelines.) Use caution as floors may

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**3-E-6-S VULTEX**

Version Number 1.3  
Revision Date 10/09/2013

Page 3 of 9  
Print Date 10/9/2013

be slippery.

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal.

**7. HANDLING AND STORAGE**

Handling : Use only in area provided with appropriate exhaust ventilation. Prolonged heating may result in product degradation. Material may settle during storage. Careful mixing without introduction of air may be necessary before use.

Storage : Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool place. Keep from freezing and temperature extremes.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Respiratory protection : A respirator is normally not required for routine handling of product in areas of good general ventilation and adequate local exhaust at processing equipment during routine operation. If using a cartridge respirator, an ammonia cartridge is required to filter out potential excess ammonia vapors.

Eye/Face Protection : Safety glasses with side-shields. Wear goggles or face shield during operations that present a splash potential.

Hand protection : Impervious gloves such as rubber or PVC

Skin and body protection : Long sleeved shirts and long pants are adequate for normal handling. Where operations present a splash or spill potential, employees should wear chemically resistant clothing, boots, apron, gloves, and eye/face protection.

Additional Protective Measures : Safety shoes

General Hygiene Considerations : Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practices.

Engineering measures : Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.



**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**3-E-6-S VULTEX**

Version Number 1.3  
Revision Date 10/09/2013

Page 4 of 9  
Print Date 10/9/2013

Exposure limit(s)

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**3-E-6-S VULTEX**

Version Number 1.3  
Revision Date 10/09/2013

Page 5 of 9  
Print Date 10/9/2013

Components	Value	Exposure time	Exposure type	List:
Kaolin	2 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Zinc oxide	2 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	10 mg/m3	Short Term Exposure Limit (STEL):	Respirable fraction.	ACGIH
	5 mg/m3	Recommended exposure limit (REL):	Fume.	NIOSH
	5 mg/m3	Recommended exposure limit (REL):	Dust.	NIOSH
	15 mg/m3	Ceiling Limit Value and Time Period (if specified):	Dust.	NIOSH
	10 mg/m3	Short Term Exposure Limit (STEL):	Fume.	NIOSH
	5 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	Fume.	OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Short Term Exposure Limit (STEL):	Fume.	OSHA Z1A
	5 mg/m3	Time Weighted Average (TWA):	Fume.	MX OEL
	10 mg/m3	Time Weighted Average (TWA):	Dust.	MX OEL
10 mg/m3	Short Term Exposure Limit (STEL):	Fume.	MX OEL	
Ethyl alcohol	1,000 ppm 1,900 mg/m3	PEL:		OSHA Z1
	1,000 ppm 1,900 mg/m3	Time Weighted Average (TWA):		MX OEL
	1,000 ppm	Short Term Exposure Limit (STEL):		ACGIH

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**3-E-6-S VULTEX**

Version Number 1.3

Page 6 of 9

Revision Date 10/09/2013

Print Date 10/9/2013

Form	: liquid	Evaporation rate	: Slower than Butyl Acetate
Appearance	: liquid	Specific Gravity	: Not determined
Colour	: NO PIGMENT	Bulk density	: Not applicable
Odour	: Slight ammonia	Vapour pressure	: Not established
Melting point/range	: not applicable	Vapour density	: Heavier than air.
Boiling Point:	: Not established	pH	: Not determined
Water solubility	: completely miscible		

**10. STABILITY AND REACTIVITY**

Stability	: The product is stable if stored and handled as prescribed.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Extremes of temperature and direct sunlight. Keep from freezing.
Incompatible Materials	: Acids, metal salts, and solvents
Hazardous decomposition products	: Carbon dioxide (CO <sub>2</sub> ), carbon monoxide (CO), oxides of nitrogen (NO <sub>x</sub> ), other hazardous materials, and smoke are all possible.

**11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
64-17-5	Ethyl alcohol	Systemic effects	Liver, heart or circulatory system, central nervous system (CNS), reproductive system.
1332-58-7	Kaolin	Systemic effects	Respiratory system, digestive system.
1314-13-2	Zinc oxide	Systemic effects	Respiratory system.

**LC50 / LD50**

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
64-17-5	Ethyl alcohol	LC50	20000 ppm	rat
		LC50		rat
		Oral	3,450 mg/kg	mouse
		LD50		
1332-58-7	Kaolin	Oral LD50	5,000 mg/kg	rat
		Dermal LD50	5,000 mg/kg	rat

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**3-E-6-S VULTEX**

Version Number 1.3  
Revision Date 10/09/2013

Page 7 of 9  
Print Date 10/9/2013

1314-13-2	Zinc oxide	LC50	2500 mg/m3	mouse
		LC50		mouse
		Oral LD50	7,950 mg/kg	mouse

**Carcinogenicity**

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
---------	---------------	------	------	-----

**IARC Carcinogen Classifications:**

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

**NTP Carcinogen Classifications:**

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

**12. ECOLOGICAL INFORMATION**

- Persistence and degradability : no data available
- Environmental Toxicity : no data available
- Bioaccumulation Potential : no data available
- Additional advice : no data available

**13. DISPOSAL CONSIDERATIONS**

- Product : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
- Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

**14. TRANSPORT INFORMATION**

- U.S. DOT Classification : Refer to specific regulation.
- ICAO/IATA : Refer to specific regulation.
- IMO/IMDG (maritime) : Refer to specific regulation.

**15. REGULATORY INFORMATION**



**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**3-E-6-S VULTEX**

Version Number 1.3  
Revision Date 10/09/2013

Page 8 of 9  
Print Date 10/9/2013

US Regulations:

- OSHA Status : Classified as hazardous based on components.
- TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition : Not applicable  
65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent
ZINC COMPOUNDS	1314-13-2	1.00 - 5.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight percent	NPRI ID#
Zinc oxide	1314-13-2	1.00 - 5.00	

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
1314-13-2
64-17-5

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.



**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**3-E-6-S VULTEX**

Version Number 1.3  
Revision Date 10/09/2013

Page 9 of 9  
Print Date 10/9/2013

National Inventories:

Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

**16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.