

MATERIAL SAFETY DATA SHEET

99100MB CELOGEN OT MB (50%)

 Version Number 1.1
 Page 1 of 6

 Revision Date 03/01/2005
 Print Date 11/17/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION

8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone : Product Stewardship (770) 590-3500 x.3563

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : 99100MB CELOGEN OT MB (50%)

Product code : FO000027 Chemical Name : Mixture CAS-No. : Mixture

Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	1 - 5
Diphenyloxide-4,4'-disulfohydrazide	80-51-3	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

May release high amount of nitrogen if inadvertenly heated above 50°C (122°F) or stored incorrectly. Pressure inside the container can increase and cause its rupture. This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Eyes, Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation : At process temperatures, product emissions may cause irritation.

Ingestion : May be harmful if swallowed. Eyes : May cause eye/skin irritation.

Skin : Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure : Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

99100MB CELOGEN OT MB (50%)

Version Number 1.1 Page 2 of 6 Revision Date 03/01/2005 Print Date 11/17/2011

Medical Conditions Aggravated by Exposure: : None known.

4. FIRST AID MEASURES

Inhalation Remove to fresh air. If breathing is irregular or stopped, administer

artificial respiration. When symptoms persist or in all cases of doubt

seek medical advice.

Ingestion Do not induce vomiting without medical advice. When symptoms

persist or in all cases of doubt seek medical advice.

Eyes Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. If eye irritation persists, seek medical attention.

Skin Wash off with soap and plenty of water.

5. FIRE-FIGHTING MEASURES

Flash point Greater than 200 °F (93 °C)

Flammable Limits

Upper explosion limit No data available Lower explosion limit No data available Autoignition temperature No data available Suitable extinguishing media waterfoam.

Special Fire Fighting

Procedures

: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Cool closed containers exposed to fire with water spray. If inadvertent heating of product results in smoke production, spray immediately and thoroughly with water. May release high amount of nitrogen if inadvertenly heated above 50°C (122°F) or stored incorrectly. Pressure inside the container can increase and cause its

rupture.

Unusual Fire/Explosion

Hazards

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May release high amount of nitrogen if inadvertenly heated above 50°C (122°F) or stored incorrectly. Pressure inside the container can increase and cause its rupture.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up Contain and collect spillage with non-combustible absorbent material,



MATERIAL SAFETY DATA SHEET

99100MB CELOGEN OT MB (50%)

Version Number 1.1 Page 3 of 6 Revision Date 03/01/2005 Print Date 11/17/2011

> (e.g. sand, earth, diatomaceus earth, vermiculite) and place in container for disposal according to local / national regulations (see

section 13).

7. HANDLING AND STORAGE

Handling Wear personal protective equipment. Take measures to prevent the

build up of electrostatic charge. Provide for appropriate exhaust

ventilation and dust collection at machinery.

Storage Keep away from open flames, hot surfaces and sources of ignition.

> Keep away from direct sunlight. Keep in a dry, cool place. May release high amount of nitrogen if inadvertenly heated above 50°C (122°F) or stored incorrectly. Pressure inside the container can

increase and cause its rupture.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection : When workers are facing concentrations above the exposure limit they

> must use appropriate certified respirators. Employees using respirators must be properly trained. Employers must follow applicable regulations such as OSHA 29 CFR 1910.134.

Eye/Face Protection : Safety glasses with side-shields.

Hand protection : Protective gloves.

Skin and body protection Long sleeved shirts and long pants are adequate for normal handling.

> Where operations present a splash or spill potential, employees should wear chemically resistant clothing, boots, apron, gloves, and eye/face

protection.

Additional Protective

Measures

When using, do not eat, drink or smoke.

General Hygiene

Considerations

: Do not breathe dust or spray mist. Handle in accordance with good

industrial hygiene and safety practices.

Engineering measures : Adequate ventilation and/or appropriate respiratory protection may

also be necessary to minimize employee exposure to processing

vapors.

Exposure limit(s)



MATERIAL SAFETY DATA SHEET

99100MB CELOGEN OT MB (50%)

 Version Number 1.1
 Page 4 of 6

 Revision Date 03/01/2005
 Print Date 11/17/2011

Components	Value	Exposure time	Exposure type	List:
Diphenyloxide-4,4'-dis	0.1 mg/m3	Time Weighted Average	Inhalable fraction.	ACGIH
ulfohydrazide		(TWA):		
Petroleum distillates,	500 ppm	PEL:	Vapor.	OSHA Z1
hydrotreated heavy	2,000			
naphthenic	mg/m3			

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : liquid Evaporation rate Not applicable Appearance Viscous liquid dispersion Specific Gravity: Not determined Color YELLOW Bulk density Not established Odor : Very faint Vapor pressure : Not determined Melting point/range : Not applicable Vapour density : Not determined : Not determined Boiling Point: : Not applicable pН

Water solubility : Negligible

10. STABILITY AND REACTIVITY

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : Heat, flames and sparks.

Incompatible Materials : Reacts with water or acids to form carbon dioxide (CO2)

Hazardous decomposition

products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

(NOx), other hazardous materials, and smoke are all possible.

Ammonia May release high amount of nitrogen if inadvertenly heated

above $50^{\circ}\text{C}\ (122^{\circ}\text{F})$ or stored incorrectly. Pressure inside the

container can increase and cause its rupture.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ	
64742-52-5	Petroleum distillates,	Irritant	Eyes, Skin.	
	hydrotreated heavy			
	naphthenic			
80-51-3	Diphenyloxide-4,4'-disulfo	Irritant	Eyes, Skin.	
	hydrazide			

12. ECOLOGICAL INFORMATION



MATERIAL SAFETY DATA SHEET

99100MB CELOGEN OT MB (50%)

 Version Number 1.1
 Page 5 of 6

 Revision Date 03/01/2005
 Print Date 11/17/2011

Persistence and degradability : No data available

Environmental Toxicity : No data available

Bioaccumulation Potential : No data available

Additional advice : No data available

13. DISPOSAL CONSIDERATIONS

Product : The generator of waste material has the responsibility for proper waste

classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material

has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial

and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Refer to specific regulation.

ICAO/IATA (air) : Refer to specific regulation.

IMO / IMDG (maritime) : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the TSCA

Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition : This product does not contain a substance listed by California Prop 65.

65

SARA Title III Section 302 Extremely Hazardous Substance Not applicable



MATERIAL SAFETY DATA SHEET

99100MB CELOGEN OT MB (50%)

 Version Number 1.1
 Page 6 of 6

 Revision Date 03/01/2005
 Print Date 11/17/2011

SARA Title III Section 313 Toxic Chemicals:

Not applicable Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Not applicable

WHMIS Classification : D2B

DSL : All components of this product are on the Canadian Domestic

Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Not determined

China IECS : Not determined

Europe EINECS : Listed

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.