## MATERIAL SAFETY DATA SHEET

## DB1541B BLACK

Version Number 1.2 Revision Date 05/10/2005 Page 1 of 6 Print Date 11/18/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DB1541B BLACK
Product code	:	FO00003548
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Petroleum distillates, hydrotreated light	64742-53-6	1 - 5
naphthenic		

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

### POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Skin contact, Ingestion		
Acute exposure		
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.	
Ingestion	: May be harmful if swallowed.	
Eyes	: May cause eye/skin irritation.	
Skin	: Experience shows no unusual dermatitis hazard from routine handling.	
Chronic exposure	: Refer to Section 11 for Toxicological Information.	
Medical Conditions Aggravated by Exposure:	: None known.	



## MATERIAL SAFETY DATA SHEET **DB1541B BLACK**

Version Number 1.2 Revision Date 05/10/2005 Page 2 of 6 Print Date 11/18/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>No data available</li> <li>No data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



# MATERIAL SAFETY DATA SHEET **DB1541B BLACK**

Storage <b>8. E</b> Respiratory protection Eye/Face Protection Hand protection Skin and body protection	Per acc : Ke and XPOSURE C : No : Sat : Pro	ne condensates may riodically clean hood sumulation of these r ep containers dry an d contamination. Sto <b>CONTROLS / PERS</b> personal respiratory fety glasses with side otective gloves.	ls, ducts, and o naterials. d tightly close ore in a cool d SONAL PRO	other surface ed to avoid n ry place. TECTION	es to min	nimize
8. E2 Respiratory protection Eye/Face Protection Hand protection	and XPOSURE C : No : Sat : Pro	l contamination. Sto CONTROLS / PERS personal respiratory fety glasses with side	ore in a cool d SONAL PRO	ry place. /TECTION		absorption
Respiratory protection Eye/Face Protection Hand protection	: No : Sat : Pro	personal respiratory	protective eq		mally re	
Eye/Face Protection Hand protection	: Sat : Pro	fety glasses with side		uipment nor	mally re	
Hand protection	: Pro		e-shields.			equired.
-		ptective gloves.				
Skin and hady protection	-	•				
Skill and body protection	: Lo	ng sleeved clothing.				
Additional Protective Measures	: Safety shoes.					
General Hygiene Considerations		ndle in accordance w ash hands before brea				fety practic
Engineering measures		at only in areas with propriate exhaust ver			lation. I	Provide
Exposure limit(s)	11	L		5		
Components	Value	Exposure time	e	Exposure ty	pe	List:
Petroleum distillates, hydrotreated light naphthenic	500 ppm 2,000 mg/m3	PEL:		Vapor.		OSHA Z
	9 PHYSIC	AL AND CHEMIC	AL PROPER	TIES		
						. 1 12 1 1
Form Appearance	: liquid	ıs, liquid	Evaporation Specific Gra			established letermined
Color	: BLAC	-	Bulk density			applicable
Odor	: Very f		Vapor press			determined
Melting point/range		plicable	Vapour den			letermined
Boiling Point:		plicable	pH	- 2		applicable
Water solubility	: Immiscible		I			11
	10. ST	ABILITY AND R	EACTIVITY			
Stability	: Sta	ble.				
Hazardous Polymerization	: Wi	ll not occur.				



### MATERIAL SAFETY DATA SHEET DB1541B BLACK

rsion Number 1.2 vision Date 05/10/2005	Page 4 c Print Date 11/18/20
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).
	11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
64742-53-6	Petroleum distillates, hydrotreated light	Irritant	Eyes, Skin.
	naphthenic		

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION

PolyOne.

## MATERIAL SAFETY DATA SHEET **DB1541B BLACK**

sion Number 1.2 ision Date 05/10/2005		Page 5 Print Date 11/18/2
U.S. DOT Classification	:	Refer to specific regulation.
ICAO/IATA (air)	:	Refer to specific regulation.
IMO / IMDG (maritime)	:	Refer to specific regulation.
	15	5. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	Not applicable
SARA Title III Section 302 E Not applicable	xtrem	ely Hazardous Substance
SARA Title III Section 313 T	oxic (	Chemicals:
Not applicable Canadian Regulations:		
National Pollutant Rele	ease I	nventory (NPRI)
Not applicable		
Not applicable WHMIS Classification	1 :	D2B
	1 : :	D2B All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
WHMIS Classification	1 : :	All components of this product are on the Canadian Domestic
WHMIS Classification	n : :	All components of this product are on the Canadian Domestic
WHMIS Classification DSL National Inventories:	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

POL VONE	CORPORATION
	COMUNATION



## MATERIAL SAFETY DATA SHEET **DB1541B BLACK**

Version Number 1.2 Revision Date 05/10/2005

Page 6 of 6 Print Date 11/18/2011

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.