MATERIAL SAFETY DATA SHEET 98880MX FLUORESCENT PINK

Version Number 1.1 Revision Date 01/28/2005 Page 1 of 7 Print Date 11/17/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:number		Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	98880MX FLUORESCENT PINK
Product code	:	FO00012390
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
1,2-Benzenedicarboxylic acid, butyl	85-68-7	1 - 5
phenylmethylester		
Zinc oxide	1314-13-2	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.		
Ingestion	: May be harmful if swallowed.		
Eyes	: May cause eye/skin irritation.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		

PolyOne

MATERIAL SAFETY DATA SHEET 98880MX FLUORESCENT PINK

Version Number 1.1 Revision Date 01/28/2005 Page 2 of 7 Print Date 11/17/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available Not applicable Carbon dioxide blanket, water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE

<u>PolyOne</u>.

MATERIAL SAFETY DATA SHEET 98880MX FLUORESCENT PINK

ersion Number 1.1	Page 3 of			
evision Date 01/28/2005	Print Date 11/17/201			
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.			
Storage	 accumulation of these materials. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place. 			
8. EXI	OSURE CONTROLS / PERSONAL PROTECTION			
Respiratory protection	: No personal respiratory protective equipment normally required.			
Eye/Face Protection	: Safety glasses with side-shields.			
Hand protection	: Protective gloves.			
Skin and body protection	: Long sleeved clothing.			
Additional Protective Measures	: Safety shoes.			
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Zinc oxide	10 mg/m3	Time Weighted Average	Total dust. as Zn	ACGIH
		(TWA):		
	5 mg/m3	PEL:	Respirable dust. as Zn	OSHA Z1
	15 mg/m3	PEL:	Total dust. as Zn	OSHA Z1
	2 mg/m3	Time Weighted Average	Respirable fraction.	ACGIH
		(TWA):		
	10 mg/m3	Short Term Exposure Limit	Respirable fraction.	ACGIH
		(STEL):		

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- liquid
 Viscous, liquid
 PINK
 Very faint
 Not applicable
 Not applicable
 Immiscible
- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH
- Not established
 Not determined
 Not applicable
 Not determined
 Not determined
 Not applicable

MATERIAL SAFETY DATA SHEET 98880MX FLUORESCENT PINK

Version Number 1.1 Revision Date 01/28/2005

_

Page 4 of 7 Print Date 11/17/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Irritant	Eyes, Skin.
		Systemic effects	Liver, reproductive system.
1314-13-2	Zinc oxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Oral LD50 Dermal LD50	2,330 mg/kg > 10 gm/kg	rat rabbit
1314-13-2	Zinc oxide	LC50 Oral LD50	2500 mg/m3 7,950 mg/kg	mouse mouse

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.

Environmental Toxicity

: Environmental toxicity has not been established for this mixture as a

PolyOne

MATERIAL SAFETY DATA SHEET 98880MX FLUORESCENT PINK

Version Number 1.1 Revision Date 01/28/2005 Page 5 of 7 Print Date 11/17/2011

Bioaccumulation Potential	accumulation Potential : No data available				
Additional advice	: No data available				
	13. DISPO	OSAL CONSIDERAT	IONS		
Product	generat classifi	tor of waste material has cation, transportation an	eferred to disposal or incineration. T s the responsibility for proper waste nd disposal in accordance with acial and local regulations.		
Contaminated packaging					
	14. TRA	NSPORT INFORMAT	ΓΙΟΝ		
U.S. DOT Classification	: Refer to	o specific regulation.			
ICAO/IATA (air)	: Refer to	o specific regulation.			
IMO / IMDG (maritime)	: Refer to	o specific regulation.			
	15. REGU	LATORY INFORMA	TION		
US Regulations:					
OSHA Status	: Classif	ied as hazardous based	on components.		
TSCA Status	: All con Invento		t are listed on or exempt from the TSC		
US. EPA CERCLA Hazardo	ous Substances (40 CFR 302)			
Chemical Name	CAS-No.	RQ for component	RQ for Mixture/Product		
1,2-Benzenedicarb oxylic acid, butyl phenylmethylester	85-68-7	100 lbs	2,275 LB		
California Propositio 65	Califor	mia to cause cancer., W	ntains a chemical known to the State of ARNING! This product contains a f California to cause birth defects or		

PolyOne.

MATERIAL SAFETY DATA SHEET 98880MX FLUORESCENT PINK

Version Number 1.1 Revision Date 01/28/2005 Page 6 of 7 Print Date 11/17/2011

other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
ZINC COMPOUNDS	1314-13-2	21.04
	73398-89-7	0.22

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
1-Methyl-2-pyrrolidone	872-50-4	0.36	164
Zinc oxide	1314-13-2	21.04	231
Xanthylium,	73398-89-7	0.22	231
3,6-bis(diethylamino)-9-[2-(methoxycarbonyl)phen			
yl]-, (T-4)-tetrachlorozincate(2-) (2:1)			
1,2-Benzenedicarboxylic acid, butyl	85-68-7	4.39	37
phenylmethylester			

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.	
1314-13-2	
85-68-7	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: L	isted	
China IECS	: L	Listed	
Europe EINECS	: L	Listed	
Japan ENCS	: N	Not determined	
Korea KECI	: L	Listed	
Philippines PICCS	: L	isted	

:

PolyOne

MATERIAL SAFETY DATA SHEET 98880MX FLUORESCENT PINK

Version Number 1.1 Revision Date 01/28/2005 Page 7 of 7 Print Date 11/17/2011

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.