

**POLYONE CORPORATION****MATERIAL SAFETY DATA SHEET****25200GNS CARAMEL**Version Number 1.5  
Revision Date 10/08/2009Page 1 of 8  
Print Date 1/9/2012**1. PRODUCT AND COMPANY IDENTIFICATION****POLYONE CORPORATION**  
**8155 Cobb Center Drive, Kennesaw, GA 30152**Telephone : Product Stewardship (770) 590-3500 x.3563  
Emergency telephone : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**Product name : 25200GNS CARAMEL  
Product code : FO00012942  
Chemical Name : Mixture  
CAS-No. : Mixture  
Product Use : Industrial Applications**2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS**

| Components        | CAS-No.    | Weight percent |
|-------------------|------------|----------------|
| Carbon black      | 1333-86-4  | 0.1 - 1        |
| Quartz            | 14808-60-7 | 0.1 - 1        |
| Titanium dioxide  | 13463-67-7 | 5 - 10         |
| Calcium carbonate | 1317-65-3  | 10 - 30        |

**3. HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

**POTENTIAL HEALTH EFFECTS****Routes of Exposure:** : Inhalation, Skin contact, Ingestion**Acute exposure**Inhalation : Inhalation of airborne droplets may cause irritation of the respiratory tract.  
Ingestion : May be harmful if swallowed.  
Eyes : May cause eye and skin irritation.  
Skin : Experience shows no unusual dermatitis hazard from routine handling.**Chronic exposure** : Refer to Section 11 for Toxicological Information.

**POLYONE CORPORATION****MATERIAL SAFETY DATA SHEET****25200GNS CARAMEL**Version Number 1.5  
Revision Date 10/08/2009Page 2 of 8  
Print Date 1/9/2012**Medical Conditions** : None known.  
**Aggravated by Exposure:****4. FIRST AID MEASURES**

Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

**5. FIRE-FIGHTING MEASURES**

Flash point : no data available

Flammable Limits  
Upper explosion limit : no data available  
Lower explosion limit : no data available

Autoignition temperature : Not applicable

Suitable extinguishing media : Carbon dioxide blanket, Water spray, Dry powder, Foam.

Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.

Unusual Fire/Explosion Hazards : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), other hazardous materials, and smoke are all possible.

**6. ACCIDENTAL RELEASE MEASURES**

Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**25200GNS CARAMEL**

Version Number 1.5  
Revision Date 10/08/2009

Page 3 of 8  
Print Date 1/9/2012

**7. HANDLING AND STORAGE**

- Handling : Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
- Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

- Respiratory protection : No personal respiratory protective equipment normally required.
- Eye/Face Protection : Safety glasses with side-shields
- Hand protection : Protective gloves
- Skin and body protection : Long sleeved clothing
- Additional Protective Measures : Safety shoes
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
- Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**25200GNS CAMEL**

Version Number 1.5  
Revision Date 10/08/2009

Page 4 of 8  
Print Date 1/9/2012

| Components        | Value     | Exposure time                     | Exposure type                | List:                |
|-------------------|-----------|-----------------------------------|------------------------------|----------------------|
| Calcium carbonate | 5 mg/m3   | PEL:                              | Respirable fraction.         | OSHA Z1              |
|                   | 15 mg/m3  | PEL:                              | Total dust.                  | OSHA Z1              |
|                   | 10 mg/m3  | Time Weighted Average (TWA):      |                              | MX OEL               |
|                   | 20 mg/m3  | Short Term Exposure Limit (STEL): |                              | MX OEL               |
| Carbon black      | 3.5 mg/m3 | Time Weighted Average (TWA):      |                              | ACGIH                |
|                   | 3.5 mg/m3 | Recommended exposure limit (REL): |                              | NIOSH                |
|                   | 0.1 mg/m3 | Recommended exposure limit (REL): |                              | NIOSH                |
|                   | 3.5 mg/m3 | PEL:                              |                              | OSHA Z1              |
|                   | 3.5 mg/m3 | Time Weighted Average (TWA):      |                              | OSHA Z1A             |
|                   | 3.5 mg/m3 | Time Weighted Average (TWA):      |                              | MX OEL               |
|                   | 7 mg/m3   | Short Term Exposure Limit (STEL): |                              | MX OEL               |
|                   | Quartz    | 0.025 mg/m3                       | Time Weighted Average (TWA): | Respirable fraction. |
| 0.05 mg/m3        |           | Recommended exposure limit (REL): | Respirable dust.             | NIOSH                |
| 0.1 mg/m3         |           | Time Weighted Average (TWA):      | Respirable dust.             | OSHA Z1A             |
| 0.1 mg/m3         |           | Time Weighted Average (TWA):      | Respirable.                  | Z3                   |
| 0.3 mg/m3         |           | Time Weighted Average (TWA):      | Total dust.                  | Z3                   |
| 0.1 mg/m3         |           | Time Weighted Average (TWA):      |                              | MX OEL               |
| Titanium dioxide  |           | 10 mg/m3                          | Time Weighted Average (TWA): |                      |
|                   | 15 mg/m3  | PEL:                              | Total dust.                  | OSHA Z1              |
|                   | 10 mg/m3  | Time Weighted Average (TWA):      | Total dust.                  | OSHA Z1A             |
|                   | 10 mg/m3  | Time Weighted Average (TWA):      | as Ti                        | MX OEL               |
|                   | 20 mg/m3  | Short Term Exposure Limit (STEL): | as Ti                        | MX OEL               |

**9. PHYSICAL AND CHEMICAL PROPERTIES**

|                     |                   |                  |                   |
|---------------------|-------------------|------------------|-------------------|
| Form                | : liquid          | Evaporation rate | : Not established |
| Appearance          | : viscous, liquid | Specific Gravity | : Not determined  |
| Colour              | : BROWN           | Bulk density     | : Not applicable  |
| Odour               | : very faint      | Vapour pressure  | : Not determined  |
| Melting point/range | : not applicable  | Vapour density   | : Not determined  |



**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**25200GNS CAMEL**

Version Number 1.5  
Revision Date 10/08/2009

Page 6 of 8  
Print Date 1/9/2012

|            |                  |    |    |    |
|------------|------------------|----|----|----|
| 1333-86-4  | Carbon black     | no | 2B | no |
| 14808-60-7 | Quartz           | no | 1  | no |
| 13463-67-7 | Titanium dioxide | no | 2B | no |

**IARC Carcinogen Classifications:**

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

**NTP Carcinogen Classifications:**

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

**Additional Health Hazard Information:**

**Carbon black 1333-86-4 Carcinogenicity:** Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

**Additional Health Hazard Information:**

**Quartz 14808-60-7** This material in its free releasable form may cause respiratory tract irritation. Long-term exposure may cause coughing, chest pain, diminished chest expansion and possibly silicosis, which is a scarring of the lungs.

**12. ECOLOGICAL INFORMATION**

- Persistence and degradability : Not readily biodegradable.
- Environmental Toxicity : Environmental toxicity has not been established for this mixture as a whole.
- Bioaccumulation Potential : no data available
- Additional advice : no data available

**13. DISPOSAL CONSIDERATIONS**

- Product : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
- Contaminated packaging : Recycling is preferred when possible. The generator of waste



**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**25200GNS CAMEL**

Version Number 1.5  
Revision Date 10/08/2009

Page 7 of 8  
Print Date 1/9/2012

material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

**14. TRANSPORT INFORMATION**

U.S. DOT Classification : Refer to specific regulation.  
ICAO/IATA : Refer to specific regulation.  
IMO / IMDG (maritime) : Refer to specific regulation.

**15. REGULATORY INFORMATION**

US Regulations:

OSHA Status : Classified as hazardous based on components.  
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition 65 : WARNING! This product contains a chemical known to the State of California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

not applicable

WHMIS Classification : D2A

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**25200GNS CAMEL**

Version Number 1.5  
Revision Date 10/08/2009

Page 8 of 8  
Print Date 1/9/2012

DSL : DSL status has not been determined. Quantity use in Canada may be restricted by regulations.

National Inventories:

Australia AICS : Not determined  
China IECS : Not determined  
Europe EINECS : Listed  
Japan ENCS : Not determined  
Korea KECI : Not determined  
Philippines PICCS : Not determined

**16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.