

SILCOCAT 1800

Version Number 1.3 Revision Date 03/31/2022 Page 1 of 16 Print Date 04/02/2022

SAFETY DATA SHEET

SILCOCAT 1800

Section 1. Identification

GHS product identifier : SILCOCAT 1800

Chemical name: MixtureCAS number: MixtureOther means of identification: FO00014248Product type: solid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : AVIENT CORPORATION

1675 Navarre Road SW, Massillon,

Ohio USA 44646

1 330 837 8679

Emergency telephone number (with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

: ORGANIC PEROXIDES - Type E SKIN IRRITATION - Category 2

EYE IRRITATION - Category 2B

GERM CELL MUTAGENICITY - Category 2

GHS label elements



SILCOCAT 1800

Version Number 1.3
Revision Date 03/31/2022

Page 2 of 16 Print Date 04/02/2022

Hazard pictograms



Signal word : Warning

Hazard statements : Heating may cause a fire.

Causes skin and eye irritation. Suspected of causing genetic defects.

Precautionary statements

: Not applicable.

Prevention : Obtain special instructions before use. Wear protective gloves. Wear

protective clothing. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from clothing and other combustible materials. Keep only in original packaging. Wash thoroughly after handling.

Response: IF exposed or concerned: Get medical advice or attention. Take off

contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or

attention.

Storage : Store at temperatures not exceeding @%1 °C/@%2 °F. Keep cool.

Store separately.

Disposal : Dispose of contents and container in accordance with all local,

regional, national and international regulations. None known.

Supplemental label elements

Hazards not otherwise classified : None known.

Not available.

Section 3. Composition/information on ingredients

Substance/mixture:MixtureChemical name:MixtureOther means of identification:FO00014248

CAS number/other identifiers

Ingredient name	%	CAS number
2,5-Dimethyl-2,5-di(tert-butylperoxy)hexane	>= 25 - <= 50	78-63-7



SILCOCAT 1800

 Version Number 1.3
 Page 3 of 16

 Revision Date 03/31/2022
 Print Date 04/02/2022

Silica, amorphous	>= 10 - <= 25	7631-86-9
Di-tert-butyl peroxide	>= 1 - <= 3	110-05-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie,

belt or waistband.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated

clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly

before reuse.

Ingestion: Wash out mouth with water. Remove dentures if any. Remove victim

to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing

such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects



Page 4 of 16

SILCOCAT 1800

Version Number 1.3 Print Date 04/02/2022 Revision Date 03/31/2022

Eye contact Causes eye irritation.

No known significant effects or critical hazards. Inhalation

Skin contact Causes skin irritation.

Ingestion No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation No specific data.

Adverse symptoms may include the following: Skin contact

> irritation redness

No specific data. **Ingestion**

Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically. Contact poison treatment specialist Notes to physician

immediately if large quantities have been ingested or inhaled.

No specific treatment. **Specific treatments**

No action shall be taken involving any personal risk or without **Protection of first-aiders**

suitable training. It may be dangerous to the person providing aid to

give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or CO₂.

None known.

Specific hazards arising from the chemical

Runoff to sewer may create fire or explosion hazard. This material increases the risk of fire and may aid combustion. Heating may cause a fire. May re-ignite itself after fire is extinguished. Hazardous

decomposition may occur.

Hazardous thermal decomposition products Decomposition products may include the following materials:

carbon dioxide carbon monoxide metal oxide/oxides



SILCOCAT 1800

Version Number 1.3 Revision Date 03/31/2022 Page 5 of 16 Print Date 04/02/2022

Special protective actions for firefighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal

protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note

of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

Methods and materials for containment and cleaning up

Small spill : Move containers from spill area. Use spark-proof tools and explosion-

proof equipment. Avoid contamination with reactive substances. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste

container. Dispose of via a licensed waste disposal contractor.

Large spill : Move containers from spill area. Use spark-proof tools and explosion-

proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid contamination with reactive substances. Avoid dust generation. Do not

dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact

information and Section 13 for waste disposal.

Section 7. Handling and storage



SILCOCAT 1800

Version Number 1.3 Revision Date 03/31/2022 Page 6 of 16 Print Date 04/02/2022

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Use only with adequate ventilation. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Keep away from clothing, incompatible materials and combustible materials. Temperature control may be required. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

To avoid the risk of formation of shock-sensitive crystals or loss of stability, it is important to store the product within the recommended temperature range. Temperature control may be required. Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store at temperatures not exceeding 38°C/100°F. Store in a well-ventilated place. Separate from reducing agents and combustible materials. Keep container tightly closed and sealed until ready for use. Prevent product contamination. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
2,5-Dimethyl-2,5-di(tert-	None.



SILCOCAT 1800

Version Number 1.3 Revision Date 03/31/2022 Page 7 of 16 Print Date 04/02/2022

butylperoxy)hexane		
Silica, amorphous	NIOSH REL (1994-06-01) TWA 6 mg/m3	
Di-tert-butyl peroxide	None.	

Appropriate engineering controls

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. Use with adequate ventilation.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.



SILCOCAT 1800

Version Number 1.3 Page 8 of 16 Print Date 04/02/2022 Revision Date 03/31/2022

Body protection Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Appropriate footwear and any additional skin protection measures Other skin protection

> should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

Respiratory protection Based on the hazard and potential for exposure, select a respirator that

meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state solid [Paste.] NO PIGMENT Color Odor Not available. **Odor threshold** Not available. Not available. рH **Melting point** Not available. **Boiling point** Not available. Flash point Not available. **Burning time** Not available. **Burning** rate Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available.

Lower and upper explosive Lower: Not available. (flammable) limits **Upper:** Not available.

Vapor pressure Not available. Not available. Vapor density Relative density Not available. **Solubility** Not available. Solubility in water Not available. Partition coefficient: n-Not available.

octanol/water

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Not available. **SADT**

Dynamic: Not available. Viscosity

Kinematic: Not available.

Aerosol product

Heat of combustion Not available.



SILCOCAT 1800

Version Number 1.3 Revision Date 03/31/2022

Page 9 of 16 Print Date 04/02/2022

Ignition distance Enclosed space ignition - Time

equivalent

Enclosed space ignition -

Deflagration density

Flame height

Not available. Flame duration Not available.

Section 10. Stability and reactivity

This product, in laboratory testing, neither detonates nor deflagrates Reactivity

and only shows low or no effect when heated under confinement.

Chemical stability Stable under recommended storage and handling conditions (see

Section 7).

Not available.

Not available.

Not available.

Possibility of hazardous reactions Hazardous reactions or instability may occur under certain conditions

of storage or use. Conditions may include the following: temperature increase high temperature Reactions may include the following:

hazardous decomposition risk of causing fire

Conditions to avoid Avoid increased storage temperature.

Reactive or incompatible with the following materials: **Incompatible materials**

> combustible materials reducing materials

copper iron rust

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Peroxide, bis(1,1-dimethylethyl))			
	LD50 Oral	Rat	25,000 mg/kg	-

Conclusion/Summary Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Silica	Eyes - Mild irritant	Rabbit	1	24 hrs	-



SILCOCAT 1800

Version Number 1.3 Revision Date 03/31/2022 Page 10 of 16 Print Date 04/02/2022

Peroxide, bis(1,1-dimethylethyl)	Eyes - Mild irritant	Rabbit	-	0.017 hrs	-
	Eyes - Mild irritant	Rabbit	-	24 hrs	-

Conclusion/Summary

Skin: Mixture.Not fully tested.Eyes: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary: Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
Silica	-	3	-

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of :

Not available.

exposure



SILCOCAT 1800

 Version Number 1.3
 Page 11 of 16

 Revision Date 03/31/2022
 Print Date 04/02/2022

Potential acute health effects

Eye contact : Causes eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes skin irritation.

Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following: pain or irritation,

watering, redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following: irritation, redness

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary : Mixture.Not fully tested.

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : Suspected of causing genetic defects.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral	Dermal	Inhalation	Inhalation	Inhalation
			(gases)	(vapors)	(dusts and
					mists)



SILCOCAT 1800

Version Number 1.3 Revision Date 03/31/2022 Page 12 of 16 Print Date 04/02/2022

SILCOCAT 1800	25,000 mg/kg	N/A	N/A	N/A	N/A
Peroxide, bis(1,1-dimethylethyl)	25,000 mg/kg	N/A	N/A	N/A	N/A

Other information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Section 12. Ecological information

Toxicity

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Peroxide, 1,1'-(1,1,4,4-tetramethyl-	7.34	839.00	high
1,4-butanediyl)bis[2-(1,1-			
dimethylethyl)			
Peroxide, bis(1,1-dimethylethyl)	3.2	-	low

Mobility in soil

Soil/water partition coefficient

(KOC)

Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever

possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental



SILCOCAT 1800

Version Number 1.3 Revision Date 03/31/2022 Page 13 of 16 Print Date 04/02/2022

protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR : UN3108, ORGANIC PEROXIDE TYPE E, SOLID (2,5-Dimethyl-

Ground/Air/Water 2,5-di-(tert-butylperoxy)hexane, as a paste ≤47%), 5.2

International Air : UN3108, ORGANIC PEROXIDE TYPE E, SOLID (2,5-Dimethyl-

ICAO/IATA 2,5-di-(tert-butylperoxy)hexane, as a paste ≤47%), 5.2

International Water : UN3108, ORGANIC PEROXIDE TYPE E, SOLID (2,5-Dimethyl-

IMO/IMDG 2,5-di-(tert-butylperoxy)hexane, as a paste \leq 47%), 5.2

Section 15. Regulatory information

U.S. Federal regulations : United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed
United States - TSCA 4(a) - ITC Priority list: Not listed
United States - TSCA 4(a) - Proposed test rules: Not listed
United States - TSCA 4(f) - Priority risk review: Not listed
United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - $TSCA\ 5(a)2$ - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed



SILCOCAT 1800

Version Number 1.3 Revision Date 03/31/2022 Page 14 of 16 Print Date 04/02/2022

United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined

United States - TSCA 8(a) - Preliminary assessment report (PAIR): Listed Poly(dimethylsiloxane)

United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Not listed

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

 $\label{thm:commerce-Precursor} \textbf{United States-Department of commerce-Precursor chemical:}$

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

Substances

Clean Air Act Section 602 Class II

Substances

DEA List I Chemicals (Precursor

Chemicals)

DEA List II Chemicals (Essential

Chemicals)

Not listed

Not listed

Not listed

Not listed

Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification : ORGANIC PEROXIDES - Type E

SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2B

GERM CELL MUTAGENICITY - Category 2

Composition/information on ingredients

Name	%	Classification
Peroxide, 1,1'-(1,1,4,4-	>= 25 - <= 50	ORGANIC PEROXIDES - Type C



SILCOCAT 1800

Version Number 1.3 Revision Date 03/31/2022 Page 15 of 16 Print Date 04/02/2022

tetramethyl-1,4- butanediyl)bis[2-(1,1- dimethylethyl)		SKIN IRRITATION - Category 2
Silica	>= 10 - <= 25	EYE IRRITATION - Category 2B
Peroxide, bis(1,1-dimethylethyl)	>= 1 - <= 3	FLAMMABLE LIQUIDS - Category 2 ORGANIC PEROXIDES - Type E EYE IRRITATION - Category 2B GERM CELL MUTAGENICITY - Category 2

Not applicable.

State regulations

Massachusetts: None of the components are listed.New York: None of the components are listed.New Jersey: The following components are listed:

Di-tert-butyl peroxide

Pennsylvania : The following components are listed:

Silica, amorphous

Di-tert-butyl peroxide

California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

United States inventory (TSCA 8b) : Not determined.

Canada inventory : Not determined.

International regulations

Inventory list

Australia Not determined. Not determined. Canada Not determined. China **Europe inventory** Not determined. Japan Not determined. **New Zealand** Not determined. **Philippines** Not determined. Republic of Korea Not determined. Taiwan Not determined. **Turkey** Not determined. **United States** Not determined.



SILCOCAT 1800

 Version Number 1.3
 Page 16 of 16

 Revision Date 03/31/2022
 Print Date 04/02/2022

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		0
Physical hazards		

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

Date of printing: 04/02/2022Date of issue/Date of revision: 03/31/2022Date of previous issue: 08/10/2016

Version : 1.3

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.