

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****WB-10514-C CEDAR ATH COATING**Version Number 1.6
Revision Date 03/12/2014Page 1 of 7
Print Date 3/18/2014**1. PRODUCT AND COMPANY IDENTIFICATION****POLYONE CORPORATION**
8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone : 1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure
number or accident).
Product name : WB-10514-C CEDAR ATH COATING
Product code : FO20005481
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

| Components | CAS-No. | Weight percent |
|------------------|------------|----------------|
| Iron oxide | 1309-37-1 | 1 - 5 |
| Titanium dioxide | 13463-67-7 | 1 - 5 |

3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. In addition, heating or processing this material may result in product degradation or byproduct formation creating additional hazards. See Sections 8 and 11 for additional details.

POTENTIAL HEALTH EFFECTS**Routes of Exposure:** : Skin contact, Inhalation, Ingestion**Acute exposure**

Inhalation : Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion : No known effects.
Eyes : Vapour during processing may be irritating to the respiratory tract and to the eyes.
Skin : May cause eye or skin irritation with susceptible persons.

Chronic exposure : Refer to Section 11 for Toxicological Information.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

WB-10514-C CEDAR ATH COATING

Version Number 1.6
Revision Date 03/12/2014

Page 2 of 7
Print Date 3/18/2014

Medical Conditions : None known.
Aggravated by Exposure:

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of vapors or fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.

Ingestion : Obtain medical attention. Never give anything by mouth to an unconscious person.

Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIREFIGHTING MEASURES

Flash point : Greater than 400 °F (204.4 °C)

Flammable Limits
Upper explosion limit : no data available
Lower explosion limit : no data available
Auto-ignition temperature : no data available
Suitable extinguishing media : Carbon dioxide (CO₂), Water, Foam, Dry chemical.

Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.

Unusual Fire/Explosion Hazards : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Ensure response personnel are properly protected (see section 8 for respiratory or other protection guidelines.) Use caution as floors may be slippery.

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

WB-10514-C CEDAR ATH COATING

Version Number 1.6
Revision Date 03/12/2014

Page 3 of 7
Print Date 3/18/2014

- Handling : Use only in area provided with appropriate exhaust ventilation. Prolonged heating may result in product degradation. Material may settle during storage. Careful mixing without introduction of air may be necessary before use.
- Storage : Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool place. Keep from freezing and temperature extremes.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Respiratory protection : A respirator is normally not required for routine handling of product in areas of good general ventilation and adequate local exhaust at processing equipment during routine operation.
- Eye/Face Protection : Safety glasses with side-shields. Wear goggles or face shield during operations that present a splash potential.
- Hand protection : Impervious gloves such as rubber or PVC
- Skin and body protection : Long sleeved shirts and long pants are adequate for normal handling. Where operations present a splash or spill potential, employees should wear chemically resistant clothing, boots, apron, gloves, and eye/face protection.
- Additional Protective Measures : Safety shoes
- General Hygiene Considerations : Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practices.
- Engineering measures : Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.

Exposure limit(s)

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

WB-10514-C CEDAR ATH COATING

Version Number 1.6
Revision Date 03/12/2014

Page 4 of 7
Print Date 3/18/2014

| Components | Value | Exposure time | Exposure type | List: |
|------------------|----------|-----------------------------------|----------------------|----------|
| Iron oxide | 10 mg/m3 | PEL: | Fume. | OSHA Z1 |
| | 5 mg/m3 | Time Weighted Average (TWA): | as Fe | MX OEL |
| | 10 mg/m3 | Short Term Exposure Limit (STEL): | as Fe | MX OEL |
| | 5 mg/m3 | Time Weighted Average (TWA): | Respirable fraction. | ACGIH |
| | 10 mg/m3 | Time Weighted Average (TWA): | | ACGIH |
| Titanium dioxide | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| | 10 mg/m3 | Time Weighted Average (TWA): | Total dust. | OSHA Z1A |
| | 10 mg/m3 | Time Weighted Average (TWA): | as Ti | MX OEL |
| | 20 mg/m3 | Short Term Exposure Limit (STEL): | as Ti | MX OEL |

9. PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|---------------------|-----------------------|------------------|-----------------------------|
| Form | : liquid | Evaporation rate | : Slower than Butyl Acetate |
| Appearance | : liquid | Specific Gravity | : Not determined |
| Colour | : BROWN | Bulk density | : Not applicable |
| Odour | : slight | Vapour pressure | : Not established |
| Melting point/range | : not applicable | Vapour density | : Heavier than air. |
| Boiling Point: | : no data available | pH | : Not determined |
| Water solubility | : completely miscible | | |

10. STABILITY AND REACTIVITY

| | |
|----------------------------------|--|
| Stability | : Stable |
| Hazardous Polymerization | : Will not occur. |
| Conditions to avoid | : Extremes of temperature and direct sunlight. Keep from freezing. |
| Incompatible Materials | : Acids, metal salts, and solvents |
| Hazardous decomposition products | : Carbon dioxide (CO ₂), carbon monoxide (CO), oxides of nitrogen (NO _x), other hazardous materials, and smoke are all possible. |

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

WB-10514-C CEDAR ATH COATING

Version Number 1.6
 Revision Date 03/12/2014

Page 5 of 7
 Print Date 3/18/2014

| CAS-No. | Chemical Name | Effect | Target Organ |
|------------|------------------|------------------|---------------------|
| 1309-37-1 | Iron oxide | Systemic effects | Respiratory system. |
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. |

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|------------|------------------|------|------|-----|
| 13463-67-7 | Titanium dioxide | no | 2B | no |

IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

- Persistence and degradability : no data available
- Environmental Toxicity : no data available
- Bioaccumulation Potential : no data available
- Additional advice : no data available

13. DISPOSAL CONSIDERATIONS

- Product : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
- Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

- U.S. DOT Classification : Refer to specific regulation.
- ICAO/IATA : Refer to specific regulation.
- IMO/IMDG (maritime) : Refer to specific regulation.



POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

WB-10514-C CEDAR ATH COATING

Version Number 1.6
Revision Date 03/12/2014

Page 6 of 7
Print Date 3/18/2014

15. REGULATORY INFORMATION

US Regulations:

- OSHA Status : Classified as hazardous based on components.
- TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

- California Proposition 65 : Not applicable

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name | CAS-No. | Weight percent | NPRI ID# |
|----------------------------------|------------|----------------|----------|
| Branched-nonylphenol, ethoxylate | 68412-54-4 | 0.10 - 1.00 | 186 |
| | | 0.10 - 1.00 | |

- WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

| |
|-----------|
| CAS-No. |
| 1309-37-1 |

- DSL : DSL status has not been determined. Quantity use in Canada may be restricted by regulations.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

WB-10514-C CEDAR ATH COATING

Version Number 1.6
Revision Date 03/12/2014

Page 7 of 7
Print Date 3/18/2014

National Inventories:

| | | |
|-------------------|---|----------------|
| Australia AICS | : | Not determined |
| China IECS | : | Not determined |
| Europe EINECS | : | Not determined |
| Japan ENCS | : | Not determined |
| Korea KECI | : | Not determined |
| Philippines PICCS | : | Not determined |

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.