

PX-V-343 BEIGE ROTOMOLDING PLAST.

Version Number 1.6 Page 1 of 21 Revision Date 01/09/2020 Print Date 01/11/2020

SAFETY DATA SHEET

PX-V-343 BEIGE ROTOMOLDING PLAST.

Section 1. Identification

GHS product identifier : PX-V-343 BEIGE ROTOMOLDING PLAST.

Chemical name: MixtureCAS number: MixtureOther means of identification: FO20010199Product type: liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number

(with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

EYE IRRITATION - Category 2B

SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2

TOXIC TO REPRODUCTION (Fertility) - Category 2 TOXIC TO REPRODUCTION (Unborn child) - Category 2

GHS label elements



PX-V-343 BEIGE ROTOMOLDING PLAST.

Version Number 1.6 Revision Date 01/09/2020 Page 2 of 21 Print Date 01/11/2020

Hazard pictograms





Signal word : Warning

Hazard statements : Causes eye irritation.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Suspected of causing cancer.

Precautionary statements

General : Not applicable.

Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Avoid

breathing vapor. Wash hands thoroughly after handling. Contaminated

work clothing must not be allowed out of the workplace.

Response: IF exposed or concerned: Get medical attention. IF ON SKIN: Wash

with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye

irritation persists: Get medical attention.

Storage : Store locked up.

Disposal: Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Supplemental label elements : None known.

Hazards not otherwise classified : None known.

Not available.

Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: FO20010199

CAS number/other identifiers

	Ingredient name	%	CAS number
--	-----------------	---	------------



PX-V-343 BEIGE ROTOMOLDING PLAST.

Version Number 1.6 Page 3 of 21 Revision Date 01/09/2020 Print Date 01/11/2020

1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	25 - 50	68515-48-0
2,4,4-Trimethyl-1,3-penytanediol diisobutyrate	1 - 3	6846-50-0
Titanium dioxide	0.3 - 1	13463-67-7
Bisphenol A - Epichlorohydrin polymer	0.3 - 1	25068-38-6
Di(2-ethylhexyl)phthalate	0 - 0.3	117-81-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim



PX-V-343 BEIGE ROTOMOLDING PLAST.

Version Number 1.6 Page 4 of 21 Revision Date 01/09/2020 Print Date 01/11/2020

to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact : May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

irritation watering redness

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact : Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.



PX-V-343 BEIGE ROTOMOLDING PLAST.

Version Number 1.6 Revision Date 01/09/2020

Page 5 of 21 Print Date 01/11/2020

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or CO₂.

None known.

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container

may burst.

Hazardous thermal

decomposition products

May emit Hydrogen Chloride (HCl).

Decomposition products may include the following materials:

carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides

Special protective actions for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without For non-emergency personnel

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

If specialized clothing is required to deal with the spillage, take note For emergency responders of any information in Section 8 on suitable and unsuitable materials.

See also the information in "For non-emergency personnel".



PX-V-343 BEIGE ROTOMOLDING PLAST.

Version Number 1.6 Revision Date 01/09/2020 Page 6 of 21 Print Date 01/11/2020

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.



PX-V-343 BEIGE ROTOMOLDING PLAST.

Version Number 1.6 Revision Date 01/09/2020 Page 7 of 21 Print Date 01/11/2020

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	None.
2,4,4-Trimethyl-1,3-penytanediol diisobutyrate	None.
Bisphenol A - Epichlorohydrin polymer	None.
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (1996-05-18) TWA 10 mg/m3
Di(2-ethylhexyl)phthalate	OSHA PEL 1989 (1989-03-01) TWA 5 mg/m3 STEL 10 mg/m3 OSHA PEL (1993-06-30) TWA 5 mg/m3 NIOSH REL (1994-06-01) TWA 5 mg/m3 STEL 10 mg/m3 ACGIH TLV (1999-03-01) TWA 5 mg/m3



PX-V-343 BEIGE ROTOMOLDING PLAST.

 Version Number 1.6
 Page 8 of 21

 Revision Date 01/09/2020
 Print Date 01/11/2020

Appropriate engineering controls: If user operations generate dust, fumes, gas, vapor or mist, use process

enclosures, local exhaust ventilation or other engineering controls to

keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls: Emissions from ventilation or work process equipment should be

checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be

necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical

products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations

and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used

when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a

higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved

standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves

cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that

meets the appropriate standard or certification. Respirators must be



PX-V-343 BEIGE ROTOMOLDING PLAST.

Version Number 1.6 Revision Date 01/09/2020 Page 9 of 21 Print Date 01/11/2020

used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state liquid [liquid] Color **BROWN** Odor Not available. **Odor threshold** Not available. pН Not available. Not available. **Melting point Boiling point** Not available. Flash point Not available. **Burning time** Not available. Not available. **Burning rate Evaporation rate** Not available. Flammability (solid, gas) Not available.

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.SolubilityNot available.Solubility in waterNot available.Partition coefficient: n-Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

Aerosol product

Heat of combustion : Not available.

Ignition distance : Not available. **Enclosed space ignition - Time** : Not available.

equivalent

Enclosed space ignition - : Not available.

Deflagration density

Flame height : Not available. Flame duration : Not available.



PX-V-343 BEIGE ROTOMOLDING PLAST.

 $\begin{array}{ccccc} \text{Version Number 1.6} & \text{Page } 10 \text{ of } 21 \\ \text{Revision Date } 01/09/2020 & \text{Print Date } 01/11/2020 \end{array}$

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : Keep away from extreme heat and oxidizing agents.

Incompatible materials : Avoid contact with acetal homopolymers and acetyl homopolymers

during processing.

Hazardous decomposition : Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

products

Product/ingredient name	Result	Species	Dose	Exposure	
Di(2-ethylhexyl)phthalate					
	LD50 Oral	Rat	30,000 mg/kg	-	
Remarks - Inhalation:	No applicable toxic	city data			
	LD50 Dermal	Rabbit	25,000 mg/kg	-	
Titanium dioxide					
Remarks - Oral:	No applicable toxic	city data			
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h	
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-	
Bisphenol A - Epichlorohydrin polymer					
	LD50 Oral	Rat	11,400 mg/kg	=	
Remarks - Inhalation:	No applicable toxicity data				
Remarks - Dermal:	No applicable toxicity data				
2,4,4-Trimethyl-1,3-penytaned	2,4,4-Trimethyl-1,3-penytanediol diisobutyrate				
Remarks - Oral:	No applicable toxicity data				
Remarks - Inhalation:	No applicable toxicity data				
Remarks - Dermal:	No applicable toxicity data				
1,2-Benzenedicarboxylic acid,	di-C8-10-branched	alkyl esters, C9-rich	_		
	LD50 Oral	Rat	10,000 mg/kg	-	



PX-V-343 BEIGE ROTOMOLDING PLAST.

Version Number 1.6 Page 11 of 21 Revision Date 01/09/2020 Print Date 01/11/2020

Remarks - Inhalation:	No applicable toxicity data
Remarks - Dermal:	No applicable toxicity data

Conclusion/Summary : Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Di(2-ethylhexyl)phthalate	Eyes - Mild irritant	Rabbit		24 hrs	-
	Skin - Mild irritant	Rabbit		24 hrs	-
	Eyes - Mild irritant	Rabbit			-
Titanium dioxide	Skin - Mild irritant	Human		72 hrs	-
Bisphenol A - Epichlorohydrin polymer	Eyes - Mild irritant	Rabbit			-
	Eyes - Mild irritant	Rabbit			-
	Skin - Moderate irritant	Rabbit		24 hrs	-
	Skin - Severe irritant	Rabbit		24 hrs	-
	Eyes - Mild irritant	Rabbit			-
2,4,4-Trimethyl-1,3- penytanediol diisobutyrate	Skin - Mild irritant	Human		504 hrs	-
	Skin - Mild irritant	Guinea pig			-
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	Eyes - Mild irritant	Rabbit			-

Conclusion/Summary

Skin: Mixture.Not fully tested.Eyes: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Sensitization

Conclusion/Summary

SkinMixture.Not fully tested.RespiratoryMixture.Not fully tested.

Mutagenicity



PX-V-343 BEIGE ROTOMOLDING PLAST.

Version Number 1.6 Page 12 of 21 Revision Date 01/09/2020 Print Date 01/11/2020

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
Di(2-ethylhexyl)phthalate	-	2B	Reasonably anticipated to be a human carcinogen.
Titanium dioxide	-	2B	-

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of

Not available.

exposure

Potential acute health effects

Eye contact : Causes eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact : May cause an allergic skin reaction.

Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following: irritation, watering,

redness

Inhalation: Adverse symptoms may include the following: reduced fetal weight,

increase in fetal deaths, skeletal malformations



PX-V-343 BEIGE ROTOMOLDING PLAST.

Version Number 1.6 Page 13 of 21 Revision Date 01/09/2020 Print Date 01/11/2020

Skin contact Adverse symptoms may include the following: irritation, redness,

reduced fetal weight, increase in fetal deaths, skeletal malformations

Adverse symptoms may include the following: reduced fetal weight, **Ingestion**

increase in fetal deaths, skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects Not available. Potential delayed effects Not available.

Long term exposure

Potential immediate effects Not available. **Potential delayed effects** Not available.

Potential chronic health effects

Conclusion/Summary Mixture.Not fully tested.

General Once sensitized, a severe allergic reaction may occur when

subsequently exposed to very low levels.

Carcinogenicity Suspected of causing cancer. Risk of cancer depends on duration and

level of exposure.

No known significant effects or critical hazards. Mutagenicity **Teratogenicity** Suspected of damaging the unborn child. No known significant effects or critical hazards.

Developmental effects

Fertility effects Suspected of damaging fertility.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Di(2-ethylhexyl)phthalate			



PX-V-343 BEIGE ROTOMOLDING PLAST.

Version Number 1.6 Revision Date 01/09/2020 Page 14 of 21 Print Date 01/11/2020

	T +		0.61
	Acute LC50 1,106.2 Mg/l Fresh	Fish - Fish	96 h
	water		
Remarks - Acute - Fish:	Acute	1	1
	Acute EC50 0.000133 Mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
Remarks - Acute - Aquatic	Acute		
invertebrates.:			
	Acute EC50 31 Mg/l Marine water	Aquatic plants - Algae	96 h
Remarks - Acute - Aquatic	Acute		
plants:			
	Acute NOEC 0.076 Mg/l Marine	Aquatic plants - Algae	72 h
	water		
Remarks - Acute - Aquatic	Chronic		
plants:			
	Chronic NOEC 0.012 Mg/l Fresh	Fish - Fish	28 d
	water		
Remarks - Chronic - Fish:	Chronic		
	Chronic NOEC 0.109 Mg/l Fresh	Aquatic invertebrates.	21 d
	water	Crustaceans	
Remarks - Chronic -	Chronic	•	
Aquatic invertebrates.:			
4	Chronic NOEC 0.077 Mg/l Fresh	Aquatic invertebrates.	21 d
	water	Daphnia	
Remarks - Chronic -	Chronic	1	•
Aquatic invertebrates.:			
Titanium dioxide			
	Acute LC50 > 1,000 Mg/l Marine	Fish - Fish	96 h
	water		
Remarks - Acute - Fish:	Acute		
	Acute LC50 3 Mg/l Fresh water	Aquatic invertebrates.	48 h
		Crustaceans	
Remarks - Acute - Aquatic	Acute		
invertebrates.:			
	Acute LC50 6.5 Mg/l Fresh water	Aquatic invertebrates.	48 h
	_	Daphnia	
Remarks - Acute - Aquatic	Acute		
invertebrates.:			
Remarks - Acute - Aquatic	No applicable toxicity data		
plants:			
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:			
Bisphenol A - Epichlorohydrir	polymer		
Remarks - Acute - Fish:	No applicable toxicity data		



PX-V-343 BEIGE ROTOMOLDING PLAST.

Version Number 1.6 Revision Date 01/09/2020 Page 15 of 21 Print Date 01/11/2020

D 1 4 4 4 4	M
Remarks - Acute - Aquatic	No applicable toxicity data
invertebrates.:	
Remarks - Acute - Aquatic	No applicable toxicity data
plants:	
Remarks - Chronic - Fish:	No applicable toxicity data
Remarks - Chronic -	No applicable toxicity data
Aquatic invertebrates.:	
2,4,4-Trimethyl-1,3-penytaned	iol diisobutyrate
Remarks - Acute - Fish:	No applicable toxicity data
Remarks - Acute - Aquatic	No applicable toxicity data
invertebrates.:	
Remarks - Acute - Aquatic	No applicable toxicity data
plants:	
Remarks - Chronic - Fish:	No applicable toxicity data
Remarks - Chronic -	No applicable toxicity data
Aquatic invertebrates.:	
1,2-Benzenedicarboxylic acid,	di-C8-10-branched alkyl esters, C9-rich
Remarks - Acute - Fish:	No applicable toxicity data
Remarks - Acute - Aquatic	No applicable toxicity data
invertebrates.:	
Remarks - Acute - Aquatic	No applicable toxicity data
plants:	
Remarks - Chronic - Fish:	No applicable toxicity data
Remarks - Chronic -	No applicable toxicity data
Aquatic invertebrates.:	
Conclusion/Summers	Not available

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Di(2-ethylhexyl)phthalate	7.6	1,380.00	high
Bisphenol A - Epichlorohydrin	2.64 - 3.78	31.00	low
polymer			
2,4,4-Trimethyl-1,3-penytanediol	-	5,340.00	high
diisobutyrate			
1,2-Benzenedicarboxylic acid, di-C8-	8.8	3.00	low
10-branched alkyl esters, C9-rich			



PX-V-343 BEIGE ROTOMOLDING PLAST.

Version Number 1.6 Page 16 of 21 Revision Date 01/09/2020 Print Date 01/11/2020

Mobility in soil

Soil/water partition coefficient

(KOC)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods: The generation of waste should be avoided or minimized wherever

possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR : Not regulated for transportation.

Ground/Air/Water

: Consult mode specific transport rules

International Air ICAO/IATA

International Water : Consult mode specific transport rules

IMO/IMDG

Section 15. Regulatory information



PX-V-343 BEIGE ROTOMOLDING PLAST.

Version Number 1.6 Revision Date 01/09/2020

Page 17 of 21 Print Date 01/11/2020

U.S. Federal regulations

United States - TSCA 12(b) - Chemical export notification: None of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Listed 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich

United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Listed 4-Nonylphenol, branched

United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined

United States - TSCA 8(a) - Preliminary assessment report (PAIR): Listed 4-Nonylphenol, branched

United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Di(2-ethylhexyl)phthalate

Zinc

Vinyl chloride monomer

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

United States - Department of commerce - Precursor chemical:

Not listed

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs) Listed

Clean Air Act Section 602 Class I

Clean Air Act Section 602 Class II

Not listed

Substances

Not listed

Substances



PX-V-343 BEIGE ROTOMOLDING PLAST.

 Version Number 1.6
 Page 18 of 21

 Revision Date 01/09/2020
 Print Date 01/11/2020

DEA List I Chemicals (Precursor: Not listed

Chemicals)

DEA List II Chemicals (Essential: Not listed

Chemicals)

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification : EYE IRRITATION - Category 2B

SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2

TOXIC TO REPRODUCTION - Fertility - Category 2 TOXIC TO REPRODUCTION - Unborn child - Category 2

Composition/information on ingredients

Name	%	Classification
1,2-Benzenedicarboxylic	>= 25 - <= 50	EYE IRRITATION - Category 2B
acid, di-C8-10-branched		
alkyl esters, C9-rich		
2,4,4-Trimethyl-1,3-	>= 1 - <= 3	TOXIC TO REPRODUCTION - Fertility - Category 2
penytanediol diisobutyrate		TOXIC TO REPRODUCTION - Unborn child - Category 2
Bisphenol A -	>= 0.3 - < 1	SKIN IRRITATION - Category 2
Epichlorohydrin polymer		EYE IRRITATION - Category 2B
		SKIN SENSITIZATION - Category 1
Titanium dioxide	>= 0.3 - <= 1	CARCINOGENICITY - Category 2
Di(2-ethylhexyl)phthalate	> 0 - <= 0.3	EYE IRRITATION - Category 2B
		CARCINOGENICITY - Category 2
		- •

SARA 313

Form R - Reporting requirements

Product name	CAS number	%
Di(2-ethylhexyl)phthalate	117-81-7	> 0 - <= 0.3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall



PX-V-343 BEIGE ROTOMOLDING PLAST.

Version Number 1.6 Page 19 of 21 Revision Date 01/09/2020 Print Date 01/11/2020

include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts: None of the components are listed.New York: The following components are listed:

Di(2-ethylhexyl)phthalate

New Jersey : The following components are listed:

Ethene, chloro-, homopolymer

Calcium carbonate Titanium dioxide

Di(2-ethylhexyl)phthalate

Pennsylvania: The following components are listed:

Calcium carbonate

Titanium dioxide

Di(2-ethylhexyl)phthalate

California Prop. 65

WARNING: This product can expose you to chemicals including Di(2-ethylhexyl)phthalate, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Titanium dioxide, 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich, which are known to the State of California to cause cancer, and Diisodecyl phthalate (mixed isomers), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	Yes.	-
Titanium dioxide	-	-
Diisodecyl phthalate (mixed isomers)	-	Yes.
Di(2-ethylhexyl)phthalate	Yes.	Yes.

United States inventory (TSCA 8b) : All components are active or exempted.

Canada inventory : At least one component is not listed in DSL but all such components

are listed in NDSL.

International regulations

Inventory list



PX-V-343 BEIGE ROTOMOLDING PLAST.

Version Number 1.6 Page 20 of 21 Revision Date 01/09/2020 Print Date 01/11/2020

Australia : Not determined.

Canada : At least one component is not listed in DSL but all such components

are listed in NDSL.

China Not determined. **Europe inventory** Not determined. Not determined. Japan **New Zealand** Not determined. **Philippines** Not determined. Republic of Korea Not determined. Taiwan Not determined. **Turkey** Not determined.

United States : All components are active or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

Date of printing: 01/11/2020Date of issue/Date of revision: 01/09/2020Date of previous issue: 11/19/2013

Version : 1.6

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine



PX-V-343 BEIGE ROTOMOLDING PLAST.

Version Number 1.6 Revision Date 01/09/2020 Page 21 of 21 Print Date 01/11/2020

pollution)

UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.