MATERIAL SAFETY DATA SHEET

DB3871 BLACK

Version Number 1.0 Revision Date 05/24/2005 Page 1 of 6 Print Date 11/18/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DB3871 BLACK
Product code	:	FO20011113
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium oxide	1305-78-8	1 - 5
Magnesium carbonate	546-93-0	1 - 5
Misc00016- Bituminous Coal	Not Available	1 - 5
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET **DB3871 BLACK**

Version Number 1.0 Revision Date 05/24/2005 Page 2 of 6 Print Date 11/18/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available Not applicable Carbon dioxide blanket, water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or th soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET DB3871 BLACK

Version Number 1.0 Revision Date 05/24/2005	Page 3 of 6 Print Date <i>11/18/2011</i>
Handling :	Heat only in areas with appropriate exhaust ventilation. Processing
	fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage :	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXPOSUI	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection :	No personal respiratory protective equipment normally required.
Eye/Face Protection :	Safety glasses with side-shields.
Hand protection :	Protective gloves.
Skin and body protection :	Long sleeved clothing.
Additional Protective : Measures	Safety shoes.
General Hygiene : Considerations	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures :	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Calcium oxide	2 mg/m3	Time Weighted Average	Dust.	ACGIH
		(TWA):		
	5 mg/m3	PEL:	Dust.	OSHA Z1
Magnesium carbonate	10 mg/m3	Time Weighted Average	Dust.	ACGIH
		(TWA):		
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Misc00016-	2.4 mg/m3	PEL:	Respirable fraction.	Z3
Bituminous Coal				
	2.0 mg/m3	Time Weighted Average	Respirable fraction.	ACGIH
		(TWA):		

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance : liquid : Viscous, liquid

Specific Gravity:

Evaporation rate : Not established : Not determined

POLYONE CORPORATION MATERIAL SAFETY DATA SHEET

DB3871 BLACK

Version Numbe	er 1.0
Revision Date	05/24/2005



Page 4 of 6 Print Date 11/18/2011

C N E	Color Odor Melting point/range Boiling Point: Water solubility	: Ve : Ne : Ne	LACK ery faint ot applicable ot applicable miscible	Bulk density Vapor pressure Vapour density pH	: : :	Not applicable Not determined Not determined Not applicable
		10). STABILITY AND RE	CACTIVITY		
S	Stability	:	Stable.			
H	Hazardous Polymerization	:	Will not occur.			
(Conditions to avoid	:	Keep away from oxidiz decomposition, do not o		me.	To avoid thermal
I	ncompatible Materials	:	Incompatible with stron with acetal homopolym			
	Hazardous decomposition broducts	:	Carbon dioxide (CO2), (NOx), hydrogen chlori smoke are all possible. degradation. As a gener after one hour at 177 °C and within 5 minutes at	de (HCl), other hazardo Prolonged heating may ral rule of thumb, degra (350 °F), after 10 min	ous i res idati	materials, and ult in product on begins to occur

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1305-78-8	Calcium oxide	Irritant	Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
		Corrosive	Skin.
546-93-0	Magnesium carbonate	Irritant	Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
Not Available	Misc00016- Bituminous Coal	Irritant	Eyes, Skin.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.

whole.

Environmental Toxicity

: Environmental toxicity has not been established for this mixture as a

4/6

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET **DB3871 BLACK**

Version Number 1.0 Revision Date 05/24/2005 Page 5 of 6 Print Date 11/18/2011

Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. T generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste mater has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSC Inventory.
US. EPA CERCLA Hazardou	as Substances (40 CFR 302)
Not applicable	
California Propositior 65	: WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 E Not applicable	xtremely Hazardous Substance
SARA Title III Section 313 T	oxic Chemicals:

PolyOne.

MATERIAL SAFETY DATA SHEET **DB3871 BLACK**

Version Number 1.0 Revision Date 05/24/2005 Page 6 of 6 Print Date 11/18/2011

Chemical Name		CAS-No.	Weight %
	ALKANES (C10 TO C13)	61788-76-9	9.19
anadian Regulations:			
National Pollutant Releas	se Inventory (NPRI)		
Not applicable			
WHMIS Classification	: D2B		
WHMIS Ingredient Disc	losure List		
CAS-No. 1305-78-8			
DSL	: All components of this Substances List (DSL)		e Canadian Domestic
ational Inventories:			
Australia AICS	: Not determined		
China IECS	: Not determined		
Europe EINECS	: Listed		
Japan ENCS	: Not determined		
Korea KECI	: Not determined		
Philippines PICCS	: Not determined		
	16. OTHER INFORM	IATION	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.