MATERIAL SAFETY DATA SHEET 99124CBA PLAST-O-CELL ADC-3052-88-ESO

Version Number 1.1 Revision Date 05/24/2005

Page 1 of 6 Print Date 11/18/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	99124CBA PLAST-O-CELL ADC-3052-88-ESO
Product code	:	FO20011138
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Azodicarbonamide	123-77-3	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

May release high amount of nitrogen if inadvertenly heated above 50°C (122°F) or stored incorrectly. Pressure inside the container can increase and cause its rupture. This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	Eyes, Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation Ingestion Eyes Skin	 At process temperatures, product emissions may cause irritation. May be harmful if swallowed. May cause eye/skin irritation. Experience shows no unusual dermatitis hazard from routine handling. 		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		



MATERIAL SAFETY DATA SHEET 99124CBA PLAST-O-CELL ADC-3052-88-ESO

Version Number 1.1 Revision Date 05/24/2005 Page 2 of 6 Print Date 11/18/2011

	4. FIRST AID MEASURES
Inhalation	: Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water.
	5. FIRE-FIGHTING MEASURES
Flash point	: Greater than 200 °F (93 °C)
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures	 No data available No data available No data available No data available waterfoam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Cool closed containers exposed to fire with water spray If inadvertent heating of product results in smoke production, spray immediately and thoroughly with water. May release high amount of nitrogen if inadvertenly heated above 50°C (122°F) or stored
Unusual Fire/Explosion Hazards	 incorrectly. Pressure inside the container can increase and cause its rupture. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May release high amount of nitrogen if inadvertenly heated above 50°C (122°F) or stored incorrectly. Pressure inside the container can increase and cause its rupture.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Contain and collect spillage with non-combustible absorbent material (e.g. sand, earth, diatomaceus earth, vermiculite) and place in container for disposal according to local / national regulations (see



MATERIAL SAFETY DATA SHEET 99124CBA PLAST-O-CELL ADC-3052-88-ESO

Version Number 1.1 Revision Date 05/24/2005 Page 3 of 6 Print Date 11/18/2011

		7. HANDLING AND STORAGE
Handling	:	Wear personal protective equipment. Take measures to prevent the build up of electrostatic charge. Provide for appropriate exhaust ventilation and dust collection at machinery.
Storage	:	Keep away from open flames, hot surfaces and sources of ignition. Keep away from direct sunlight. Keep in a dry, cool place. May release high amount of nitrogen if inadvertenly heated above 50°C (122°F) or stored incorrectly. Pressure inside the container can increase and cause its rupture.
8. EXI	POSUI	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	When workers are facing concentrations above the exposure limit the must use appropriate certified respirators. Employees using respirators must be properly trained. Employers must follow applicable regulations such as OSHA 29 CFR 1910.134.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved shirts and long pants are adequate for normal handling. Where operations present a splash or spill potential, employees should wear chemically resistant clothing, boots, apron, gloves, and eye/face protection.
Additional Protective Measures	:	When using, do not eat, drink or smoke.
General Hygiene Considerations	:	Do not breathe dust or spray mist. Handle in accordance with good industrial hygiene and safety practices.
Engineering measures	:	Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.
Exposure limit(s)		

Form Appearance Color Odor : liquid: Viscous liquid dispersion: NOT APPLICABLE: Very faint

Evaporation rate Specific Gravity: Bulk density Vapor pressure Not applicableNot determinedNot establishedNot determined



MATERIAL SAFETY DATA SHEET 99124CBA PLAST-O-CELL ADC-3052-88-ESO

Version Number 1.1 Revision Date 05/24/2005 Page 4 of 6 Print Date 11/18/2011

Melting point/range Boiling Point: Water solubility	Not applicableNot applicableNegligible	Vapour density pH	Not determinedNot determined					
10. STABILITY AND REACTIVITY								
Stability	: Stable.							
Hazardous Polymerization	: Will not occur.							
Conditions to avoid	: Heat, flames and sp	parks.						
Incompatible Materials	: Reacts with water of	or acids to form carbon di	oxide (CO2)					
Hazardous decomposition products	(NOx), other hazard Ammonia May rele above 50°C (122°F	D2), carbon monoxide (C dous materials, and smok ease high amount of nitro) or stored incorrectly. P ase and cause its rupture.	e are all possible. gen if inadvertenly heated					

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
123-77-3	Azodicarbonamide	sensitizer	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
123-77-3	Azodicarbonamide	LC50 Oral LD50	200 mg/l > 6,400 mg/kg	rat rat
		Dermal LD50	> 2,000 mg/kg	rabbit

Additional Health Hazard Information:

Azodicarbonamide 123-77-3 Sensitizer to the respiratory system with repeated minimal inhalation. While no chronic health problems have been identified, individuals with respiratory problems should avoid inhalation exposure to this material.

12. ECOLOGICAL INFORMATION

Persistence and degradability

: No data available

Environmental Toxicity

: No data available

sion Date 05/24/2005		Pag //Print Date 11/
Bioaccumulation Potential	:	No data available
Additional advice	:	No data available
	1.	3. DISPOSAL CONSIDERATIONS
Product	:	The generator of waste material has the responsibility for proper v classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste mat has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provinci- and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Refer to specific regulation.
ICAO/IATA (air)	:	Refer to specific regulation.
IMO / IMDG (maritime)	:	Refer to specific regulation.
	15	5. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the T Inventory.
US. EPA CERCLA Hazardou	s Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	Not applicable
SARA Title III Section 302 E Not applicable	xtrem	ely Hazardous Substance

1

.

PolyOne.

MATERIAL SAFETY DATA SHEET 99124CBA PLAST-O-CELL ADC-3052-88-ESO

Version Number 1.1 Revision Date 05/24/2005

_

Page 6 of 6 Print Date 11/18/2011

National Pollutant Release	se Ir	iventory (NPRI)	
Not applicable			
WHMIS Classification	:	D2A	
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
National Inventories:			
Australia AICS	:	Listed	
China IECS	:	Listed	
Europe EINECS	:	Listed	
Japan ENCS	:	Listed	
Korea KECI	:	Listed	
Philippines PICCS	:	Listed	
		16. OTHER INFORMATION	Ī

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.