MATERIAL SAFETY DATA SHEET STAN-TONE VC-29844 TAN

Version Number 1.0 Revision Date 04/08/2005

Page 1 of 6 Print Date 11/17/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	STAN-TONE VC-29844 TAN
Product code	:	FO20011330
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Chromium (III) oxide	1308-38-9	1 - 5
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET STAN-TONE VC-29844 TAN

Version Number 1.0 Revision Date 04/08/2005 Page 2 of 6 Print Date 11/17/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit	Not applicableNot applicable
Autoignition temperature	: Not relevant
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume

PolyOne

MATERIAL SAFETY DATA SHEET STAN-TONE VC-29844 TAN

Version Number 1.0 Revision Date 04/08/2005 Page 3 of 6 Print Date 11/17/2011

condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Chromium (III) oxide	0.5 mg/m3	Time Weighted Average	as Cr	ACGIH
		(TWA):		
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
	20 mppcf	PEL:	Total dust.	Z3
	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	0.8 mg/m3	Time Weighted Average		Z3
		(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Solidpowder, granularTANVery faint

Evaporation rate Specific Gravity: Bulk density Vapor pressure Not applicableNot determinedNot determinedNot applicable

MATERIAL SAFETY DATA SHEET STAN-TONE VC-29844 TAN

Version Number 1.0 Revision Date 04/08/2005 Page 4 of 6 Print Date 11/17/2011

Melting point/range Boiling Point: Water solubility	Not determinedNot applicableInsoluble	Vapour density pH	Not applicableNot applicable		
	10. STABILITY ANI	D REACTIVITY		T	
Stability	: Stable.				
Hazardous Polymerization	: Will not occur.				
Conditions to avoid	: To avoid thermal d oxidizing agents an	ecomposition, do not ove nd open flame.	erheat. Keep away from		
Incompatible Materials	-	strong acids and oxidizin olymers and acetal copoly			
Hazardous decomposition products	(NOx), hydrogen c smoke are all possi or more) above 392 °C) may result in p	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride. 			

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1308-38-9	Chromium (III) oxide	Irritant	Eyes, Skin.
		sensitizer	Skin.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Additional Health Hazard Information:

Chromium (III) oxide 1308-38-9 The bi and trivalent forms of chrome have a low order of acute toxicity but may cause skin sensitization and irritation to the eyes. No effects have been reported for chromium (III) oxide. Chromium (III) componds are not considered carcinogenic in animals or humans.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	:	No data available

PolyOne.

MATERIAL SAFETY DATA SHEET STAN-TONE VC-29844 TAN

Version Number 1.0 Revision Date 04/08/2005 Page 5 of 6 Print Date 11/17/2011

	13. DISPOSAL CON	ISIDERATIONS		
Product	generator of waste classification, trans			
Contaminated packaging	has the responsibili	ity for proper waste cl ordance with applicab	ne generator of waste mat assification, transportatio le federal, state/provincia	n
	14. TRANSPORT IN	NFORMATION		
U.S. DOT Classification	: Not regulated for tr	ransportation.		
ICAO/IATA (air)	: Not regulated for tr	ransportation.		
IMO / IMDG (maritime)	: Not regulated for tr	ransportation.		
	15. REGULATORY	INFORMATION		
US Regulations:				
OSHA Status	: Classified as hazard	dous based on compo	nents.	
TSCA Status		-	on or exempt from the TS	SCA
US. EPA CERCLA Hazardou	18 Substances (40 CFR 302	2)		
		,		
Not applicable				
California Proposition 65	n : This product does r	not contain a substance	e listed by California Prop	p 65
SARA Title III Section 302 E Not applicable	Extremely Hazardous Subst	ance		
SARA Title III Section 313 T	Coxic Chemicals:			
Chemical Name		CAS-No.	Weight %	
CHROMIUM III CO	MDOLINIDE	1308-38-9	4.06	

MATERIAL SAFETY DATA SHEET STAN-TONE VC-29844 TAN

Philippines PICCS

Version Number 1.0 Revision Date 04/08/2005 Page 6 of 6 Print Date 11/17/2011

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight %	NPRI ID#
Chromium (III) oxide	1308-38-9	4.06	69
Zinc stearate	557-05-1	0.12	231

WHMIS Classification : D2B WHMIS Ingredient Disclosure List CAS-No. 1308-38-9 7631-86-9 DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt. National Inventories: Australia AICS Listed : China IECS Listed : **Europe EINECS** Listed · Japan ENCS Not determined : Korea KECI : Listed

:

Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.