MATERIAL SAFETY DATA SHEET

DB3918 BLACK

Version Number 1.0 Revision Date 07/07/2005 Page 1 of 7 Print Date 11/18/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DB3918 BLACK
Product code	:	FO20011931
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Antimony trioxide	1309-64-4	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET **DB3918 BLACK**

Version Number 1.0 Revision Date 07/07/2005 Page 2 of 7 Print Date 11/18/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures	 No data available No data available Not applicable Carbon dioxide blanket, water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



MATERIAL SAFETY DATA SHEET **DB3918 BLACK**

ion Number 1.0 sion Date 07/07/2005				Print Da	Page ate 11/18,
	Р	ume condensates may cont eriodically clean hoods, du ccumulation of these mate	ucts, and other surfa	toxic resid aces to min	lue. nimize
Storage		Leep containers dry and tig nd contamination. Store in		1 moisture	absorption
8. 1	EXPOSURE	CONTROLS / PERSON	AL PROTECTIO	N	
Respiratory protection	: N	lo personal respiratory pro	tective equipment r	normally r	equired.
Eye/Face Protection	: S	afety glasses with side-shi	elds.		
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		landle in accordance with g Vash hands before breaks a			ifety praction
Engineering measures Exposure limit(s)		leat only in areas with app ppropriate exhaust ventilat		ntilation.	Provide
<u></u>					
Components	Value	Exposure time	Exposure	type	List:
Antimony trioxide	0.5 mg/m3	PEL:	as St)	OSHA Z
	0.5 mg/m3	Time Weighted Averag (TWA):	ge as St	0	ACGIH
	9. PHYSIC	CAL AND CHEMICAL	PROPERTIES		
Form	: liqui	d Fr	vaporation rate	• Not	established
Appearance			ecific Gravity:		determined
Color	: 01500 : BLA		alk density		applicable
Odor			apor pressure		determined
			Vapour density		determined
Melting point/range			pH		applicable
Melting point/range Boiling Point:	: Not a	applicable pH			
	: Not a : Imm		-		
Boiling Point:	: Imm				
Boiling Point:	: Imm 10. S	iscible			



MATERIAL SAFETY DATA SHEET **DB3918 BLACK**

Version Number 1.0 Revision Date 07/07/2005		Page 4 of 7 Print Date 11/18/2011
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).
	11. 7	FOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1309-64-4	Antimony trioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

PolyOne.

MATERIAL SAFETY DATA SHEET **DB3918 BLACK**

Version Number 1.0 Revision Date 07/07/2005 Page 5 of 7 Print Date 11/18/2011

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	

PolyOne.

MATERIAL SAFETY DATA SHEET **DB3918 BLACK**

Version Number 1.0 Revision Date 07/07/2005 Page 6 of 7 Print Date 11/18/2011

California Proposition 65		California to cau	use cance		ins a chem	ical kno	own to the State of
SARA Title III Section 302 E Not applicable	xtrem	ely Hazardous Su	bstance				
SARA Title III Section 313 T	oxic C	Chemicals:					
Chemical Name ANTIMONY COMPOUNI	DS			CAS-N 1309-6		Weigh	
Canadian Regulations:							
National Pollutant Rele	ease Iı	nventory (NPRI)	I				
Chemical Name Antimony trioxide			CAS-N 1309-6		Weigh 1.00 -		NPRI ID# 17
National Inventories: Australia AICS	:	Substances List	(DSL) or	are exe	mpt.		
China IECS	:	Not determined					
Europe EINECS	:	Not determined					
Japan ENCS	:	Not determined					
Korea KECI	:	Not determined					
Philippines PICCS	:	Not determined					
		16. OTHER IN	NFORM	ATION			



MATERIAL SAFETY DATA SHEET **DB3918 BLACK**

Version Number 1.0 Revision Date 07/07/2005

Page 7 of 7 Print Date 11/18/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.