



# POLYONE CORPORATION

## MATERIAL SAFETY DATA SHEET

### STAN-TONE HCC-12600 BLACK

Version Number 1.1  
Revision Date 02/14/2007

Page 1 of 8  
Print Date 11/26/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

**POLYONE CORPORATION**  
8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone : Product Stewardship (770) 590-3500 x.3563  
Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure  
number : or accident).

Product name : STAN-TONE HCC-12600 BLACK  
Product code : FO20013036  
Chemical Name : Mixture  
CAS-No. : Mixture  
Product Use : Industrial Applications

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

| Components                           | CAS-No.    | Weight % |
|--------------------------------------|------------|----------|
| Ethyl benzene                        | 100-41-4   | 0.1 - 1  |
| Rutile, antimony chromium buff       | 68186-90-3 | 1 - 5    |
| Titanium dioxide                     | 13463-67-7 | 1 - 5    |
| Spinels, chromium (III) copper black | 68186-91-4 | 30 - 60  |

#### 3. HAZARDS IDENTIFICATION

##### EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

##### POTENTIAL HEALTH EFFECTS

**Routes of Exposure:** : Inhalation, Skin contact, Ingestion

##### Acute exposure

Inhalation : Inhalation of airborne droplets may cause irritation of the respiratory tract.  
Ingestion : May be harmful if swallowed.  
Eyes : May cause eye/skin irritation.  
Skin : Experience shows no unusual dermatitis hazard from routine handling.

**Chronic exposure** : Refer to Section 11 for Toxicological Information.

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**STAN-TONE HCC-12600 BLACK**

Version Number 1.1  
Revision Date 02/14/2007

Page 2 of 8  
Print Date 11/26/2011

**Medical Conditions** : None known.  
**Aggravated by Exposure:**

**4. FIRST AID MEASURES**

Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. Seek medical attention if necessary.

Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

**5. FIRE-FIGHTING MEASURES**

Flash point : No data available

Flammable Limits  
Upper explosion limit : No data available  
Lower explosion limit : No data available

Autoignition temperature : Not applicable

Suitable extinguishing media : Carbon dioxide blanket, water spray, dry powder, foam.

Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.

Unusual Fire/Explosion Hazards : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), other hazardous materials, and smoke are all possible.

**6. ACCIDENTAL RELEASE MEASURES**

Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

**7. HANDLING AND STORAGE**

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**STAN-TONE HCC-12600 BLACK**

Version Number 1.1

Revision Date 02/14/2007

Page 3 of 8

Print Date 11/26/2011

Handling : Heat only in areas with appropriate exhaust ventilation. Prolonged heating may result in product degradation.

Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

Respiratory protection : Under normal handling conditions a respirator may not be required.

Eye/Face Protection : Safety glasses with side-shields.

Hand protection : Protective gloves.

Skin and body protection : Long sleeved clothing.

Additional Protective Measures : Safety shoes.

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**STAN-TONE HCC-12600 BLACK**

Version Number 1.1  
Revision Date 02/14/2007

Page 4 of 8  
Print Date 11/26/2011

| Components                           | Value     | Exposure time                     | Exposure type      | List:   |
|--------------------------------------|-----------|-----------------------------------|--------------------|---------|
| Ethyl benzene                        | 100 ppm   | Time Weighted Average (TWA):      | Vapor and aerosol. | ACGIH   |
|                                      | 434 mg/m3 |                                   |                    |         |
|                                      | 125 ppm   | Short Term Exposure Limit (STEL): | Vapor and aerosol. | ACGIH   |
|                                      | 543 mg/m3 |                                   |                    |         |
| Rutile, antimony chromium buff       | 100 ppm   | PEL:                              | Vapor and aerosol. | OSHA Z1 |
|                                      | 435 mg/m3 |                                   |                    |         |
|                                      | 0.5 mg/m3 | Time Weighted Average (TWA):      | as Cr              | ACGIH   |
|                                      | 0.5 mg/m3 | PEL:                              | as Cr              | OSHA Z1 |
|                                      | 0.5 mg/m3 | Time Weighted Average (TWA):      |                    | MX OEL  |
|                                      | 0.5 mg/m3 | Time Weighted Average (TWA):      | as Sb              | ACGIH   |
|                                      | 0.5 mg/m3 | PEL:                              | as Sb              | OSHA Z1 |
|                                      | 0.5 mg/m3 | Time Weighted Average (TWA):      | as Sb              | MX OEL  |
| Spinels, chromium (III) copper black | 0.5 mg/m3 | Time Weighted Average (TWA):      | as Cr              | ACGIH   |
|                                      | 0.5 mg/m3 | PEL:                              | as Cr              | OSHA Z1 |
| Titanium dioxide                     | 10 mg/m3  | Time Weighted Average (TWA):      |                    | ACGIH   |
|                                      | 15 mg/m3  | PEL:                              | Total dust.        | OSHA Z1 |
|                                      | 20 mg/m3  | Short Term Exposure Limit (STEL): | as Ti              | MX OEL  |

**9. PHYSICAL AND CHEMICAL PROPERTIES**

|                     |                                     |                   |                     |
|---------------------|-------------------------------------|-------------------|---------------------|
| Form                | : liquid                            | Evaporation rate  | : Not established   |
| Appearance          | : liquid, Viscous liquid dispersion | Specific Gravity: | : Not determined    |
| Color               | : BLACK                             | Bulk density      | : Not applicable    |
| Odor                | : Very faint                        | Vapor pressure    | : Not determined    |
| Melting point/range | : Not applicable                    | Vapour density    | : Heavier than air. |
| Boiling Point:      | : Not applicable                    | pH                | : Not determined    |
| Water solubility    | : Immiscible                        |                   |                     |

**10. STABILITY AND REACTIVITY**

|                          |  |
|--------------------------|--|
| Stability                | : Stable.  |
| Hazardous Polymerization | : Will not occur.  |
| Conditions to avoid      | : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. |
| Incompatible Materials   | : Incompatible with strong acids and oxidizing agents.   |
| Hazardous decomposition  | : Carbon dioxide (CO <sub>2</sub> ), carbon monoxide (CO), oxides of nitrogen                      |

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**STAN-TONE HCC-12600 BLACK**

Version Number 1.1  
Revision Date 02/14/2007

Page 5 of 8  
Print Date 11/26/2011

products (NOx), other hazardous materials, and smoke are all possible.

**11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No.    | Chemical Name                        | Effect           | Target Organ  |
|------------|--------------------------------------|------------------|---|
| 100-41-4   | Ethyl benzene                        | Irritant         | Eyes, Skin, Respiratory system.                               |
|            |                                      | Systemic effects | Eyes, Skin, Respiratory system, central nervous system (CNS). |
| 68186-90-3 | Rutile, antimony chromium buff       | Irritant         | Eyes, Skin, Respiratory system.                               |
| 13463-67-7 | Titanium dioxide                     | Systemic effects | Respiratory system.   |
| 68186-91-4 | Spinels, chromium (III) copper black | Irritant         | Eyes, Skin, Respiratory system.                               |

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No.  | Chemical Name | Route       | Value       | Species |
|----------|---------------|-------------|-------------|---------|
| 100-41-4 | Ethyl benzene | Oral LD50   | 3,500 mg/kg | rat     |
|          |               | Dermal LD50 | 17800 ul/kg | rabbit  |

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No.    | Chemical Name    | OSHA | IARC | NTP |
|------------|------------------|------|------|-----|
| 100-41-4   | Ethyl benzene    | no   | 2B   | no  |
| 13463-67-7 | Titanium dioxide | no   | 2B   | no  |

IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

**Additional Health Hazard Information:**

**Rutile, antimony chromium buff 68186-90-3** Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

**Additional Health Hazard Information:**

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**STAN-TONE HCC-12600 BLACK**

Version Number 1.1  
Revision Date 02/14/2007

Page 6 of 8  
Print Date 11/26/2011

**Spinels, chromium (III) copper black 68186-91-4 The bi- and trivalent forms of chrome have a low order of acute toxicity, but may cause skin sensitization and irritation to the eyes. No effects have been reported for chromium (III) oxide. Chromium (III) compounds are not considered carcinogenic in animals or humans.**

**12. ECOLOGICAL INFORMATION**

Persistence and degradability : Not readily biodegradable.  
Environmental Toxicity : Environmental toxicity has not been established for this mixture as a whole.  
Bioaccumulation Potential : No data available  
Additional advice : No data available

**13. DISPOSAL CONSIDERATIONS**

Product : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.  
Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

**14. TRANSPORT INFORMATION**

U.S. DOT Classification : Refer to specific regulation.  
ICAO/IATA (air) : Refer to specific regulation.  
IMO / IMDG (maritime) : Refer to specific regulation.

**15. REGULATORY INFORMATION**

US Regulations:

OSHA Status : Classified as hazardous based on components.  
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**STAN-TONE HCC-12600 BLACK**

Version Number 1.1  
Revision Date 02/14/2007

Page 7 of 8  
Print Date 11/26/2011

California Proposition : Not applicable  
65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

| Chemical Name   | CAS-No.    | Weight %      |
|---|------------|---------------|
| CHROMIUM III COMPOUNDSANTIMONY COMPOUNDS                  | 68186-90-3 | 1.00 - 5.00   |
| CHROMIUM III COMPOUNDS COPPER COMPOUNDS (WITH EXCEPTIONS) | 68186-91-4 | 30.00 - 60.00 |

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name                  | CAS-No.    | Weight %    | NPRI ID# |
|--------------------------------|------------|-------------|----------|
| Rutile, antimony chromium buff | 68186-90-3 | 1.00 - 5.00 | 69       |
|                                |            | 1.00 - 5.00 | 17       |
| Xylenes (o-, m-, p- isomers)   | 1330-20-7  | 0.10 - 1.00 | 230      |

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

|            |
|------------|
| CAS-No.    |
| 100-41-4   |
| 68186-90-3 |
| 68186-91-4 |
| 1330-20-7  |

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Not determined

China IECS : Not determined



**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**STAN-TONE HCC-12600 BLACK**

Version Number 1.1  
Revision Date 02/14/2007

Page 8 of 8  
Print Date 11/26/2011

Europe EINECS : Listed  
Japan ENCS : Not determined  
Korea KECI : Not determined  
Philippines PICCS : Not determined

**16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.