NEC AM100 GRAY

Version Number 1.5 Revision Date 11/07/2018

ne

Page 1 of 19 Print Date 12/08/2018

SAFETY DATA SHEET

NEC AM100 GRAY

Section 1. Identification		
GHS product identifier	:	NEC AM100 GRAY
Chemical name	:	Mixture
CAS number	:	Mixture
Other means of identification	:	FO20022542
Product type	:	liquid
<u>Relevant identified uses of the sub</u> Product use	stance :	or mixture and uses advised against Industrial applications. Plastics.
Supplier's details	:	POLYONE CORPORATION
		33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

GHS label elements

NEC AM100 GRAY

Version Number 1.5 Revision Date 11/07/2018

<u>PolyOne</u>

Page 2 of 19
Print Date 12/08/2018

Hazard pictograms	:	
Signal word Hazard statements	:	Danger Highly flammable liquid and vapor. Causes serious eye irritation. Causes skin irritation.
Precautionary statements		
General	:	Not applicable.
Prevention Response	:	Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Wash hands thoroughly after handling. IF ON SKIN (or hair): Take off immediately all contaminated
Response	•	clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	:	Store in a well-ventilated place. Keep cool.
Disposal	:	Dispose of contents and container in accordance with all local,
Supplemental label elements		regional, national and international regulations. None known.
Supplemental label elements Hazards not otherwise classified	:	None known.

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	FO20022542

CAS number/other identifiers

Ingredient name	%	CAS number
Methyl ethyl ketone	50 - 75	78-93-3



NEC AM100 GRAY

Version Number 1.5 Revision Date 11/07/2018 Page 3 of 19 Print Date 12/08/2018

Titanium dioxide	0.3 - 1	13463-67-7
Carbon black	0 - 0.3	1333-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.

NEC AM100 GRAY

<u>PolyOne</u>

Version Number 1.5 Revision Date 11/07/2018 Page 4 of 19 Print Date 12/08/2018

Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact	:	Causes serious eye irritation.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Causes skin irritation.
Ingestion	:	No known significant effects or critical hazards.
Over-exposure signs/symptoms	<u>.</u>	
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Indication of immediate medica	al attentio	n and special treatment needed, if necessary
Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	Use dry chemical, CO_2 , water spray (fog) or foam. Do not use water jet.
Specific hazards arising from the	:	Highly flammable liquid and vapor. In a fire or if heated, a pressure

NEC AM100 GRAY



Version Number 1.5 Revision Date 11/07/2018	Page 5 of 19 Print Date 12/08/2018
chemical	increase will occur and the container may burst, with the risk of a
	subsequent explosion. Runoff to sewer may create fire or explosion hazard.
Hazardous thermal :	May emit Hydrogen Chloride (HCl).
decomposition products	Decomposition products may include the following materials: carbon dioxide

Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire- exposed containers cool.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

carbon monoxide

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders Environmental precautions	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containm	ent a	nd cleaning up
Small spill Large spill	:	Stop leak if without risk. Move containers from spill area. Use spark- proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. Stop leak if without risk. Move containers from spill area. Use spark-
		E/40

NEC AM100 GRAY

Version Number 1.5 Revision Date 11/07/2018



Page 6 of 19 Print Date 12/08/2018

proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

NEC AM100 GRAY

Version Number 1.5 Revision Date 11/07/2018 <u>PolyOne</u>.

Page 7 of 19 Print Date 12/08/2018

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (1996-05-18) TWA 10 mg/m3
Carbon black	OSHA PEL 1989 (1989-03-01) TWA 3.5 mg/m3 OSHA PEL (1993-06-30) TWA 3.5 mg/m3 NIOSH REL (1994-06-01) TWA 3.5 mg/m3 TWA 0.1 mgPAH/m³ ACGIH TLV (2010-12-06) TWA 3 mg/m3 Form: Inhalable fraction
Methyl ethyl ketone	OSHA PEL 1989 (1989-03-01) TWA 590 mg/m3 200 ppm STEL 885 mg/m3 300 ppm OSHA PEL (1993-06-30) TWA 590 mg/m3 200 ppm NIOSH REL (1994-06-01) TWA 590 mg/m3 200 ppm STEL 885 mg/m3 300 ppm STEL 885 mg/m3 200 ppm STEL 885 mg/m3 200 ppm STEL 885 mg/m3 300 ppm STEL 885 mg/m3 200 ppm STEL 885 mg/m3 300 ppm
Appropriate engineering controls Environmental exposure controls	 Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of

NEC AM100 GRAY

<u>PolyOne</u>

Version Number 1.5	Page 8 of 19
Revision Date 11/07/2018	Print Date 12/08/2018
	environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product., When there is a risk of ignition from static electricity, wear anti-static protective clothing., For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

NEC AM100 GRAY

Version Number 1.5 Revision Date 11/07/2018

<u>PolyOne</u>

Page 9 of 19 Print Date 12/08/2018

Appearance

Physical state	:	liquid [liquid]
Color	:	GREY
Odor	:	Not available.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Closed cup: -9 °C (16 °F)
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n-	:	Not available.
octanol/water		
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	Dynamic: Not available.
-		Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	 Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	 Avoid contact with acetal homopolymers and acetyl homopolymers during processing. Reactive or incompatible with the following materials:
	9/19



NEC AM100 GRAY

Version Number 1.5 Revision Date 11/07/2018

Page 10 of 19 Print Date 12/08/2018

		oxidizing materials
Hazardous decomposition	:	Under normal conditions of storage and use, hazardous decomposition
products		products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure		
Carbon black						
	LD50 Oral	Rat	15,400 mg/kg	-		
Remarks - Inhalation:	No applicable toxi	No applicable toxicity data				
Remarks - Dermal:	No applicable toxi	No applicable toxicity data				
Titanium dioxide						
Remarks - Oral:	No applicable toxicity data					
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h		
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-		
Methyl ethyl ketone						
	LD50 Oral	Rat	2,737 mg/kg	-		
Remarks - Inhalation:	No applicable toxicity data					
	LD50 Dermal	Rabbit	6,480 mg/kg	-		
Conclusion/Summary	: Mixtu	re.Not fully tested.				

Conclusion/Summary

Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium dioxide	Skin - Mild irritant	Human		72 hrs	-
Methyl ethyl ketone	Skin - Mild irritant	Rabbit		24 hrs	-
	Skin - Moderate irritant	Rabbit		24 hrs	-
	Skin - Mild irritant	Rabbit		24 hrs	-
Conclusion/Summary					
Skin	: M	lixture.Not ful	ly tested.		
Eyes : Mixture.Not fully tested.					
Respiratory	: M	lixture.Not ful	ly tested.		
		10/19	9		

NEC AM100 GRAY

Version Number 1.5 Revision Date 11/07/2018 Page 11 of 19 Print Date 12/08/2018

Sensitization				
Conclusion/Summary Skin Respiratory	Mixture.Not fully tested.Mixture.Not fully tested.			
Mutagenicity				
Conclusion/Summary	:	Mixture.No	Not fully tested.	
Carcinogenicity				
Conclusion/Summary Classification	:	Mixture.No	Not fully tested.	
Product/ingredient name	OSHA	IARC	C NTP	
Carbon black		2B		
Titanium dioxide		2B		
<u>Reproductive toxicity</u> Conclusion/Summary	:	Mixture.No	Not fully tested.	
Teratogenicity				
Conclusion/Summary	:	Mixture.No	Not fully tested.	
Specific target organ toxicity Not available.	v (single exp	<u>osure)</u>		
Specific target organ toxicity Not available.	v (repeated o	exposure)		
Aspiration hazard Not available.				
Information on likely routes exposure	of :	Not availab	able.	
Potential acute health effects				
Eye contact	:	Causes seri	rious eye irritation.	
Inhalation			i significant effects or critical hazards.	
Skin contact			in irritation.	
Ingestion			n significant effects or critical hazards.	
	•		-	
			11/19	



NEC AM100 GRAY

Version Number 1.5 Revision Date 11/07/2018 PolyOne

Page 12 of 19 Print Date 12/08/2018

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	:	Adverse symptoms may include the following: pain or irritation watering
Inhalation	:	redness No specific data.
Skin contact	:	Adverse symptoms may include the following:
		irritation
		redness
Ingestion	:	No specific data.
Delayed and immediate effects as w	<u>ell as</u>	chronic effects from short and long-term exposure
Short term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	No known significant effects or critical hazards.
Developmental effects	:	No known significant effects or critical hazards.
Fertility effects	:	No known significant effects or critical hazards.
Numerical measures of toxicity		

Acute toxicity estimates

Route	ATE value
Oral	4,507.5 mg/kg



NEC AM100 GRAY

Version Number 1.5 Revision Date 11/07/2018 Page 13 of 19 Print Date 12/08/2018

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Carbon black			
Remarks - Acute - Fish:	No applicable toxicity data		
	Acute EC50 37.563 Mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
Remarks - Acute - Aquatic	Acute		
invertebrates.:			
Remarks - Acute - Aquatic	No applicable toxicity data		
plants:			
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:			
Titanium dioxide			1
	Acute LC50 > 1,000 Mg/l Marine	Fish - Fish	96 h
	water		
Remarks - Acute - Fish:	Acute		
	Acute LC50 3 Mg/l Fresh water	Aquatic invertebrates.	48 h
		Crustaceans	
Remarks - Acute - Aquatic	Acute		
invertebrates.:			40.1
	Acute LC50 6.5 Mg/l Fresh water	Aquatic invertebrates.	48 h
	A	Daphnia	
Remarks - Acute - Aquatic invertebrates.:	Acute		
	No applicable terricity data		
Remarks - Acute - Aquatic	No applicable toxicity data		
plants:	No appliaghla toxicity data		
Remarks - Chronic - Fish: Remarks - Chronic -	No applicable toxicity data No applicable toxicity data		
Aquatic invertebrates.:	No applicable toxicity data		
Methyl ethyl ketone	1		
	Acute LC50 3,220 Mg/l Fresh	Fish - Fish	96 h
	water	1 1511 - 1 1511	70 11
Remarks - Acute - Fish:	Acute	1	1
Actinar https:// Acture = 11511.	Acute EC50 5.091 Mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
Remarks - Acute - Aquatic	Acute		1
invertebrates.:			
	Acute EC50 > 500 Mg/l Marine	Aquatic plants - Algae	96 h
	water	1	



NEC AM100 GRAY

Version Number 1.5 Revision Date 11/07/2018 Page 14 of 19 Print Date 12/08/2018

Remarks - Acute - Aquatic	Acute
plants:	
Remarks - Chronic - Fish:	No applicable toxicity data
Remarks - Chronic -	No applicable toxicity data
Aquatic invertebrates.:	
Conclusion/Summary	: Not available.
Persistence and degradability	<u>v</u>

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Methyl ethyl ketone	0.29	-	low

Mobility in soil

Soil/water partition coefficient	:	Not available.
(KOC) Other adverse effects	:	No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods The generation of waste should be avoided or minimized wherever : possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14/19



NEC AM100 GRAY

Version Number 1.5 Revision Date 11/07/2018 Page 15 of 19 Print Date 12/08/2018

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Listed

Ingredient	CAS #	Status	Reference number
Methyl ethyl ketone	78-93-3	Listed	

Section 14. Transport information

U.S.DOT 49CFR	
Ground/Air/Water	
Proper Shipping Name:	Resin solution
Technical Name:	
Hazard Class / Division	3
UN Number	UN1866
Packing Group	II
Label Required	3
-	
International Air	
ICAO/IATA	
Proper Shipping Name:	Resin solution
Technical Name:	
Hazard Class / Division	3
UN Number	UN1866
Packing Group	II
Label Required	3
-	
International Water	
IMO/IMDG	
Proper Shipping Name:	Resin solution
Technical Name:	
Hazard Class / Division	3
UN Number	UN1866
Packing Group	II
Label Required	3
1	

Section 15. Regulatory information

U.S. Federal regulations	 United States - TSCA 12(b) - Chemical export notification: None of the components are listed. United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed
	15/19

NEC AM100 GRAY

Version Number 1.5

ŀ	olyOne	~
_		

Page 16 of 19

	Drint Data 12/08/2018
Revision Date 11/07/2018	Print Date 12/08/2018
	Heited States TSCA (C) Deignite wide novierne Nat listed
	United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not listed
	United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed
	United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed
	United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed
	United States - TSCA 8(a) - Chemical Fisk Fulles. Not listed
	United States - TSCA 8(a) - Chemical Data Reporting (CDR): No determined
	United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed
	United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed
	United States - TSCA 8(d) - Health and safety studies: Not listed
	United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Phthalocyanine Blue
	United States - EPA Clean water act (CWA) section 311 -
	Hazardous substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental
	release prevention - Flammable substances: Not listed
	United States - EPA Clean air act (CAA) section 112 - Accidental
	release prevention - Toxic substances: Not listed
	United States - Department of commerce - Precursor chemical: Not listed

Clean Air Act Section 112(b)	:	Not listed
Hazardous Air Pollutants (HAPs)		
Clean Air Act Section 602 Class I	:	Not listed
Substances		
Clean Air Act Section 602 Class II	:	Not listed
Substances		
DEA List I Chemicals (Precursor	:	Not listed
Chemicals)		
DEA List II Chemicals (Essential	:	Listed
Chemicals)		

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name CAS-No. RQ for component
--



NEC AM100 GRAY

Version Number 1.5 Revision Date 11/07/2018 Page 17 of 19 Print Date 12/08/2018

Methyl ethyl ketone	78-93-3	5,000 lb(s) 2,270 kg 2,270 kg 5,000 lb(s)	
---------------------	---------	--	--

SARA 311/312

Classification

FLAMMABLE LIQUIDS Category 2SKIN IRRITATION Category 2EYE IRRITATION Category 2A

Composition/information on ingredients

Name	%	Classification
Carbon black	0 - 0.3	СН
Titanium dioxide	0.3 - 1	СН
Methyl ethyl ketone	50 - 75	F, AH

<u>SARA 313</u>

Not applicable.

State regulations	
Massachusetts	None of the components are listed.
New York	: The following components are listed: Methyl ethyl ketone
New Jersey	: The following components are listed: Carbon black Titanium dioxide Methyl ethyl ketone
Pennsylvania	: The following components are listed: Methyl ethyl ketone
	Titanium dioxide

:

Carbon black

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, Carbon black, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.



NEC AM100 GRAY

Version Number 1.5 Revision Date 11/07/2018 Page 18 of 19 Print Date 12/08/2018

Ingredient name	No significant risk level	Maximum acceptable dosage level
Titanium dioxide	No.	No.
Carbon black	No.	No.

United States inventory (TSCA 8b)	:	All components are listed or exempted.
Canada inventory	:	All components are listed or exempted.
International regulations		
Inventory list		
Australia	:	Not determined.
Canada	:	All components are listed or exempted.
China	:	Not determined.
Europe inventory	:	All components are listed or exempted.
Japan	:	Not determined.
New Zealand	:	Not determined.
Philippines	:	Not determined.
Republic of Korea	:	Not determined.
Taiwan	:	All components are listed or exempted.
Turkey	:	Not determined.
United States	:	All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	2
Flammability		3
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. <u>History</u>

NEC AM100 GRAY

Version Number 1.5 Revision Date 11/07/2018

<u>PolyOne</u>

Page 19 of 19 Print Date 12/08/2018

Date of printing Date of issue/Date of revision Date of previous issue Version	:	12/08/2018 11/07/2018 05/16/2018 1.5
Key to abbreviations	:	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
References	:	Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.