PolvOne

MATERIAL SAFETY DATA SHEET **STAN-TONE MB-31875 GRAY**

Version Number 1.2 Revision Date 03/30/2014 Page 1 of 8 Print Date 4/8/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	STAN-TONE MB-31875 GRAY
Product code	:	FO20023631
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Titanium dioxide	13463-67-7	1 - 5
Silica, amorphous, precipitated and gel	112926-00-8	5 - 10
Carbon black	1333-86-4	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne

MATERIAL SAFETY DATA SHEET **STAN-TONE MB-31875 GRAY**

Version Number 1.2 Revision Date 03/30/2014 Page 2 of 8 Print Date 4/8/2014

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media	 not applicable not applicable Not relevant Water spray, Dry powder, Foam, Carbon dioxide (CO2).
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
D 1	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET **STAN-TONE MB-31875 GRAY**

ision Date 03/30/2014		Print Date 4/8/2
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXP	OSUI	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required when handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this material.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.
Exposure limit(s)		

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **STAN-TONE MB-31875 GRAY**

Version Number 1.2 Revision Date 03/30/2014 Page 4 of 8 Print Date 4/8/2014

Components	Value	Exposure time		Exposure type	List:
Carbon black	3.5 mg/m3	Recommended exp limit (REL):			NIOSH
	0.1 mg/m3	Recommended exp limit (REL):	osure		NIOSH
	3.5 mg/m3	PEL:			OSHA Z1
	3.5 mg/m3	Time Weighted Av (TWA):	•		OSHA Z1A
	3.5 mg/m3	Time Weighted Av (TWA):	_		MX OEL
	7 mg/m3	Short Term Exposure (STEL):	e Limit		MX OEL
	3 mg/m3	Time Weighted Av (TWA):	erage	Inhalable fraction.	ACGIH
Silica, amorphous, 6 mg/r precipitated and gel		Time Weighted Av (TWA):	erage		OSHA Z1A
· · · · · ·	10 mg/m3	Time Weighted Av (TWA):	erage		MX OEL
	0.8 mg/m3	Time Weighted Av (TWA):	erage		Z3
Titanium dioxide	10 mg/m3	/m3 Time Weighted Average (TWA):			ACGIH
	15 mg/m3	PEL:		Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Av (TWA):	erage	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Av (TWA):	_	as Ti	MX OEL
	20 mg/m3	Short Term Exposure (STEL):	e Limit	as Ti	MX OEL
	9. PHYSIC	CAL AND CHEMIC	AL PRO	PERTIES	
Form	: solid		Evene	aration rate : No	t applicable
Appearance	: pellets, Slabs, sheets				ot determined
Colour	: GREY		Bulk de		ot established
Odour		acteristic rubber odor			t applicable
Melting point/range		determined			t applicable
Boiling Point:		pplicable	pH		t applicable
Water solubility	: insol		r	. 10	approuoio
	10. 8	STABILITY AND RI	EACTIV	ITY	

10. STABILITY AND REACTIVITY

Stability	:	Stable

Hazardous Polymerization : Will not occur.

Conditions to avoid

: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.

MATERIAL SAFETY DATA SHEET **STAN-TONE MB-31875 GRAY**

Version Number 1.2 Revision Date 03/30/2014 Page 5 of 8 Print Date 4/8/2014

Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
112926-00-8	Silica, amorphous, precipitated and gel	Irritant	Respiratory system, Eyes.
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

PolvOne

MATERIAL SAFETY DATA SHEET STAN-TONE MB-31875 GRAY

Version Number 1.2 Revision Date 03/30/2014 Page 6 of 8 Print Date 4/8/2014

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

12. ECOLOGICAL INFORMATION

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO/IMDG (maritime)	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
-	
OSHA Status	: Classified as hazardous based on components.

PolyOne

MATERIAL SAFETY DATA SHEET **STAN-TONE MB-31875 GRAY**

Version Number 1.2 Revision Date 03/30/2014

TSCA Status

Page 7 of 8 Print Date 4/8/2014

: All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Aluminum oxide	1344-28-1	0.10 - 1.00	

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
1333-86-4	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Not determined
China IECS	:	Listed
Europe EINECS	:	Listed

:

MATERIAL SAFETY DATA SHEET **STAN-TONE MB-31875 GRAY**

Version Number 1.2 Revision Date 03/30/2014

	age 8 of 8
Print Date	4/8/2014

Japan ENCS	: Not determined	
Korea KECI	: Listed	
Philippines PICCS	: Listed	

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.