



POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

STAN-TONE HCC-33207 GHOST WHITE

Version Number 1.2
Revision Date 03/26/2014

Page 1 of 7
Print Date 4/2/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION
8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone : 1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure
number or accident).
Product name : STAN-TONE HCC-33207 GHOST WHITE
Product code : FO20025324
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Propylene glycol diamine, 2-amino-, diether with Propylene	9046-10-0	30 - 60
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	60 - 100

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. This product may contain amine catalyst. Please note these catalysts can be corrosive. Severe skin, eye, and irritation or damage may result with direct contact.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation : Vapors or mists from heating or from poorly ventilated areas may cause irritation. Nasal discharge, coughing or discomfort to the nose and throat may occur. Prolonged overexposure may result in lung damage.

Ingestion : Can cause burning of mouth, throat, and stomach . Nausea, vomiting,

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****STAN-TONE HCC-33207 GHOST WHITE**Version Number 1.2
Revision Date 03/26/2014Page 2 of 7
Print Date 4/2/2014

- diarrhea, thirst, weakness and collapse may occur. Aspiration may occur during swallowing or vomiting, resulting in lung damage.
- Eyes : Can cause severe irritation or chemical burns to the eyes with excessive tearing and redness. May cause blindness.
- Skin : May cause severe irritation or chemical burns with possible tissue destruction. Short term adverse effects are not expected from brief skin contact with immediate first aid response.

Chronic exposure : Refer to Section 11 for Toxicological Information.

Medical Conditions : None known.

Aggravated by Exposure:

4. FIRST AID MEASURES

- Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
- Ingestion : Do not induce vomiting without medical advice. Seek medical attention if necessary.
- Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
- Skin : Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIREFIGHTING MEASURES

- Flash point : no data available
- Flammable Limits
- Upper explosion limit : no data available
 - Lower explosion limit : no data available
- Auto-ignition temperature : Not applicable
- Suitable extinguishing media : Carbon dioxide blanket, Water spray, Dry powder, Foam.
- Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
- Unusual Fire/Explosion Hazards : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

STAN-TONE HCC-33207 GHOST WHITE

Version Number 1.2
Revision Date 03/26/2014

Page 3 of 7
Print Date 4/2/2014

- Environmental precautions : The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
- Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

- Handling : Heat only in areas with appropriate exhaust ventilation. Prolonged heating may result in product degradation.
- Storage : Keep containers tightly closed in a dry, cool and well-ventilated place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Respiratory protection : In high vapour concentrations, use respiratory protection with independent air supply.
- Eye/Face Protection : Wear goggles or face shield during operations that present a splash potential. Do not wear contact lenses.
- Hand protection : Protective gloves
- Skin and body protection : Long sleeved shirts and long pants are adequate for normal handling. Where operations present a splash or spill potential, employees should wear chemically resistant clothing, boots, apron, gloves, and eye/face protection.
- Additional Protective Measures : Safety shoes
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
- Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

STAN-TONE HCC-33207 GHOST WHITE

Version Number 1.2
Revision Date 03/26/2014

Page 4 of 7
Print Date 4/2/2014

Components	Value	Exposure time	Exposure type	List:
Silica, amorphous	6 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: liquid	Evaporation rate	: Not established
Appearance	: liquid, Viscous liquid dispersion	Specific Gravity	: Not determined
Colour	: WHITE	Bulk density	: Not applicable
Odour	: very faint	Vapour pressure	: Not determined
Melting point/range	: not applicable	Vapour density	: Heavier than air.
Boiling Point:	: not applicable	pH	: Not determined
Water solubility	: immiscible		

10. STABILITY AND REACTIVITY

Stability	: Stable
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	: Carbon dioxide (CO ₂), carbon monoxide (CO), oxides of nitrogen (NO _x), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

STAN-TONE HCC-33207 GHOST WHITE

Version Number 1.2
Revision Date 03/26/2014

Page 5 of 7
Print Date 4/2/2014

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
9046-10-0	Propylene glycol diamine, 2-amino-, diether with Propylene	Toxic	Refer to LC50 / LD50 Data on MSDS..
		Corrosive	Eyes, Skin.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
9046-10-0	Propylene glycol diamine, 2-amino-, diether with Propylene	Oral LD50 Dermal LD50	242 mg/kg 360 mg/kg	rat rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

- Persistence and degradability : Not readily biodegradable.
- Environmental Toxicity : Environmental toxicity has not been established for this mixture as a whole.
- Bioaccumulation Potential : no data available
- Additional advice : no data available

13. DISPOSAL CONSIDERATIONS

- Product : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

STAN-TONE HCC-33207 GHOST WHITE

Version Number 1.2
Revision Date 03/26/2014

Page 6 of 7
Print Date 4/2/2014

classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification
Proper Shipping Name: Corrosive liquids, n.o.s.
Technical Name: Polyoxypropylenediamine
Hazard Class / Division 8
UN Number UN1760
Packing Group III
Label Required 8

ICAO/IATA Refer to specific regulation.
IMO/IMDG (maritime) Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition : Not applicable
65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

STAN-TONE HCC-33207 GHOST WHITE

Version Number 1.2
Revision Date 03/26/2014

Page 7 of 7
Print Date 4/2/2014

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

not applicable

WHMIS Classification : D1B

WHMIS Ingredient Disclosure List

CAS-No.
7631-86-9

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Listed

China IECS : Listed

Europe EINECS : Not determined

Japan ENCS : Listed

Korea KECI : Listed

Philippines PICCS : Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.